

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.10.2021

Version: 6.01

Revision: 22.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** SONAX XTREME WHEEL CLEANER PLUS**Article number:** 02303410**1.2 Relevant identified uses of the substance or mixture and uses advised against****Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC35 Washing and cleaning products (including solvent based products)**Application of the substance / the mixture** Car care product**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + 49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Aerosol 3 H229 Pressurised container: May burst if heated.

Acute Tox. 4 H302 Harmful if swallowed.

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS07

Signal word Warning**Hazard-determining components of labelling:**

sodium mercaptoacetate solution (46%)

Hazard statements

H229 Pressurised container: May burst if heated.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

(Contd. on page 2)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.10.2021

Version: 6.01

Revision: 22.04.2021

Trade name: SONAX XTREME WHEEL CLEANER PLUS

(Contd. of page 1)

P261 Avoid breathing spray.
 P280 Wear protective gloves.
 P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

11 % by mass of the contents are flammable

Labelling of packages where the contents do not exceed 125 ml**Hazard pictograms**

GHS07

Signal word Warning**Hazard-determining components of labelling:**

sodium mercaptoacetate solution (46%)

Hazard statements

H229 Pressurised container: May burst if heated.

H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P280 Wear protective gloves.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**Determination of endocrine-disrupting properties** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Preparation of propellant, water and solvents**Dangerous components:**

CAS: 367-51-1 EINECS: 206-696-4 Reg.nr.: 01-2119968564-24-xxxx	sodium mercaptoacetate solution (46%) ⚠ Acute Tox. 4, H302; Skin Sens. 1B, H317	20-<25%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	3-<5%
CAS: 126-92-1 EINECS: 204-812-8 Reg.nr.: 01-2119971586-23-xxxx	sodium etasulfate ⚠ Eye Dam. 1, H318; ⚠ Skin Irrit. 2, H315 Specific concentration limits: Eye Dam. 1; H318: C ≥ 20 % Eye Irrit. 2; H319: 10 % ≤ C < 20 %	1-<3%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<3%

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.10.2021

Version: 6.01

Revision: 22.04.2021

Trade name: SONAX XTREME WHEEL CLEANER PLUS

(Contd. of page 2)

Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons	≥5 - <15%
anionic surfactants	<5%
perfumes, limonene, methylisothiazolinone, benzisothiazolinone, sodium pyrithione	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Induce vomiting only, if affected person is fully conscious.

Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

sensitization

Headache

Dizziness

Drowsiness

Gastric or intestinal disorders

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.10.2021

Version: 6.01

Revision: 22.04.2021

Trade name: SONAX XTREME WHEEL CLEANER PLUS

(Contd. of page 3)

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Prevent any seepage into the ground.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from oxidising agents.

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 106-97-8 butane

WEL (Great Britain)	Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene)
---------------------	---

Regulatory information WEL (Great Britain): EH40/2011

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Hand protection

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Natural rubber, NR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥480min)

Eye/face protection Not required in normal cases

GB

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.10.2021

Version: 6.01

Revision: 22.04.2021

Trade name: SONAX XTREME WHEEL CLEANER PLUS

(Contd. of page 4)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Fluid
Colour:	Light red
Odour:	Characteristic
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	100 °C (Active ingredient data)
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Auto-ignition temperature:	Product is not selfigniting.
Decomposition temperature:	Not determined.
pH at 20 °C	7.0 - 8.0 (Active ingredient data)
Viscosity:	
Kinematic viscosity	Not determined.
Solubility	
water:	Fully miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	1.11 - 1.12 g/cm ³ (Active ingredient data)
Relative density	Not determined.
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Aerosol
Important information on protection of health and environment, and on safety.	
Explosive properties:	Not determined.
Change in condition	
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	
Pressurised container: May burst if heated.	
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

GB

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.10.2021

Version: 6.01

Revision: 22.04.2021

Trade name: SONAX XTREME WHEEL CLEANER PLUS

(Contd. of page 5)

SECTION 10: Stability and reactivity**10.1 Reactivity** No dangerous reactions known.**10.2 Chemical stability** Stable under normal conditions.**10.3 Possibility of hazardous reactions** No dangerous reactions known.**10.4 Conditions to avoid**

An increase in pressure may lead to bursting.

Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents**10.6 Hazardous decomposition products:** No dangerous decomposition products known.**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Harmful if swallowed.

LD/LC50 values relevant for classification:

Oral	ATE	1,607 mg/kg (Additivity formula)
Dermal	ATE	10,978 mg/kg (Additivity formula)

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

Oral	LD50	200-500 mg/kg (rat) (OECD 423 (Conc. 46%))
Dermal	LD50	1,000-2,000 mg/kg (rat) (OECD 402 (Conc. 98%))

CAS: 106-97-8 butane

Inhalative	LC50/4d	658 mg/l (rat)
------------	---------	----------------

CAS: 126-92-1 sodium etasulfate

Oral	LD50	2,840 mg/kg (Ratte) (OECD 401)
Dermal	LD50	>2,000 mg/kg (Ratte) (OECD 402)

Skin corrosion/irritation Based on available data, the classification criteria are not met.**Serious eye damage/irritation** Based on available data, the classification criteria are not met.**Respiratory or skin sensitisation**

Result: Causes sensitization

Species: mouse

Method: OECD 429

May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**11.2 Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information**12.1 Toxicity** There are no ecotoxicological data available on this mixture.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 08.10.2021

Version: 6.01

Revision: 22.04.2021

Trade name: SONAX XTREME WHEEL CLEANER PLUS

(Contd. of page 6)

Aquatic toxicity:

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

LC50 / 96h	>100 mg/l (Oncorhynchus mykiss) (OECD 203 (Subs. thioglycolic acid))
LC50 / 48h	880 mg/l (Leuciscus idus) (DIN 38412 / 15 (Subs. thioglycolic acid))
EC50 / 48h	38 mg/l (Daphnia magna) (84/449/EWG (Subs. thioglycolic acid))
EC50 / 72h	13 mg/l (Pseudokirchneriella subcapitata) (OECD 201 (Subs. thioglycolic acid))

12.2 Persistence and degradability

The surface-active substances contained in the product meet the requirement of the EU Detergent Regulation (EC/648/2004) for ultimate biodegradability for surfactants in detergents.

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

Biodegradation 67 % (28d OECD 301d (thioglycolic acid))

12.3 Bioaccumulative potential

CAS: 367-51-1 sodium mercaptoacetate solution (46%)

log POW ≤2.99 log POW (20°C OECD 107 (thioglycolic acid))

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG

UN1950

IATA

Product not approved for air transport!

14.2 UN proper shipping name

ADR/RID/ADN

1950 AEROSOLS

IMDG

AEROSOLS

14.3 Transport hazard class(es)

ADR/RID/ADN



Class

2 5A Gases.

Label

2.2

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.10.2021

Version: 6.01

Revision: 22.04.2021

Trade name: SONAX XTREME WHEEL CLEANER PLUS

(Contd. of page 7)

IMDG

Class 2 Gases.
Label 2.2

14.4 Packing group
ADR/RID/ADN Void

14.5 Environmental hazards:
Marine pollutant: No

14.6 Special precautions for user Warning: Gases.

14.7 Maritime transport in bulk according to IMO instruments Not applicable.

Transport/Additional information:

ADR/RID/ADN
Limited quantities (LQ) 1L
Transport category 3
Tunnel restriction code E

UN "Model Regulation": UN1950, AEROSOLS, 2.2

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations:****Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

Classification according to Regulation (EC) No 1272/2008

Aerosols	On basis of test data
----------	-----------------------

Acute toxicity - oral Skin sensitisation	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
---	--

Version number of previous version: 6.00**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 08.10.2021

Version: 6.01

Revision: 22.04.2021

Trade name: SONAX XTREME WHEEL CLEANER PLUS

(Contd. of page 8)

*ATE: acute toxicity estimate**ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**IOELV = indicative occupational exposure limit values**Flam. Gas 1A: Flammable gases – Category 1A**Aerosol 3: Aerosols – Category 3**Press. Gas (Comp.): Gases under pressure – Compressed gas**Acute Tox. 4: Acute toxicity – Category 4**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Skin Sens. 1: Skin sensitisation – Category 1**Skin Sens. 1B: Skin sensitisation – Category 1B***Sources**

"Regulation (EC) Nr. 1907/2006 (REACH), 1272/2008 (CLP), 648/2004 (Detergents) in the respective valid version. National occupation exposure limits for each country in the respective valid version. Transportation regulations according to ADR, RID, IMDG, IATA in the respective valid version."

** Data compared to the previous version altered.*

GB