

Printing date 18.09.2024 Version: 3.00 (replaces version 2.05) Revision: 02 11 2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: SONAX PROFILINE CeramicCoating CC36 - GlossCoat (2)

Article number:

02362410,

B02230000

(GlossCoat (2) for SONAX PROFILINE CeramicCoating CC36 [02369410])

UFI: QFR0-C06R-700A-EKNV

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Car care product

Sealing

Consumer uses: Private households / general public / consumers

Professional uses

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

#### Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

# SECTION 2: Hazards identification

# 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 3 H229 Pressurised container: May burst if heated.

#### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms Void

Signal word Warning

Hazard statements

H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

3 % by mass of the contents are flammable

2.3 Other hazards

Results of PBT and vPvB assessment

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

(Contd. on page 2)



Printing date 18.09.2024 Version: 3.00 (replaces version 2.05) Revision: 02.11.2021

Trade name: SONAX PROFILINE CeramicCoating CC36 - GlossCoat (2)

(Contd. of page 1)

#### vPvB.

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

#### Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Description: Preparation made from gas under pressure and water-based cleaning emulsion

Dangerous components:			
EC No 918-167-1 Reg.nr.: 01-2119472146-39-xxxx	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics Alternative CAS numbers: 90622-57-4, 64742-48-9      Flam. Liq. 3, H226;  Asp. Tox. 1, H304; Aquatic Chronic 4, H413	1-<3%	
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide ♦ Press. Gas (Ref. Liq.), H281	1-<3%	
EC No 934-956-3 Reg.nr.: 01-2119827000-58-xxxx	Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7  \$\infty\$ Asp. Tox. 1, H304	1-<3%	

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air.

After skin contact: Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

#### SECTION 5: Firefighting measures

#### 5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

### 5.3 Advice for firefighters

#### Protective equipment:

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

#### Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

#### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation (Contd. on page 3)



Printing date 18.09.2024 Version: 3.00 (replaces version 2.05) Revision: 02.11.2021

Trade name: SONAX PROFILINE CeramicCoating CC36 - GlossCoat (2)

(Contd. of page 2)

#### For non-emergency personnel

Do not inhale gases / fumes / aerosols.

The usual precautionary measures are to be adhered to when handling chemicals.

For emergency responders Wear protective equipment. Keep unprotected persons away.

#### 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

#### 6.3 Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

Dispose contaminated material as waste according to section 13.

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

# **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

#### Information about fire - and explosion protection:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

# 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

### Requirements to be met by storerooms and receptacles:

Prevent any seepage into the ground.

Observe official regulations on storing packagings with pressurised containers.

#### Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

#### Further information about storage conditions:

Protect from heat and direct sunlight.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Store receptacle in a well ventilated area. Recommended storage temperature: 20 °C

7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

#### CAS: 124-38-9 carbon dioxide

WEL (Great Britain) Short-term value: 27400 mg/m³, 15000 ppm

Long-term value: 9150 mg/m³, 5000 ppm Long-term value: 9000 mg/m³, 5000 ppm

OEL (Ireland) Long-term value: 9000 mg/m³, 5000 ppm

# Regulatory information

IOELV (EU)

WEL (Great Britain): EH40/2020 IOELV (EU): (EU) 2019/1831

OEL (Ireland): 2020 CoP for the Safety, Health and Welfare at Work

Additional information: The lists valid during the making were used as basis.

#### 8.2 Exposure controls

#### Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

(Contd. on page 4)



Printing date 18.09.2024 Version: 3.00 (replaces version 2.05) Revision: 02.11.2021

Trade name: SONAX PROFILINE CeramicCoating CC36 - GlossCoat (2)

(Contd. of page 3)

Individual protection measures, such as personal protective equipment General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work. Keep away from foodstuffs, beverages and feed.

Respiratory protection: Not required in normal cases

Ensure good ventilation/exhaustion at the workplace. Hand protection Not required in normal cases. Eye/face protection Not required in normal cases

# SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

**General Information** 

Physical state Fluid Colour: White Odour: Odourless Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

100 °C (CAS: 7732-18-5 water) range Flammability Product is not flammable.

Lower and upper explosion limit

Not applicable Lower: Upper: Not applicable

Flash point: Not applicable, as aerosol.

Decomposition temperature: Not determined.

pH at 20 °C

(Active ingredient data)

Viscosity:

Kinematic viscosity at 40 °C <20.5 mm<sup>2</sup>/s

(Active ingredient data)

Solubility

water: Partly miscible. Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C:

Density and/or relative density

23 hPa (CAS: 7732-18-5 water)

0.99-1.01 g/cm<sup>3</sup> Density at 20 °C:

(Active ingredient data) Not determined. Vapour density

9.2 Other information

Appearance:

Form: Aerosol

Important information on protection of health and

environment, and on safety.

Ignition temperature: Not determined.

Explosive properties: Product does not present an explosion hazard.

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard classes

**Explosives** Flammable gases

Aerosols Negative ignition distance test in line with 31.4 UN

RTGD, handbook on test methods and criteria. Negative enclosed space ignition test in line with 31.5

UN RTDG, handbook on test methods and criteria.

Pressurised container: May burst if heated. Void

Oxidising gases Gases under pressure Void Flammable liquids Void

(Contd. on page 5)



Flammable solids

Pyrophoric liquids

Pyrophoric solids

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Desensitised explosives

gases in contact with water

# Safety data sheet according to UK REACH

Printing date 18.09.2024 Version: 3.00 (replaces version 2.05) Revision: 02.11.2021

Trade name: SONAX PROFILINE CeramicCoating CC36 - GlossCoat (2)

(Contd. of page 4) Void Self-reactive substances and mixtures Void Void Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable Void Void Void Void Void Void

### SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions known.
- 10.2 Chemical stability Stable under normal conditions.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

See Section 7 for information on safe handling.

- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	LD/LC50 values relevant for classification:		
Hydrocari	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)	
Inhalative	LC50 / 4h	>5,000 mg/m³ (rat) (OECD 403)	
Hydrocari	Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)	
Inhalative	LC50 / 4h	>5.266 mg/m³ (rat) (OECD 403)	

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

(Contd. on page 6)



Printing date 18.09.2024 Version: 3.00 (replaces version 2.05) Revision: 02.11.2021

Trade name: SONAX PROFILINE CeramicCoating CC36 - GlossCoat (2)

(Contd. of page 5)

None of the ingredients is listed.

# SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxic	Aquatic toxicity:		
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics			
LLO 96 h	1,000 mg/l (Oncorhynchus mykiss)		
NOELR 72 h	>1,000 mg/l (Pseudokirchneriella subcapitata)		
NOELR 21d	≥1 mg/l (Daphnia magna)		
NOEC / 28d	0.209 mg/l (Oncorhynchus mykiss)		
ELO 48 h	>1,000 mg/l (Daphnia magna)		
ELO 72 h	>1,000 mg/l (Pseudokirchneriella subcapitata)		
Hydrocarbor	Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics		
LC50 / 4 d	>1,028 mg/l (Scophtalamus maximus) (OECD 203)		
LC50 / 48h	>3,193 mg/l (Acartia tonsa)		
NOEC / 21 d	>1,000 mg/l (Daphnia magna)		
NOEC / 28d	>1,000 mg/l (Oncorhynchus mykiss)		
LC50 / 3 d	>10,000 mg/l (Skeletonema costatum)		

#### 12.2 Persistence and degradability

#### Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Biodegradation 74 %

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

#### 12.5 Results of PBT and vPvB assessment

#### PBT:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

#### vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

# 12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

The product does not contain substances with endocrine disrupting properties.

### 12.7 Other adverse effects

#### Additional ecological information:

General notes: The product may not be released into the environment without control.

# SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Recommendation Waste must be disposed of while observing the local, official regulations.

#### European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10\* packaging containing residues of or contaminated by hazardous substances

#### Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

GB



Printing date 18.09.2024 Version: 3.00 (replaces version 2.05) Revision: 02.11.2021

Trade name: SONAX PROFILINE CeramicCoating CC36 - GlossCoat (2)

(Contd. of page 6)

# SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR/RID/ADN 1950 AEROSOLS IMDG AEROSOLS

IATA AEROSOLS, non-flammable

#### 14.3 Transport hazard class(es)

#### ADR/RID/ADN



Class 2 5A Gases.

Label 2.2

IMDG, IATA



Class 2.2 Gases.

Label 2.2

14.4 Packing group

ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Warning: Gases.

#### Transport/Additional information:

ADR/RID/ADN

Limited quantities (LQ) 1L Transport category 3 Tunnel restriction code E

UN "Model Regulation": UN 1950 AEROSOLS, 2.2

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) 2.94 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

#### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

#### National regulations:

#### Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

(Contd. on page 8)



Printing date 18.09.2024 Version: 3.00 (replaces version 2.05) Revision: 02.11.2021

Trade name: SONAX PROFILINE CeramicCoating CC36 - GlossCoat (2)

(Contd. of page 7)

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

H226 Flammable liquid and vapour.

H281 Contains refrigerated gas; may cause cryogenic burns or injury.

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

# Classification according to Regulation (EC) No 1272/2008

Aerosols, Section 2.3.1 On basis of test data

Date of previous version: 22.04.2021 Version number of previous version: 2.05

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration LC = letal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent IOELV = indicative occupational exposure limit values Aerosol 3: Aerosols – Category 3

Press. Gas (Ref. Liq.): Gases under pressure – Refrigerated liquefied gas

Flam. Liq. 3: Flammable liquids – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

\* Data compared to the previous version altered.