

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.02

Revision: 22.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - BaseCoat (1)

Article number:

02361410,

B02369410

(BaseCoat (1) for SONAX PROFILINE CERAMIC COATING CC 36 [02369410])

UFI: F8N0-M0P1-W000-XY3G

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Car care product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

propan-2-ol

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.02

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - BaseCoat (1)

(Contd. of page 1)

Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear eye protection.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Labelling of packages where the contents do not exceed 125 ml

Marking container <125 ml deviates. Reduced labeling according article 29 and annex I, no. 1.5 CLP-regulation is used.

2.3 Other hazards
Results of PBT and vPvB assessment

PBT:	
CAS: 541-02-6	decamethylcyclopentasiloxane
CAS: 540-97-6	Dodecamethylcyclohexasiloxane
vPvB:	
CAS: 541-02-6	decamethylcyclopentasiloxane
CAS: 540-97-6	Dodecamethylcyclohexasiloxane

Determination of endocrine-disrupting properties Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description: Formulation consisting of pressurised gas and a dispersion of silica particles

Dangerous components:		
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
CAS: 541-02-6 EINECS: 208-764-9 Reg.nr.: 01-2119511367-43-xxxx	decamethylcyclopentasiloxane Non-classified vPvB substance. Non-classified PBT substance.	25-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 64-17-5 EINECS: 200-578-6 Reg.nr.: 01-2119457610-43-xxxx	ethanol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	3-<5%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<3%
CAS: 112-53-8 EINECS: 203-982-0 Reg.nr.: 01-2119485976-15-xxxx	Lauryl alcohol ⚠ Aquatic Acute 1, H400; Aquatic Chronic 2, H411; ⚠ Eye Irrit. 2, H319	1-<3%
CAS: 540-97-6 EINECS: 208-762-8 Reg.nr.: 01-2119517435-42-xxxx	Dodecamethylcyclohexasiloxane Non-classified vPvB substance. Non-classified PBT substance.	1-<3%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.02

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - BaseCoat (1)

(Contd. of page 2)

Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Take affected persons out of danger area and lay down.

Remove soiled clothing

After inhalation:

Supply fresh air; consult doctor in case of complaints.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact:

Generally the product does not irritate the skin.

Wash the areas of skin affected with water and a mild detergent.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.**After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Eye irritation

Drowsiness

Dizziness

Headache

Dizziness

Nausea

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

Foam

Fire-extinguishing powder

Carbon dioxide

Water spray

For safety reasons unsuitable extinguishing agents: Water with full jet**5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

In case of fire, the following can be released:

Carbon monoxide and carbon dioxide

Formaldehyde

Silicon oxides

5.3 Advice for firefighters**Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.02

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - BaseCoat (1)

(Contd. of page 3)

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Prevent any seepage into the ground.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Store receptacle in a well ventilated area.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 67-63-0 propan-2-ol

WEL (Great Britain) Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

CAS: 106-97-8 butane

WEL (Great Britain) Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

CAS: 64-17-5 ethanol

WEL (Great Britain) Long-term value: 1920 mg/m³, 1000 ppm

Regulatory information WEL (Great Britain): EH40/2018

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.02

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - BaseCoat (1)

(Contd. of page 4)

DNELs
CAS: 67-63-0 propan-2-ol

Oral	DNEL	26 mg/kg (consumer) (chronic effects (1d))
Dermal	DNEL	319 mg/kg (consumer) (chronic effects (1d))
		888 mg/kg (worker) (chronic effects (1d))
Inhalative	DNEL	89 mg/m ³ (consumer) (chronic effects)
		500 mg/m ³ (worker) (chronic effects)

CAS: 64-17-5 ethanol

Oral	DNEL	87 mg/kg (consumer) (long-term exposure - systemic effects)
Dermal	DNEL	206 mg/kg bw/day (consumer) (long-term exposure - systemic effects)
		343 mg/kg bw/day (worker) (lon-term exposure - systemic effects)
Inhalative	DNEL	950 mg/m ³ (consumer) (acute short-tem exposure - local effects)
		1,900 mg/m ³ (worker) (acute short-tem exposure - local effects)
		114 mg/m ³ (consumer) (long-term exposure - systemic effects)
	DNEL	950 mg/m ³ (worker) (long-term exposure - systemic effects)

CAS: 112-53-8 Lauryl alcohol

Oral	DNEL	75 mg/kg bw/day (VK)
		75 mg/kg bw/day (VL)
Dermal	DNEL	125 mg/bw/day (worker short-term)
		75 mg/kg bw/day (VK)
Inhalative	DNEL	75 mg/kg bw/day (VL)
		125 mg/kg bw/day (worker long-term)
		65 mg/m ³ (VK)
		65 mg/m ³ (VL)
		220 mg/m ³ (worker short-term)
		220 mg/m ³ (worker long-term)

PNECs
CAS: 67-63-0 propan-2-ol

PNEC	140.9 mg/l (sporadic release)
	2,251 mg/l (STP)
	140.9 mg/l (water (fresh water))
	140.9 mg/l (water (sea water))
PNEC	28 mg/kg (gro)
	552 mg/kg (sediment)

CAS: 64-17-5 ethanol

PNEC	0.96 mg/l (water (fresh water))
	0.79 mg/l (water (sea water))
PNEC	3.6 mg/kg (sediment (fresh water))
	2.9 mg/kg (sediment (sea water))
	0.63 mg/kg (soil)

CAS: 112-53-8 Lauryl alcohol

PNEC	0.021 mg/l (sewage plant)
	0.0028 mg/l (freshwater (Süßwasser))
	0.00028 mg/l (water (sea water))
PNEC	1.1 mg/kg (sediment (fresh water))
	0.888 mg/kg (soil)
	0.11 mg/kg (water (sea water))

Additional information: The lists valid during the making were used as basis.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.02

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - BaseCoat (1)

(Contd. of page 5)

8.2 Exposure controls**Suitable technical control devices**

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection Not required in normal cases.

Eye/face protection

Safety glasses

[EN 166]

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties**General Information****Physical state**

Fluid

Colour:

Colourless

Odour:

Alcohol-like

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

78 - 265 °C
(Active ingredient data)
Not applicable.

Flammability**Lower and upper explosion limit****Lower:**

2.0 Vol.% (Main ingredient data)

1,5 Vol.% (Propellant data)

Upper:

12.0 Vol.% (Main ingredient data)

10,9 Vol.% (Propellant data)

Flash point:

16 °C (DIN 51755)
(Active ingredient data)

Auto-ignition temperature:

Not determined.

Decomposition temperature:

Not determined.

pH

Not applicable.

Viscosity:**Kinematic viscosity at 40 °C**

< 20.5 mm²/s
(Active ingredient data)

Solubility**water:**

Partly miscible.

Partition coefficient n-octanol/water (log value)

Not determined.

Vapour pressure:

Not determined.

Density and/or relative density**Density at 20 °C:**

0.87 - 0.88 g/cm³
(Active ingredient data)

Relative density

Not determined.

Vapour density

Not determined.

9.2 Other information**Appearance:****Form:**

Aerosol

(Contd. on page 7)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.02

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - BaseCoat (1)

(Contd. of page 6)

Important information on protection of health and environment, and on safety.

Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Solvent separation test:	
VOC (EC)	0.00 %
Change in condition	
Evaporation rate	Not applicable.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity**10.1 Reactivity** No dangerous reactions known.**10.2 Chemical stability** Stable under normal conditions.**10.3 Possibility of hazardous reactions** Develops readily flammable gases/fumes.**10.4 Conditions to avoid**

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials:

strong oxidizing agents

strong acids

10.6 Hazardous decomposition products: Formaldehyde**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****CAS: 67-63-0 propan-2-ol**

Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	13,900 mg/kg (rabbit)
Inhalative	LC50 / 6 h	>25 mg/l (rat) (OECD 403)

CAS: 64-17-5 ethanol

Oral	LD50	5,560 mg/kg (guinea pig)
------	------	--------------------------

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.02

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - BaseCoat (1)

(Contd. of page 7)

		3,450 mg/kg (mouse)
		7,060 mg/kg (rat)
		6,300 mg/kg (rabbit)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4d	20,000 mg/l (rat)
CAS: 112-53-8 Lauryl alcohol		
Oral	LD50	>2,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (Morone saxatilis) (OECD-Prüfrichtlinie 402)
		>2,000 mg/kg (rabbit)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Additional toxicological information:

Repeated dose toxicity

CAS: 64-17-5 ethanol

Oral LOAEL 3,160 mg/kg (rat)

NOAEL 1,730 mg/kg (rat)

CAS: 112-53-8 Lauryl alcohol

Oral NOAEL 2,000 mg/kg (rat) (based on body weight and day)

2,000 mg/kg (Ratte)

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:

CAS: 67-63-0 propan-2-ol

LC50 / 96h 9,640 mg/l (Pimephales promelas)

LC50 / 24h 9,714 mg/l (daphnia)

EC50 >100 mg/l (bacteria)

EC50 / 72h >100 mg/l (algae)

CAS: 106-97-8 butane

LC50 / 96 h 27.98 mg/l (fish)

EC50 / 4 d 7.71 mg/l (algae)

CAS: 74-98-6 propane

LC50 / 96 h 27.98 mg/l (fish)

EC50 / 96 h 7.71 mg/l (algae)

CAS: 64-17-5 ethanol

LC50 / 48h 8,140 mg/l (Leuciscus idus)

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.02

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - BaseCoat (1)

(Contd. of page 8)

LC50 / 24h	>100 mg/l (<i>Daphnia magna</i>)
EC5 / 16h	6,500 mg/l (<i>Pseudomonas putida</i>)
EC50 / 48h	9,268 mg/l (<i>Daphnia magna</i>)

CAS: 75-28-5 isobutane

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)

CAS: 112-53-8 Lauryl alcohol

Inhalative	LC50/1	>71 mg/L (rat)
	LC50 / 96h	>1-10 mg/l (<i>Pimephales promelas</i>) (OECD-Prüfrichtlinie 203)
	EC50	>0.1-1 mg/l (<i>Grünalge Pseudokirchneriella subcapitata</i>) (OECD-Prüfrichtlinie201)
	EC50 / 48h	>0.1-1 mg/l (<i>Daphnia magna</i>) (OECD Prüfrichtlinie 202)
	EC50 / 72h	>0.1-1 mg/l (<i>Scenedesmus subspicatus</i>) (OECD Prüfrichtlinie 201)
	NOEC / 21 d	>0.01-0.1 mg/l (<i>Daphnia magna</i>) (OECD-Prüfrichtlinie 211; Literaturwert)

12.2 Persistence and degradability

CAS: 67-63-0 propan-2-ol

Biodegradation 53 %

CAS: 112-53-8 Lauryl alcohol

Biodegradation >60 % (OECD TG 301 B)

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

CAS: 541-02-6	decamethylcyclopentasiloxane
CAS: 540-97-6	Dodecamethylcyclohexasiloxane

vPvB:

CAS: 541-02-6	decamethylcyclopentasiloxane
CAS: 540-97-6	Dodecamethylcyclohexasiloxane

12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.

12.7 Other adverse effects

Additional ecological information:

General notes: The product may not be released into the environment without control.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Must be specially treated adhering to official regulations.

European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR/RID/ADN 1950 AEROSOLS
IMDG AEROSOLS
IATA AEROSOLS, flammable

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.02

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - BaseCoat (1)

(Contd. of page 9)

14.3 Transport hazard class(es)

ADR/RID/ADN



Class 2 5F Gases.
Label 2.1

IMDG, IATA



Class 2.1
Label 2.1

14.4 Packing group

ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:**Marine pollutant:** No**14.6 Special precautions for user** Warning: Gases.**14.7 Maritime transport in bulk according to IMO instruments** Not applicable.**Transport/Additional information:**

ADR/RID/ADN

Limited quantities (LQ) 1L**Transport category** 2**Tunnel restriction code** D**UN "Model Regulation":** UN1950, AEROSOLS, 2.1**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulations:****Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H400 Very toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 11)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.02

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - BaseCoat (1)

(Contd. of page 10)

Classification according to Regulation (EC) No 1272/2008

Aerosols	On basis of test data
Serious eye damage/eye irritation Specific target organ toxicity (single exposure)	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Version number of previous version: 2.01

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = Lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Sources

"Regulation (EC) Nr. 1907/2006 (REACH), 1272/2008 (CLP), 648/2004 (Detergents) in the respective valid version. National occupation exposure limits for each country in the respective valid version. Transportation regulations according to ADR, RID, IMDG, IATA in the respective valid version."

*** Data compared to the previous version altered.**

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.05

Revision: 22.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - GlossCoat (2)

Article number:

02362410,

B02230000

(GlossCoat (2) for SONAX PROFILINE CERAMIC COATING CC 36 [02369410])

UFI: QFR0-C06R-700A-EKNV

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Car care product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 3 H229 Pressurised container: May burst if heated.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms Void

Signal word Warning

Hazard statements

H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

3 % by mass of the contents are flammable

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.05

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - GlossCoat (2)

(Contd. of page 1)

Determination of endocrine-disrupting properties Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Preparation made from gas under pressure and water-based cleaning emulsion

Dangerous components:

EC No 918-167-1 Reg.nr.: 01-2119472146-39-xxxx	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics Alternative CAS numbers: 90622-57-4, 64742-48-9 ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304	1-<3%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide ⚠ Press. Gas (Ref. Liq.), H281	1-<3%
EC No 934-956-3 Reg.nr.: 01-2119827000-58-xxxx	Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7 ⚠ Asp. Tox. 1, H304	1-<3%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air.

After skin contact:

Generally the product does not irritate the skin.

Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow to penetrate the ground/soil.

6.3 Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

Dispose contaminated material as waste according to item 13.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.05

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - GlossCoat (2)

(Contd. of page 2)

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**Information about fire - and explosion protection:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:**

Prevent any seepage into the ground.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Store receptacle in a well ventilated area.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 124-38-9 carbon dioxide**

WEL (Great Britain)

Short-term value: 27400 mg/m³, 15000 ppmLong-term value: 9150 mg/m³, 5000 ppm

IOELV (EU)

Long-term value: 9000 mg/m³, 5000 ppm**Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics**

GERMAN RCP-METHOD (EU)

Long-term value: 600 mg/m³

2 (II) / AGW (German TRGS 900)

Regulatory information

WEL (Great Britain): EH40/2011

IOELV (EU): (EU) 2017/164

Additional information: The lists valid during the making were used as basis.**8.2 Exposure controls****Suitable technical control devices**

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Hand protection Not required in normal cases.

(Contd. on page 4)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.05

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - GlossCoat (2)

Eye/face protection Not required in normal cases

(Contd. of page 3)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Fluid
Colour:	White
Odour:	Odourless
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	100 - 278 °C (Active ingredient data)
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH	7.0 - 7.5 (Active ingredient data)
Viscosity:	
Kinematic viscosity	Not determined.
Solubility	
water:	Partly miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.99 - 1.01 g/cm ³ (Active ingredient data)
Relative density	Not determined.
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Aerosol
Important information on protection of health and environment, and on safety.	
Explosive properties:	Not determined.
Change in condition	
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	
<i>Pressurised container: May burst if heated.</i>	
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void

(Contd. on page 5)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.05

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - GlossCoat (2)

(Contd. of page 4)

Corrosive to metals
Desensitised explosives

Void
Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions No dangerous reactions known.

10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5,000 mg/m ³ (rat) (OECD 403)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

LLO 96 h	1,000 mg/l (Oncorhynchus mykiss)
NOEC/NOEL	0.011 mg/l (Daphnia magna) (21d)
NOELR 72 h	1,000 mg/l (Pseudokirchneriella subcapitata)
NOELR 21d	≥1 mg/l (Daphnia magna)
ELO 48 h	1,000 mg/l (Daphnia magna)
ELO 72 h	1,000 mg/l (Pseudokirchneriella subcapitata)

12.2 Persistence and degradability No further relevant information available.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.05

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - GlossCoat (2)

(Contd. of page 5)



12.3 Bioaccumulative potential No further relevant information available.
12.4 Mobility in soil No further relevant information available.
12.5 Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.
12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
12.7 Other adverse effects
Additional ecological information:
General notes: The product may not be released into the environment without control.

SECTION 13: Disposal considerations

13.1 Waste treatment methods
Waste classified as hazardous according to Annex III to Directive 2008/98/EC.
Recommendation Waste must be disposed of while observing the local, official regulations.
European waste catalogue
Disposal / product + Disposal / contaminated packaging

15 01 10* | packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR/RID/ADN IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, non-flammable
14.3 Transport hazard class(es) ADR/RID/ADN	
	
Class Label	2 5A Gases. 2.2
IMDG, IATA	
	
Class Label	2.2 2.2
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Warning: Gases.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
Transport/Additional information:	
ADR/RID/ADN Limited quantities (LQ)	1L

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.05

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - GlossCoat (2)

(Contd. of page 6)

Transport category	3
Tunnel restriction code	E
UN "Model Regulation":	UN 1950 AEROSOLS, 2.2

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H281 Contains refrigerated gas; may cause cryogenic burns or injury.

H304 May be fatal if swallowed and enters airways.

Classification according to Regulation (EC) No 1272/2008

Aerosols	On basis of test data
----------	-----------------------

Version number of previous version: 2.04

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Aerosol 3: Aerosols – Category 3

Press. Gas (Ref. Liq.): Gases under pressure – Refrigerated liquefied gas

Flam. Liq. 3: Flammable liquids – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Sources

"Regulation (EC) Nr. 1907/2006 (REACH), 1272/2008 (CLP), 648/2004 (Detergents) in the respective valid version. National occupation exposure limits for each country in the respective valid version. Transportation regulations according to ADR, RID, IMDG, IATA in the respective valid version."

* **Data compared to the previous version altered.**

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.03

Revision: 22.04.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - Prepare

Article number:

B02371000-02

(Prepare for SONAX PROFILINE CERAMIC COATING CC 36 [02369410])

UFI: HJR0-U0W4-H00T-2X7X

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC35 Washing and cleaning products (including solvent based products)

Application of the substance / the mixture Car care product

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + 49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

propan-2-ol

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

(Contd. on page 2)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.03

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - Prepare

(Contd. of page 1)

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

Labelling of packages where the contents do not exceed 125 ml

Marking container <125 ml deviates. Reduced labeling according article 29 and annex I, no. 1.5 CLP-regulation is used.

2.3 Other hazards
Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Determination of endocrine-disrupting properties Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures
Description: Preparation of propellant and solvents

Dangerous components:

EC No 927-241-2 Reg.nr.: 01-2119471843-32-xxxx	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics Alternative CAS number: 64742-48-9 ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336; Aquatic Chronic 3, H412, EUH066	50 - <75%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	15 - <20%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10 - <15%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5 - <10%
EC No 918-167-1 Reg.nr.: 01-2119472146-39-xxxx	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics Alternative CAS numbers: 90622-57-4, 64742-48-9 ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304	3 - <5%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	3 - <5%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons	≥30%
------------------------	------

Additional information: For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.03

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - Prepare

(Contd. of page 2)

SECTION 4: First aid measures**4.1 Description of first aid measures****General information:***Take affected persons out of danger area and lay down.**Immediately remove any clothing soiled by the product.***After inhalation:***Supply fresh air.**In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.***After skin contact:***Wash the areas of skin affected with water and a mild detergent.**If symptoms persist consult doctor.***After eye contact:***Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.***After swallowing:** *Do not induce vomiting; call for medical help immediately.***4.2 Most important symptoms and effects, both acute and delayed***Headache**Dizziness**Nausea**Drowsiness**Eye irritation**Reddening, drying and crack formation of the skin**At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.***4.3 Indication of any immediate medical attention and special treatment needed***Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.***SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:***Foam**Carbon dioxide**Fire-extinguishing powder**Water haze***For safety reasons unsuitable extinguishing agents:** *Water with full jet***5.2 Special hazards arising from the substance or mixture***Can form explosive gas-air mixtures.**In case of fire, the following can be released:**Carbon monoxide (CO)**Carbon dioxide (CO₂)***5.3 Advice for firefighters****Protective equipment:***Do not inhale explosion gases or combustion gases.**Wear fully protective suit.**Do not enter the hazardous area without a self-contained breathing apparatus.**See Section 8 for information on personal protection equipment.***Additional information***Cool endangered receptacles with water spray.**Collect contaminated fire fighting water separately. It must not enter the sewage system.***SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures***Wear protective equipment. Keep unprotected persons away.**Keep away from ignition sources.**Ensure adequate ventilation***6.2 Environmental precautions:***Do not allow to enter sewers/ surface or ground water.**Do not allow to penetrate the ground/soil.*

(Contd. on page 4)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.03

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - Prepare

(Contd. of page 3)

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 67-63-0 propan-2-ol

WEL (Great Britain)	Short-term value: 1250 mg/m ³ , 500 ppm
	Long-term value: 999 mg/m ³ , 400 ppm

CAS: 106-97-8 butane

WEL (Great Britain)	Short-term value: 1810 mg/m ³ , 750 ppm
	Long-term value: 1450 mg/m ³ , 600 ppm
	Carc (if more than 0.1% of buta-1.3-diene)

Regulatory information WEL (Great Britain): EH40/2011

DNELs

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	DNEL	300 mg/kg bw/day (consumer) (ChronicExposure, SystemicEffects)
Dermal	DNEL	300 mg/kg bw/day (consumer) (ChronicExposure, SystemicEffects)

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.03

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - Prepare

(Contd. of page 4)

Inhalative	DNEL	300 mg/kg bw/day (worker) (ChronicExposure, SystemicEffects)
		900 mg/m ³ (consumer) (ChronicExposure, SystemicEffects)
		1500 mg/m ³ (worker) (ChronicExposure, SystemicEffects)

CAS: 67-63-0 propan-2-ol

Oral	DNEL	26 mg/kg (consumer) (chronic effects (1d))
Dermal	DNEL	319 mg/kg (consumer) (chronic effects (1d)) 888 mg/kg (worker) (chronic effects (1d))
Inhalative	DNEL	89 mg/m ³ (consumer) (chronic effects) 500 mg/m ³ (worker) (chronic effects)

PNECs

CAS: 67-63-0 propan-2-ol

PNEC	140.9 mg/l (sporadic release)
	2251 mg/l (STP)
	140.9 mg/l (water (fresh water))
	140.9 mg/l (water (sea water))
PNEC	28 mg/kg (gro)
	552 mg/kg (sediment)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection Protective gloves

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥480min)

Eye/face protection

Safety glasses

[EN 166]

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

Colour:

Colourless

Odour:

Solvent-like

Melting point/freezing point:

Undetermined.

Boiling point or initial boiling point and boiling range

80 - 205 °C

Not applicable.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.03

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - Prepare

(Contd. of page 5)

Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	0.6 Vol.% (Main ingredient data) 1,5 Vol.% (Propellant data)
Upper:	7.0 Vol.% (Main ingredient data) 10,9 Vol.% (Propellant data)
Flash point:	9 °C (DIN 51755) (Active ingredient data)
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
pH	Not applicable.
Viscosity:	
Kinematic viscosity at 40 °C	<20.5 mm ² /s (Active ingredient data)
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.75 - 0.76 g/cm ³ (Active ingredient data)
Relative density	Not determined.
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Aerosol
Important information on protection of health and environment, and on safety.	
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Change in condition	
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	
Extremely flammable aerosol. Pressurised container: May burst if heated.	
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.

(Contd. on page 7)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.03

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - Prepare

(Contd. of page 6)

10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/4d	>4951 mg/l (rat) (OECD 403)

CAS: 67-63-0 propan-2-ol

Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50 / 6 h	>25 mg/l (rat) (OECD 403)

CAS: 106-97-8 butane

Inhalative	LC50/4d	658 mg/l (rat)
------------	---------	----------------

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5000 mg/m ³ (rat) (OECD 403)

Skin corrosion/irritation Long-term exposure causes slight irritation of the skin.**Serious eye damage/irritation**

May cause slight, short-term eye complaints.

Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** May cause drowsiness or dizziness.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.**11.2 Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

(Contd. on page 8)

-GB-

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.03

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - Prepare

(Contd. of page 7)

Aquatic toxicity:**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

LL50 / 96h	>10 - <30 mg/l (Oncorhynchus mykiss)
EL50 / 48h	>22 - <46 mg/l (Daphnia magna)
EL50 / 72h	>1000 mg/l (Pseudokirchneriella subcapitata)
NOELR 72 h	< 1 mg/l (Pseudokirchneriella subcapitata)

CAS: 67-63-0 propan-2-ol

LC50 / 96h	9640 mg/l (Pimephales promelas)
LC50 / 24h	9714 mg/l (daphnia)
EC50	>100 mg/l (bacteria)
EC50 / 72h	>100 mg/l (algae)

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

LLO 96 h	1000 mg/l (Oncorhynchus mykiss)
NOEC/NOEL	0.011 mg/l (Daphnia magna) (21d)
NOELR 72 h	1000 mg/l (Pseudokirchneriella subcapitata)
NOELR 21d	≥1 mg/l (Daphnia magna)
ELO 48 h	1000 mg/l (Daphnia magna)
ELO 72 h	1000 mg/l (Pseudokirchneriella subcapitata)

12.2 Persistence and degradability**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Biodegradation	89 % (28d)
----------------	------------

12.3 Bioaccumulative potential No further relevant information available.**12.4 Mobility in soil** No further relevant information available.**12.5 Results of PBT and vPvB assessment** Not applicable.**PBT:** Not applicable.**vPvB:** Not applicable.**12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.**12.7 Other adverse effects****Additional ecological information:****General notes:** The product may not be released into the environment without control.**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.**European waste catalogue**

Disposal / product + Disposal / contaminated packaging

15 01 10* packaging containing residues of or contaminated by hazardous substances

SECTION 14: Transport information**14.1 UN number or ID number**

ADR/RID/ADN, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR/RID/ADN	1950 AEROSOLS
IMDG	AEROSOLS
IATA	AEROSOLS, flammable

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.03

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - Prepare

(Contd. of page 8)

14.3 Transport hazard class(es)

ADR/RID/ADN



Class 2 5F Gases.
Label 2.1

IMDG, IATA



Class 2.1
Label 2.1

14.4 Packing group

ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:**Marine pollutant:** No**14.6 Special precautions for user**see Sections 6-8
Warning: Gases.**14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

Transport/Additional information:

ADR/RID/ADN

Limited quantities (LQ) 1L
Transport category 2
Tunnel restriction code D

UN "Model Regulation": UN 1950 AEROSOLS, 2.1**SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
The following substance(s) in this product is (are) identified by CAS number either in countries not subject to the REACH regulation or in regulations not yet updated with the new naming convention for hydrocarbon solvents.

Chemical safety assessment

Catégorie SEVESO (DIRECTIVE 2012/18/EU) P3a FLAMMABLE AEROSOLS

National regulations:**Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.

(Contd. on page 10)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 12.10.2021

Version: 2.03

Revision: 22.04.2021

Trade name: SONAX PROFILINE CERAMIC COATING CC 36 - Prepare

(Contd. of page 9)

H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.
EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

Aerosols	On basis of test data
Serious eye damage/eye irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Version number of previous version: 2.02

Abbreviations and acronyms:

vPvB: very persistent and very bioaccumulative
PBT: persistent, bioaccumulative, toxic
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
NOEL = No Observed Effect Level
NOEC = No Observed Effect Concentration
LC = lethal Concentration
EC50 = half maximal effective concentration
log POW = Octanol / water partition coefficient
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
ATE: acute toxicity estimate
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
IOELV = indicative occupational exposure limit values
Flam. Gas 1A: Flammable gases – Category 1A
Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

Sources

"Regulation (EC) Nr. 1907/2006 (REACH), 1272/2008 (CLP), 648/2004 (Detergents) in the respective valid version. National occupation exposure limits for each country in the respective valid version. Transportation regulations according to ADR, RID, IMDG, IATA in the respective valid version."

* **Data compared to the previous version altered.**