

Printing date 18.09.2024 Version: 6.00 (replaces version 5.00) Revision: 17.10.2023

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: SONAX Spray+Seal

**Article number:** 02435000, 02439000

UFI: 37N5-60HK-R009-X4WX

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Car care product

Sealing

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.

## 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

## Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

# SECTION 2: Hazards identification

# 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour. Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

# 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

## Hazard pictograms





GHS02 GHS07

## Signal word Warning Hazard statements

H226 Flammable liquid and vapour. H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

## Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

(Contd. on page 2)



Printing date 18.09.2024 Version: 6.00 (replaces version 5.00) Revision: 17.10.2023

(Contd. of page 1)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P264 Wash hands thoroughly after handling. P273 Avoid release to the environment.

P280 Wear eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

### 2.3 Other hazards

### Results of PBT and vPvB assessment

#### PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

### vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

# Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Description: Cleaning components and alcohols in a water-based solution.

Dangerous components:		
CAS: 56-81-5 EINECS: 200-289-5	glycerol substance with a Community workplace exposure limit	25-<50%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol	10-<15%
CAS: 68554-54-1	Dimethyl Siloxane with Aminoethylaminopropyl Silsesquioxane, Hydroxy-term  Skin Irrit. 2, H315; Eye Irrit. 2, H319	5-<10%
CAS: 69011-36-5 EC No 931-138-8	isotridecanol,ethoxylated (>5-20EO)	5-<10%
CAS: 556-67-2 EINECS: 209-136-7 Reg.nr.: 01-2119529238-36-xxxx	octamethylcyclotetrasiloxane  Flam. Liq. 3, H226; Repr. 2, H361f; Aquatic Chronic 1, H410 (M=10)  PBT; vPvB	<0.1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

# 4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Wash the areas of skin affected with water and a mild detergent.

After eve contact: Rinse opened eve for several minutes under running water. Then consult

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed Eye irritation

(Contd. on page 3)



Printing date 18.09.2024 Version: 6.00 (replaces version 5.00) Revision: 17.10.2023

(Contd. of page 2)

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

# SECTION 5: Firefighting measures

### 5.1 Extinguishing media

## Suitable extinguishing agents:

Water spray

Alcohol resistant foam

Carbon dioxide

Fire-extinguishing powder

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

## 5.3 Advice for firefighters

## Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

## Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

## SECTION 6: Accidental release measures

# **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation For non-emergency personnel

The usual precautionary measures are to be adhered to when handling chemicals.

For emergency responders Wear protective equipment. Keep unprotected persons away.

## 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

## 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

## 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. **Information about fire - and explosion protection:** 



Keep ignition sources away - Do not smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

## Storage:

Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

## Further information about storage conditions:

Keep container tightly sealed.

Store receptacle in a well ventilated area.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

(Contd. on page 4)



Printing date 18.09.2024 Version: 6.00 (replaces version 5.00) Revision: 17.10.2023

(Contd. of page 3)

7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

## 8.1 Control parameters

Ingredients with lin	Ingredients with limit values that require monitoring at the workplace:		
CAS: 56-81-5 glycerol			
WEL (Great Britain)	Long-term value: 10 mg/m³		
OEL (Ireland)	Long-term value: 10 mg/m³		
CAS: 67-63-0 propan-2-ol			
WEL (Great Britain)	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm		
OEL (Ireland)	Short-term value: 400 ppm Long-term value: 200 ppm Sk		

# Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

DNELs			
CAS: 67-6	CAS: 67-63-0 propan-2-ol		
Oral	DNEL	26 mg/kg (consumer) (chornic effects (1d))	
Dermal	DNEL	319 mg/kg (consumer) (chronic effects (1d))	
		888 mg/kg (worker) (chronic effects (1d))	
Inhalative	DNEL	89 mg/m³ (consumer) (chronic effects)	
		500 mg/m³ (worker) (chronic effects)	

# **PNECs**

# CAS: 67-63-0 propan-2-ol

PNEC 140.9 mg/l (sporadic release)

2,251 mg/l (STP)

140.9 mg/l (water (fresh water))

140.9 mg/l (water (sea water))

PNEC 28 mg/kg (gro)

552 mg/kg (sediment)

Additional information: The lists valid during the making were used as basis.

## 8.2 Exposure controls

# Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

## Individual protection measures, such as personal protective equipment

## General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

# Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Hand protection Not required in normal cases.

Eye/face protection

Safety glasses

[EN 166]

GR -



Printing date 18.09.2024 Version: 6.00 (replaces version 5.00) Revision: 17.10.2023

(Contd. of page 4)

# SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical stateFluidColour:ColourlessOdour:Fruit-likeMelting point/freezing point:Undetermined.

Boiling point or initial boiling point and boiling

range 82 °C (CAS: 67-63-0 propan-2-ol)
Flammability Flammable liquid and vapour.

Lower and upper explosion limit

 Lower:
 2 Vol % (CAS: 67-63-0 propan-2-ol)

 Upper:
 13 Vol % (CAS: 67-63-0 propan-2-ol)

Flash point: 31 °C

**Decomposition temperature:** Not determined.

pH at 20 °C 4-5

Viscosity:

Kinematic viscosity at 40 °C <20.5 mm<sup>2</sup>/s

Solubility

water: Fully miscible.
Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C:

Vapour pressure at 20 °C:

43 hPa (CAS: 67-63-0 propan-2-ol)

Density and/or relative density

Density at 20 °C: 1.04-1.06 g/cm³ Vapour density Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Ignition temperature:Not determined.Explosive properties:Not determined.

Change in condition

**Evaporation rate** Not determined.

Information with regard to physical hazard classes

ExplosivesVoidFlammable gasesVoidAerosolsVoidOxidising gasesVoidGases under pressureVoid

Flammable liquids Flammable liquid and vapour.

Flammable solids

Self-reactive substances and mixtures

Void

Pyrophoric liquids

Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures, which emit flammable

gases in contact with water

Void

Oxidising liquids

Void

gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals Void
Desensitised explosives Void

## SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

**10.3 Possibility of hazardous reactions** No dangerous reactions known.

10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

(Contd. on page 6)



Printing date 18.09.2024 Version: 6.00 (replaces version 5.00) Revision: 17.10.2023

(Contd. of page 5)

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

**10.6 Hazardous decomposition products:** Carbon monoxide and carbon dioxide

Silicon oxides

Nitrogen oxides (NOx)

# **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	LD/LC50 values relevant for classification:		
CAS: 67-6	CAS: 67-63-0 propan-2-ol		
Oral	LD50	5,840 mg/kg (rat)	
Dermal	LD50	13,900 mg/kg (rabbit)	
Inhalative	LC50 / 6 h	>25 mg/l (rat) (OECD 403)	
CAS: 690	CAS: 69011-36-5 isotridecanol,ethoxylated (>5-20EO)		
Oral	LD50	>300-2,000 mg/kg (rat) (OECD 423)	
	ATE	>300-2,000 mg/kg (rat)	

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Additional toxicological information:

Values relevant for classification:

CAS: 67-63-0 propan-2-ol

Oral NOAEL 400 mg/kg/day (rat)

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

# **SECTION 12: Ecological information**

**12.1 Toxicity** There are no ecotoxicological data available on this mixture.

Aquatic toxicity:		
CAS: 67-63-0 propan-2-ol		
LC50 / 96h	9,640 mg/l (Pimephales promelas)	
LC50 / 24h	9,714 mg/l (daphnia)	
EC50	>100 mg/l (bacteria)	
EC50 / 72h	>100 mg/l (algae)	
LOEC	1,000 mg/l (algae)	

## 12.2 Persistence and degradability

CAS: 67-63-0 propan-2-ol

Biodegradation 53 %

(Contd. on page 7)



Printing date 18.09.2024 Version: 6.00 (replaces version 5.00) Revision: 17.10.2023

(Contd. of page 6)

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

#### PBT:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

### vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

### 12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

The product does not contain substances with endocrine disrupting properties.

### 12.7 Other adverse effects

Additional ecological information:

General notes: The product may not be released into the environment without control.

# SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Recommendation Waste must be disposed of while observing the local, official regulations.

### European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

07 06 04*	other organic solvents, washing liquids and mother liquors	
15 01 10*	packaging containing residues of or contaminated by hazardous substances	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP14	Ecotoxic	

## Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

## SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA UN1987

14.2 UN proper shipping name

ADR/RID/ADN Void

IMDG, IATA ALCOHOLS, N.O.S. (ISOPROPANOL)

### 14.3 Transport hazard class(es)

# ADR/RID/ADN



Class 3 (F1) Flammable liquids.

Label

## IMDG, IATA



Class 3 Flammable liquids.

Label

(Contd. on page 8)



Printing date 18.09.2024 Version: 6.00 (replaces version 5.00) Revision: 17.10.2023

	(Contd. of page
14.4 Packing group ADR/RID/ADN, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for u	ser Warning: Flammable liquids.
Transport/Additional informati	ion:
ADR/RID/ADN	
Limited quantities (LQ)	5L
Transport category	3
Tunnel restriction code	D/E
UN "Model Regulation":	Void

# SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) 12.50 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) P5c FLAMMABLE LIQUIDS

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

### National regulations:

# Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning juveniles must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

### Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H410 Very toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008		
Flammable liquids	On basis of test data	
Serious eye damage/irritation Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

**Date of previous version:** 01.02.2023 **Version number of previous version:** 5.00

Abbreviations and acronyms: NOEL = No Observed Effect Level NOEC = No Observed Effect Concentration LC = letal Concentration

(Contd. on page 9)



Printing date 18.09.2024 Version: 6.00 (replaces version 5.00) Revision: 17.10.2023

(Contd. of page 8)

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)
PNEC: Predicted No-Effect Concentration (UK REACH)
LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.