

**Safety data sheet
according to UK REACH**

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** SONAX Scratch Remover Paintwork (Polish)**Article number:** B03208410, B03208180**1.2 Relevant identified uses of the substance or mixture and uses advised against****Application of the substance / the mixture**

Car care product

Abrasive

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against None**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

The product is not classified, according to the GB CLP regulation.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008** Void**Hazard pictograms** Void**Signal word** Void**Hazard statements** Void**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Description:** Emulsion of solvents, abrasives and additives

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Polish)

(Contd. of page 1)

Dangerous components:

CAS: 72623-86-0 EINECS: 276-737-9 Reg.nr.: 01-2119474878-16-XXXX	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based ⚠ Asp. Tox. 1, H304	5-<10%
EC No 934-956-3 Reg.nr.: 01-2119827000-58-xxxx	Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7 ⚠ Asp. Tox. 1, H304	3-<5%
CAS: 56-81-5 EINECS: 200-289-5	glycerol substance with a Community workplace exposure limit	3-<5%
EC No 934-954-2 Reg.nr.: 01-2119826592-36-xxxx	Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7 ⚠ Asp. Tox. 1, H304	1-<3%
EINECS: 265-149-8 Reg.nr.: 01-2119453414-43-xxxx	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8 ⚠ Asp. Tox. 1, H304, EUH066	1-<3%

Additional information: For the wording of the listed hazard phrases refer to section 16.**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:** Remove soiled clothing**After inhalation:** Supply fresh air.**After skin contact:** Wash the areas of skin affected with water and a mild detergent.**After eye contact:** Rinse opened eye for several minutes under running water.**After swallowing:** Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.**5.2 Special hazards arising from the substance or mixture** No further relevant information available.**5.3 Advice for firefighters****Protective equipment:**

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation**For non-emergency personnel**

The usual precautionary measures are to be adhered to when handling chemicals.

For emergency responders Wear protective equipment. Keep unprotected persons away.**6.2 Environmental precautions:**

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Absorb liquid components with liquid-binding material.

Dispose contaminated material as waste according to section 13.

(Contd. on page 3)

GB

Trade name: SONAX Scratch Remover Paintwork (Polish)

(Contd. of page 2)

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling No special precautions are necessary if used correctly.
Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 56-81-5 glycerol

WEL (Great Britain)	Long-term value: 10 mg/m ³
---------------------	---------------------------------------

OEL (Ireland)	Long-term value: 10 mg/m ³
---------------	---------------------------------------

Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

DNELs

CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Inhalative	DNEL	1.2 mg/m ³ (consumer) (local / longterm (repeated))
------------	------	--

		5.4 mg/m ³ (worker) (local / longterm (repeated))
--	--	--

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Hand protection Not required in normal cases.

Eye/face protection Not required in normal cases

GB

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Polish)

(Contd. of page 3)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Fluid
Colour:	White
Odour:	Solvent-like
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	100 - 355 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Decomposition temperature:	Not determined.
pH	Not applicable.
Viscosity:	
Kinematic viscosity at 40 °C	>20.5 mm ² /s
Solubility	
water:	Partly miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.98 - 0.99 g/cm ³
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Pasty
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Polish)

(Contd. of page 4)

10.4 Conditions to avoid See Section 7 for information on safe handling.**10.5 Incompatible materials:** strong oxidizing agents**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based**

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rabbit)

Inhalative LC50/4d >5,000 mg/l (rat)

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Oral LD50 >5,000 mg/kg (rat) (OECD 401)

Dermal LD50 >3,160 mg/kg (rabbit) (OECD 402)

Inhalative LC50 / 4h >5.266 mg/m³ (rat) (OECD 403)**Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics**

Oral LD50 >5,000 mg/kg (rat) (OECD 401)

Dermal LD50 >3,160 mg/kg (rabbit) (OECD 402)

Inhalative LC50 / 4h >5.266 mg/m³ (rat) (OECD 403)**Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

Oral LD50 >5,000 mg/kg (rat) (OECD 401)

Dermal LD50 >5,000 mg/kg (rabbit) (OECD 402)

Inhalative LC50 / 4h >5.6 mg/m³ (rat) (OECD 403)**Skin corrosion/irritation** Based on available data, the classification criteria are not met.**Serious eye damage/irritation** Based on available data, the classification criteria are not met.**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard**Viscosity: > 20,5mm²/s (40°C)

Based on available data, the classification criteria are not met.

11.2 Information on other hazards**Endocrine disrupting properties**

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.**Aquatic toxicity:****CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based**NOEC / 2 d ≥10,000 mg/l (*Daphnia magna*) (OECD 202)

LC50 / 96h >100 mg/l (fish)

EC50 / 48h >10,000 mg/l (*Daphnia magna*) (OECD 202)

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Polish)

(Contd. of page 5)

ErC 50 / 72h	>100 mg/l (algae)
NOEC 96h	≥100 mg/l (fish) (OECD 203)
NOEC / 21 d	≥10 mg/l (Daphnia magna) (OECD 211)
NOEC / 72 h	≥100 mg/l (algae)
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	
LC50 / 4 d	>1,028 mg/l (Scophtalamus maximus) (OECD 203)
LC50 / 48h	>3,193 mg/l (Acartia tonsa)
NOEC / 21 d	>1,000 mg/l (Daphnia magna)
NOEC / 28d	>1,000 mg/l (Oncorhynchus mykiss)
LC50 / 3 d	>10,000 mg/l (Skeletonema costatum)
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	
LC50 / 2 d	>3,193 mg/l (Acartia tonsa)
LC50 / 4 d	>1,028 mg/l (Scophtalamus maximus) (OECD 203)
NOEC / 21 d	>1,000 mg/l (Daphnia magna)
NOEC / 28d	>1,000 mg/l (Oncorhynchus mykiss)
EC50 / 3 d	>10,000 mg/l (Skeletonema costatum)
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
LC50 / 2 d	>1,000 mg/l (Daphnia magna) (OECD 202)
LC50 / 4 d	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)
NOEC / 21 d	>1,000 mg/l (Daphnia magna)
NOEC / 28d	>1,000 mg/l (Oncorhynchus mykiss)
EC50 / 3 d	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
12.2 Persistence and degradability	
CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	
Biodegradation	>60 % (28d)
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	
Biodegradation	74 %
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	
Biodegradation	74 %
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Biodegradation	67.6 %

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects

Additional ecological information:

General notes: The product may not be released into the environment without control.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Not classified as hazardous waste according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

(Contd. on page 7)

-GB

Safety data sheet according to UK REACH

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Polish)

(Contd. of page 6)

European waste catalogue

- 1) Disposal / product
2) Disposal / contaminated packaging

12 01 99	wastes not otherwise specified
15 01 02	plastic packaging

SECTION 14: Transport information

14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR/RID/ADN, IMDG, IATA	Void
14.3 Transport hazard class(es) ADR/RID/ADN, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**European Directives:**

Directive 2010/75/EU (VOC) 6.40 %
Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to
REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.
Annex II - REPORTABLE EXPLOSIVES PRECURSORS
None of the ingredients is listed.

National regulations:**Information about limitation of use:**

Employment restrictions concerning juveniles must be observed.
Employment restrictions concerning pregnant and lactating women must be observed.
15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H304 May be fatal if swallowed and enters airways.
EUH066 Repeated exposure may cause skin dryness or cracking.

Date of previous version: 24.05.2022**Version number of previous version:** 2.00**Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
NOEL = No Observed Effect Level

(Contd. on page 8)

**Safety data sheet
according to UK REACH**

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Polish)

(Contd. of page 7)

*NOEC = No Observed Effect Concentration**LC = letal Concentration**EC50 = half maximal effective concentration**log POW = Octanol / water partition coefficient**GHS: Globally Harmonized System of Classification and Labelling of Chemicals**ATE: acute toxicity estimate**ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**DNEL: Derived No-Effect Level (UK REACH)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**IOELV = indicative occupational exposure limit values**Asp. Tox. 1: Aspiration hazard – Category 1**** Data compared to the previous version altered.**

GB

**Safety data sheet
according to UK REACH**

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** SONAX Scratch Remover Paintwork (Finish)**Article number:** B03058410, B03058180**1.2 Relevant identified uses of the substance or mixture and uses advised against****Application of the substance / the mixture**

Car care product

Abrasive

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against None**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

The product is not classified, according to the GB CLP regulation.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008** Void**Hazard pictograms** Void**Signal word** Void**Hazard statements** Void**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients**3.2 Mixtures****Description:** Emulsion of solvents, abrasives and additives

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Finish)

(Contd. of page 1)

Dangerous components:

CAS: 72623-86-0 EINECS: 276-737-9 Reg.nr.: 01-2119474878-16-XXXX	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based ⚠ Asp. Tox. 1, H304	5-<10%
CAS: 107-98-2 EINECS: 203-539-1 Reg.nr.: 01-2119457435-35-xxxx	1-Methoxy-2-propanol ⚠ Flam. Liq. 3, H226; ⚠ STOT SE 3, H336	3-<5%
EC No 934-956-3 Reg.nr.: 01-2119827000-58-xxxx	Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7 ⚠ Asp. Tox. 1, H304	3-<5%
CAS: 56-81-5 EINECS: 200-289-5	glycerol substance with a Community workplace exposure limit	3-<5%
EC No 934-954-2 Reg.nr.: 01-2119826592-36-xxxx	Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7 ⚠ Asp. Tox. 1, H304	1-<3%
EINECS: 265-149-8 Reg.nr.: 01-2119453414-43-xxxx	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8 ⚠ Asp. Tox. 1, H304, EUH066	1-<3%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures**

General information: No special measures required.

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Wash the areas of skin affected with water and a mild detergent.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters**Protective equipment:**

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation**For non-emergency personnel**

The usual precautionary measures are to be adhered to when handling chemicals.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Finish)

(Contd. of page 2)

6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

Absorb liquid components with liquid-binding material.

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling No special precautions are necessary if used correctly.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 107-98-2 1-Methoxy-2-propanol

WEL (Great Britain)	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
---------------------	---

IOELV (EU)	Short-term value: 568 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Skin
------------	---

OEL (Ireland)	Short-term value: 568 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm IOELV
---------------	--

CAS: 56-81-5 glycerol

WEL (Great Britain)	Long-term value: 10 mg/m ³
---------------------	---------------------------------------

OEL (Ireland)	Long-term value: 10 mg/m ³
---------------	---------------------------------------

Regulatory information

WEL (Great Britain): EH40/2020

IOELV (EU): (EU) 2019/1831

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

DNELs

CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Inhalative	DNEL	1.2 mg/m ³ (consumer) (local / longterm (repeated)) 5.4 mg/m ³ (worker) (local / longterm (repeated))
------------	------	--

CAS: 107-98-2 1-Methoxy-2-propanol

Oral	DNEL	3.3 mg/kg (consumer) (long-term / systemic effects)
------	------	---

Dermal	DNEL	18.1 mg/kg (consumer) (long-term / systemic effects)
--------	------	--

		50.6 mg/kg (worker) (long-term / systemic effects)
--	--	--

Inhalative	DNEL	43.9 mg/m ³ (consumer) (long-term / systemic effects)
------------	------	--

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Finish)

(Contd. of page 3)

	553.5 mg/m ³ (worker) (short-term / local effects)
DNEL	369 mg/m ³ (worker) (long-term / systemic effects)

PNECs

CAS: 107-98-2 1-Methoxy-2-propanol

PNEC	100 mg/l (STP)
	100 mg/l (water (intermittent release))
	10 mg/l (water (fresh water))
	1 mg/l (water (sea water))
PNEC	2.47 mg/kg (gro)
	41.6 mg/kg (sediment (fresh water))
	4.17 mg/kg (sediment (sea water))

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Hand protection Not required in normal cases.

Eye/face protection Not required in normal cases

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Fluid
Colour:	White
Odour:	Solvent-like
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	100 - 310 °C
Flammability	Not applicable.
Lower and upper explosion limit	
Lower:	Not determined.
Upper:	Not determined.
Flash point:	Not applicable.
Decomposition temperature:	Not determined.
pH	Not applicable.
Viscosity:	
Kinematic viscosity at 40 °C	>20.5 mm ² /s
Solubility	
water:	Partly miscible.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.98 - 0.99 g/cm ³
Relative density	Not determined.
Vapour density	Not determined.

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Finish)

(Contd. of page 4)

9.2 Other information**Appearance:****Form:**

Emulsion

Important information on protection of health and environment, and on safety.**Ignition temperature:**

Product is not selfigniting.

Explosive properties:

Product does not present an explosion hazard.

Change in condition**Evaporation rate**

Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.**10.2 Chemical stability** Stable under normal conditions.**10.3 Possibility of hazardous reactions** No dangerous reactions known.**10.4 Conditions to avoid** See Section 7 for information on safe handling.**10.5 Incompatible materials:** strong oxidizing agents**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based**

Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4d	>5,000 mg/l (rat)

CAS: 107-98-2 1-Methoxy-2-propanol

Oral	LD50	4,016 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC0 / 6h	>7,000 ppm (rat)

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5.266 mg/m ³ (rat) (OECD 403)

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Finish)

(Contd. of page 5)

Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5.266 mg/m ³ (rat) (OECD 403)

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5.6 mg/m ³ (rat) (OECD 403)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

Viscosity: > 20,5mm²/s (40°C)

Based on available data, the classification criteria are not met.

11.2 Information on other hazards**Endocrine disrupting properties**

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:**CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based**

NOEC / 2 d	≥10,000 mg/l (Daphnia magna) (OECD 202)
LC50 / 96h	>100 mg/l (fish)
EC50 / 48h	>10,000 mg/l (Daphnia magna) (OECD 202)
ErC 50 / 72h	>100 mg/l (algae)
NOEC 96h	≥100 mg/l (fish) (OECD 203)
NOEC / 21 d	≥10 mg/l (Daphnia magna) (OECD 211)
NOEC / 72 h	≥100 mg/l (algae)

CAS: 107-98-2 1-Methoxy-2-propanol

LC50 / 96h	>6,800 mg/l (Leuciscus idus) (DIN38412)
LC50 / 48h	23,300 mg/l (Daphnia magna)
EC50	>1,000 mg/l (Pseudokirchneriella subcapitata) (7d)
EC50/3h	>1,000 mg/l (activated sludge) (OECD 209)

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

LC50 / 4 d	>1,028 mg/l (Scophtalamus maximus) (OECD 203)
LC50 / 48h	>3,193 mg/l (Acartia tonsa)
NOEC / 21 d	>1,000 mg/l (Daphnia magna)
NOEC / 28d	>1,000 mg/l (Oncorhynchus mykiss)
LC50 / 3 d	>10,000 mg/l (Skeletonema costatum)

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Finish)

(Contd. of page 6)

Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

LC50 / 2 d	>3,193 mg/l (Acartia tonsa)
LC50 / 4 d	>1,028 mg/l (Scophtalamus maximus) (OECD 203)
NOEC / 21 d	>1,000 mg/l (Daphnia magna)
NOEC / 28d	>1,000 mg/l (Oncorhynchus mykiss)
EC50 / 3 d	>10,000 mg/l (Skeletonema costatum)

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics

LC50 / 2 d	>1,000 mg/l (Daphnia magna) (OECD 202)
LC50 / 4 d	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)
NOEC / 21 d	>1,000 mg/l (Daphnia magna)
NOEC / 28d	>1,000 mg/l (Oncorhynchus mykiss)
EC50 / 3 d	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)

12.2 Persistence and degradability

CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based

Biodegradation >60 % (28d)

CAS: 107-98-2 1-Methoxy-2-propanol

Biodegradation 90-100 % (OECD 301E)

Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Biodegradation 74 %

Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics

Biodegradation 74 %

Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation 67.6 %

12.3 Bioaccumulative potential

CAS: 107-98-2 1-Methoxy-2-propanol

log Kow ≤0.43 (25°C)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects

Additional ecological information:

General notes: The product may not be released into the environment without control.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Not classified as hazardous waste according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

12 01 99	wastes not otherwise specified
----------	--------------------------------

15 01 02	plastic packaging
----------	-------------------

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Finish)

(Contd. of page 7)

15 01 04 metallic packaging

SECTION 14: Transport information

14.1 UN number or ID number
ADR/RID/ADN, IMDG, IATA Void

14.2 UN proper shipping name
ADR/RID/ADN, IMDG, IATA Void

14.3 Transport hazard class(es)
ADR/RID/ADN, ADN, IMDG, IATA
Class Void

14.4 Packing group
ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:
Marine pollutant: No

14.6 Special precautions for user Not applicable.

UN "Model Regulation": Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
European Directives:

Directive 2010/75/EU (VOC) 6.40 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to
REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Date of previous version: 23.05.2022

Version number of previous version: 2.00

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration

(Contd. on page 9)

**Safety data sheet
according to UK REACH**

Printing date 19.09.2024

Version: 3.00 (replaces version 2.00)

Revision: 24.10.2023

Trade name: SONAX Scratch Remover Paintwork (Finish)

(Contd. of page 8)

*log POW = Octanol / water partition coefficient**GHS: Globally Harmonized System of Classification and Labelling of Chemicals**ATE: acute toxicity estimate**ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**DNEL: Derived No-Effect Level (UK REACH)**PNEC: Predicted No-Effect Concentration (UK REACH)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**IOELV = indicative occupational exposure limit values**Flam. Liq. 3: Flammable liquids – Category 3**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**Asp. Tox. 1: Aspiration hazard – Category 1**** Data compared to the previous version altered.**

GB