

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 3.00 (replaces version 2.03)

Revision: 01.09.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

**Trade name:** SONAX Soft Top & Fabric Water Proof Impregnation

**Article number:**

03102000

**UFI:** M2V0-M06E-3003-6X4K

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

#### Application of the substance / the mixture

Impregnation spray for textiles

Consumer uses: Private households / general public / consumers

Professional uses

**Uses advised against** There is currently no information available on this.

### 1.3 Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

#### Further information obtainable from:

Product safety

E-mail: [erp@sonax.de](mailto:erp@sonax.de)

Phone: + +49 (0) 8431 53 217

#### United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: [info@aaoil.co.uk](mailto:info@aaoil.co.uk)

### 1.4 Emergency telephone number:

**European Union:** +49 (0) 89 19240 (Poison Centre Munich)

**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

#### Hazard pictograms



GHS02

GHS07

GHS09

**Signal word** Danger

#### Hazard-determining components of labelling:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

#### Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

GB

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 3.00 (replaces version 2.03)

Revision: 01.09.2022

Trade name: SONAX Soft Top &amp; Fabric Water Proof Impregnation

(Contd. of page 1)

**Precautionary statements**

- P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P261 Avoid breathing spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.  
 Buildup of explosive mixtures possible without sufficient ventilation.

**2.3 Other hazards****Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

**vPvB:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

**Determination of endocrine-disrupting properties**

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures**

**Description:** Formulation consisting of pressurised gas and solvents with additives

**Dangerous components:**

EC No 920-750-0 Reg.nr.: 01-2119473851-33-xxxx	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics Alternative CAS number: 64742-49-0 ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ STOT SE 3, H336	50-<75%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	3-<5%
EC No 927-241-2 Reg.nr.: 01-2119471843-32-xxxx	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics Alternative CAS number: 64742-48-9 ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304; ⚠ STOT SE 3, H336; Aquatic Chronic 3, H412, EUH066	3-<5%
EC No 918-167-1 Reg.nr.: 01-2119472146-39-xxxx	Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics Alternative CAS numbers: 90622-57-4, 64742-48-9 ⚠ Flam. Liq. 3, H226; ⚠ Asp. Tox. 1, H304	1-<3%
EC No 920-901-0 Reg.nr.: 01-21194456810-40	Hydrocarbons, C11-C13, isoalkanes,, <2% aromatics ⚠ Asp. Tox. 1, H304	1-<3%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<3%
CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-2119450011-60-xxxx	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	1-<3%

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 3.00 (replaces version 2.03)

Revision: 01.09.2022

**Trade name: SONAX Soft Top & Fabric Water Proof Impregnation**

(Contd. of page 2)

**Additional information:****Hydrocarbon mixture:**

Benzene content &lt; 0.1%

For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

**4.1 Description of first aid measures****General information:**

Take affected persons out of danger area and lay down.

Remove soiled clothing

**After inhalation:**

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

**After skin contact:** Wash the areas of skin affected with water and a mild detergent.**After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** Do not induce vomiting; call for medical help immediately.**4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Nausea

Drowsiness

Reddening, drying and crack formation of the skin

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

## SECTION 5: Firefighting measures

**5.1 Extinguishing media****Suitable extinguishing agents:**

Foam

Carbon dioxide

Fire-extinguishing powder

Water spray

**For safety reasons unsuitable extinguishing agents:** Water with full jet**5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO<sub>2</sub>)**5.3 Advice for firefighters****Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

**Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

## SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation

For non-emergency personnel Keep away from ignition sources.

For emergency responders Wear protective equipment. Keep unprotected persons away.

**6.2 Environmental precautions:**

Do not allow to penetrate the ground/soil.

(Contd. on page 4)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 3.00 (replaces version 2.03)

Revision: 01.09.2022

**Trade name: SONAX Soft Top & Fabric Water Proof Impregnation**

(Contd. of page 3)

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

### 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

**Information about fire - and explosion protection:**



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Protect against electrostatic charges.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

#### Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

#### Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

#### Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

#### CAS: 106-97-8 butane

WEL (Great Britain) Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm  
Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm  
Carc (if more than 0.1% of buta-1.3-diene)

OEL (Ireland) Short-term value: 1000 ppm

#### CAS: 74-98-6 propane

OEL (Ireland) Asphx

#### CAS: 67-63-0 propan-2-ol

WEL (Great Britain) Short-term value: 1250 mg/m<sup>3</sup>, 500 ppm  
Long-term value: 999 mg/m<sup>3</sup>, 400 ppm

OEL (Ireland) Short-term value: 400 ppm  
Long-term value: 200 ppm  
Sk

(Contd. on page 5)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 3.00 (replaces version 2.03)

Revision: 01.09.2022

**Trade name: SONAX Soft Top & Fabric Water Proof Impregnation**

(Contd. of page 4)

<b>CAS: 75-28-5 isobutane</b>	
OEL (Ireland)	Short-term value: 1000 ppm
<b>CAS: 34590-94-8 Dipropylene glycol monomethyl ether</b>	
WEL (Great Britain)	Long-term value: 308 mg/m <sup>3</sup> , 50 ppm Sk
IOELV (EU)	Long-term value: 308 mg/m <sup>3</sup> , 50 ppm Skin
OEL (Ireland)	Long-term value: 308 mg/m <sup>3</sup> , 50 ppm Sk, IOELV

### Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

IOELV (EU): (EU) 2019/1831

### DNELs

#### Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Oral	DNEL	699 mg/kg bw/day (consumer) (longterm systematic effects)
Dermal	DNEL	699 mg/bw/day (consumer) (longterm systematic effects)
	DNEL	773 mg/kg bw/day (worker) (longterm systematic effects)
Inhalative	DNEL	2,035 mg/m <sup>3</sup> (worker) (longterm systematic effects)
	DNEL	608 mg/m <sup>3</sup> (consumer) (longterm systematic effects)

#### CAS: 67-63-0 propan-2-ol

Oral	DNEL	26 mg/kg (consumer) (chronic effects (1d))
Dermal	DNEL	319 mg/kg (consumer) (chronic effects (1d))
		888 mg/kg (worker) (chronic effects (1d))
Inhalative	DNEL	89 mg/m <sup>3</sup> (consumer) (chronic effects)
		500 mg/m <sup>3</sup> (worker) (chronic effects)

#### Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Oral	DNEL	125 mg/kg bw/day (consumer) (ChronicExposure, SystemicEffects)
Dermal	DNEL	125 mg/kg bw/day (consumer) (ChronicExposure, SystemicEffects)
		208 mg/kg bw/day (worker) (ChronicExposure, SystemicEffects)
Inhalative	DNEL	185 mg/m <sup>3</sup> (consumer) (ChronicExposure, SystemicEffects)
		871 mg/m <sup>3</sup> (worker) (ChronicExposure, SystemicEffects)

### PNECs

#### CAS: 67-63-0 propan-2-ol

PNEC	140.9 mg/l (sporadic release)
	2,251 mg/l (STP)
	140.9 mg/l (water (fresh water))
	140.9 mg/l (water (sea water))
PNEC	28 mg/kg (gro)
	552 mg/kg (sediment)

**Additional information:** The lists valid during the making were used as basis.

### 8.2 Exposure controls

#### Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

#### Individual protection measures, such as personal protective equipment

##### General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

##### Respiratory protection:

If the occupational exposure limit is exceeded:

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 3.00 (replaces version 2.03)

Revision: 01.09.2022

Trade name: SONAX Soft Top &amp; Fabric Water Proof Impregnation

(Contd. of page 5)

The following breathing protection is recommended:  
Respiratory filter for organic gases and vapours (Type A)  
Identification colour: Brown  
[DIN EN 14387]  
**Hand protection** Protective gloves  
**Material of gloves**  
Nitrile rubber, NBR  
Recommended thickness of the material:  $\geq 0.45$  mm  
[EN 374]  
**Penetration time of glove material** Value for the permeation: Level 6 ( $\geq 480$ min)  
**Eye/face protection**  
Safety glasses  
[EN 166]

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

#### General Information

#### Physical state

Fluid

#### Colour:

Colourless

#### Odour:

Petrol-like

#### Melting point/freezing point:

Undetermined.

#### Boiling point or initial boiling point and boiling range

Not applicable, as aerosol.

#### Flammability

Extremely flammable aerosol.

#### Lower and upper explosion limit

#### Lower:

0.7 Vol % (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

#### Upper:

7.7 Vol % (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

#### Flash point:

Not applicable, as aerosol.

#### Decomposition temperature:

Not determined.

#### pH

Not applicable

#### Viscosity:

#### Kinematic viscosity at 40 °C

<20.5 mm<sup>2</sup>/s  
(Active ingredient data )

#### Solubility

#### water:

Not miscible or difficult to mix.

#### Partition coefficient n-octanol/water (log value)

Not determined.

#### Vapour pressure:

Not determined.

#### Density and/or relative density

#### Density at 20 °C:

0.75-0.76 g/cm<sup>3</sup> (DIN 51757)  
(Active ingredient data )

#### Vapour density

Not determined.

### 9.2 Other information

#### Appearance:

#### Form:

Aerosol

#### Important information on protection of health and environment, and on safety.

#### Ignition temperature:

Not determined.

#### Explosive properties:

In use, may form flammable/explosive vapour-air mixture.

#### Change in condition

#### Evaporation rate

Not determined.

#### Information with regard to physical hazard classes

#### Explosives

Void

#### Flammable gases

Void

#### Aerosols

Extremely flammable aerosol.

Pressurised container: May burst if heated.

(Contd. on page 7)

GB



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 3.00 (replaces version 2.03)

Revision: 01.09.2022

Trade name: SONAX Soft Top &amp; Fabric Water Proof Impregnation

(Contd. of page 6)

Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

### SECTION 10: Stability and reactivity

**10.1 Reactivity** No dangerous reactions known.

**10.2 Chemical stability** Stable under normal conditions.

**10.3 Possibility of hazardous reactions** Develops readily flammable gases/fumes.

**10.4 Conditions to avoid**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

An increase in pressure may lead to bursting.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

**10.5 Incompatible materials:** strong oxidizing agents

**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity** Based on available data, the classification criteria are not met.

**LD/LC50 values relevant for classification:**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,800 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>23.3 mg/l (Ratte) (OECD 403)

**CAS: 67-63-0 propan-2-ol**

Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	13,900 mg/kg (rabbit)
Inhalative	LC50 / 6 h	>25 mg/l (rat) (OECD 403)

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>4,951 mg/m <sup>3</sup> (rat) (OECD 403)

**Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5,000 mg/m <sup>3</sup> (rat) (OECD 403)

**Hydrocarbons, C11-C13, isoalkanes,, <2% aromatics**

Oral	LD50	10,000 mg/kg (rat)
Dermal	LD50	3,160 mg/kg (rabbit)

(Contd. on page 8)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 3.00 (replaces version 2.03)

Revision: 01.09.2022

Trade name: SONAX Soft Top & Fabric Water Proof Impregnation

(Contd. of page 7)

**Skin corrosion/irritation** Repeated exposure may cause skin dryness or cracking.

**Serious eye damage/irritation** Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** May cause drowsiness or dizziness.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**Additional toxicological information:**

**Values relevant for classification:**

**CAS: 67-63-0 propan-2-ol**

Oral	NOAEL	400 mg/kg/day (rat)
------	-------	---------------------

**11.2 Information on other hazards**

**Endocrine disrupting properties**

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

## SECTION 12: Ecological information

**12.1 Toxicity**

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

**Aquatic toxicity:**

**Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics**

LL50 / 96h	>13.4 mg/l (Regenbogenforelle)
EL50 / 48h	3 mg/l (Daphnia magna)
EL50 / 72h	10-30 mg/l (Grünalge Pseudokirchneriella subcapitata)
NOELR 72 h	10 mg/l (Grünalge Pseudokirchneriella subcapitata)

**CAS: 106-97-8 butane**

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)

**CAS: 74-98-6 propane**

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 96 h	7.71 mg/l (algae)

**CAS: 67-63-0 propan-2-ol**

LC50 / 96h	9,640 mg/l (Pimephales promelas)
LC50 / 24h	9,714 mg/l (daphnia)
EC50	>100 mg/l (bacteria)
EC50 / 72h	>100 mg/l (algae)
LOEC	1,000 mg/l (algae)

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

LL50 / 96h	>10-<30 mg/l (Oncorhynchus mykiss)
EL50 / 48h	>22-<46 mg/l (Daphnia magna)
EL50 / 72h	>1,000 mg/l (Pseudokirchneriella subcapitata)
NOELR 72 h	<1 mg/l (Pseudokirchneriella subcapitata)

**Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics**

LLO 96 h	1,000 mg/l (Oncorhynchus mykiss)
----------	----------------------------------

(Contd. on page 9)



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 3.00 (replaces version 2.03)

Revision: 01.09.2022

**Trade name: SONAX Soft Top & Fabric Water Proof Impregnation**

(Contd. of page 8)

NOELR 72 h	>1,000 mg/l ( <i>Pseudokirchneriella subcapitata</i> )
NOELR 21d	≥1 mg/l ( <i>Daphnia magna</i> )
NOEC / 28d	0.209 mg/l ( <i>Oncorhynchus mykiss</i> )
ELO 48 h	>1,000 mg/l ( <i>Daphnia magna</i> )
ELO 72 h	>1,000 mg/l ( <i>Pseudokirchneriella subcapitata</i> )

**CAS: 75-28-5 isobutane**

LC50 / 96 h	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)

**12.2 Persistence and degradability**

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics**

Biodegradation	89 % (28d)
----------------	------------

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**

**PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

**vPvB:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

**12.6 Endocrine disrupting properties**

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

**12.7 Other adverse effects**

**Additional ecological information:**

**General notes:** The product may not be released into the environment without control.

### SECTION 13: Disposal considerations

**13.1 Waste treatment methods**

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

**Recommendation** Waste must be disposed of while observing the local, official regulations.

**European waste catalogue**

Disposal / product + Disposal / contaminated packaging

15 01 10*	packaging containing residues of or contaminated by dangerous substances
-----------	--

**Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

### SECTION 14: Transport information

**14.1 UN number or ID number**  
ADR/RID/ADN, IMDG, IATA

UN1950

**14.2 UN proper shipping name**  
ADR/RID/ADN  
IMDG  
IATA

1950 AEROSOLS  
AEROSOLS  
AEROSOLS, flammable

**14.3 Transport hazard class(es)**

ADR/RID/ADN



**Class**

2 5F Gases.

(Contd. on page 10)

**Safety data sheet**  
according to 1907/2006/EC, Article 31


Printing date 15.12.2023

Version: 3.00 (replaces version 2.03)

Revision: 01.09.2022

Trade name: SONAX Soft Top &amp; Fabric Water Proof Impregnation

(Contd. of page 9)

<b>Label</b>	2.1
<b>IMDG, IATA</b>	
	
<b>Class</b>	2.1 Gases.
<b>Label</b>	2.1
<b>14.4 Packing group</b> <b>ADR/RID/ADN, IMDG, IATA</b>	Void
<b>14.5 Environmental hazards:</b> <b>Marine pollutant:</b>	Yes absent due to package size =<5l
<b>14.6 Special precautions for user</b>	see Sections 6-8 Warning: Gases.
<b>14.7 Maritime transport in bulk according to IMO instruments</b>	Not applicable.
<b>Transport/Additional information:</b>	
<b>ADR/RID/ADN</b>	
<b>Limited quantities (LQ)</b>	1L
<b>Transport category</b>	2
<b>Tunnel restriction code</b>	D
<b>UN "Model Regulation":</b>	UN1950, AEROSOLS, 2.1

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

##### European Directives:

Directive 2010/75/EU (VOC) 95.10 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU)

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

REGULATION (EU) 2019/1148

#### Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

#### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

#### National regulations:

##### Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

(Contd. on page 11)

GB

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 3.00 (replaces version 2.03)

Revision: 01.09.2022

**Trade name: SONAX Soft Top & Fabric Water Proof Impregnation**

(Contd. of page 10)

H304 May be fatal if swallowed and enters airways.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.  
 H412 Harmful to aquatic life with long lasting effects.  
 EUH066 Repeated exposure may cause skin dryness or cracking.

**Classification according to Regulation (EC) No 1272/2008**

Aerosols, Section 2.3.1	On basis of test data
Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**Date of previous version:** 22.04.2021

**Version number of previous version:** 2.03

**Abbreviations and acronyms:**

vPvB: very persistent and very bioaccumulative

PBT: persistent, bioaccumulative, toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

**\* Data compared to the previous version altered.**