

**Safety data sheet
according to UK REACH**

Printing date 18.09.2024

Version: 1.01 (replaces version 1.00)

Revision: 30.11.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** SONAX Engine Starter**Article number:**

03121410

UFI: 4A35-G0JD-D00S-MW47**1.2 Relevant identified uses of the substance or mixture and uses advised against****Application of the substance / the mixture**

Car care product

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Aerosol 1	H222 Extremely flammable aerosol.
	H229 Pressurised container: May burst if heated.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.
Aquatic Chronic 3	H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS02 GHS07

Signal word Danger**Hazard-determining components of labelling:**

acetone

C6-7 Alkane/Cycloalkane

Hazard statements

H222 Extremely flammable aerosol.

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 1.01 (replaces version 1.00)

Revision: 30.11.2022

Trade name: SONAX Engine Starter

(Contd. of page 1)

H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/eye protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Formulation consisting of pressurised gas and solvents with additives

Dangerous components:

CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25-<50%
CAS: 1634-04-4 EINECS: 216-653-1 Reg.nr.: 01-2119452786-27-xxxx	tert-butyl methyl ether ⚠ Flam. Liq. 2, H225; ⚠ Skin Irrit. 2, H315	25-<50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10-<15%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 1.01 (replaces version 1.00)

Revision: 30.11.2022

Trade name: SONAX Engine Starter

(Contd. of page 2)

CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
EC No 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Alternative CAS number: 64742-49-0 ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<3%
CAS: 67-56-1 EINECS: 200-659-6 Reg.nr.: 01-2119433307-44-xxxx	methanol ⚠ Flam. Liq. 2, H225; ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT SE 1, H370; STOT SE 2, H371 Specific concentration limits: STOT SE 1; H370: C ≥ 10 % STOT SE 2; H371: 3 % ≤ C < 10 %	0-<1%

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out of danger area and lay down.

Remove soiled clothing

After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If symptoms persist consult doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Drowsiness

Nausea

Skin irritation

Eye irritation

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Foam

Carbon dioxide

Fire-extinguishing powder

Water haze

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Sulphur dioxide (SO₂)

(Contd. on page 4)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 1.01 (replaces version 1.00)

Revision: 30.11.2022

Trade name: SONAX Engine Starter

(Contd. of page 3)

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

For non-emergency personnel Keep away from ignition sources.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

GB

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 1.01 (replaces version 1.00)

Revision: 30.11.2022

Trade name: SONAX Engine Starter

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 75-28-5 isobutane

OEL (Ireland) Short-term value: 1000 ppm

CAS: 1634-04-4 tert-butyl methyl ether

WEL (Great Britain) Short-term value: 367 mg/m³, 100 ppm
Long-term value: 183.5 mg/m³, 50 ppm

IOELV (EU) Short-term value: 367 mg/m³, 100 ppm
Long-term value: 183.5 mg/m³, 50 ppm

OEL (Ireland) Short-term value: 367 mg/m³, 100 ppm
Long-term value: 183.5 mg/m³, 50 ppm
IOELV

CAS: 67-64-1 acetone

WEL (Great Britain) Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

IOELV (EU) Long-term value: 1210 mg/m³, 500 ppm

OEL (Ireland) Long-term value: 1210 mg/m³, 500 ppm
IOELV

CAS: 74-98-6 propane

OEL (Ireland) Asphx

CAS: 106-97-8 butane

WEL (Great Britain) Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

OEL (Ireland) Short-term value: 1000 ppm

CAS: 67-56-1 methanol

WEL (Great Britain) Short-term value: 333 mg/m³, 250 ppm
Long-term value: 266 mg/m³, 200 ppm
Sk

IOELV (EU) Long-term value: 260 mg/m³, 200 ppm
Skin

OEL (Ireland) Long-term value: 260 mg/m³, 200 ppm
Sk, IOELV

Regulatory information

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

WEL (Great Britain): EH40/2020

IOELV (EU): (EU) 2019/1831

DNELs

CAS: 1634-04-4 tert-butyl methyl ether

Oral	DNEL	7.1 mg/kg bw/day (vls)
Dermal	DNEL	3,570 mg/kg bw/day (vls) 5,100 mg/kg bw/day (wls)
Inhalative	DNEL	214 mg/m ³ (vll) 53.6 mg/m ³ (vls) 357 mg/m ³ (wll) 178.5 mg/m ³ (wls)

CAS: 67-64-1 acetone

Dermal DNEL 186 mg/kg (worker) (chronic systemic effect)

Inhalative DNEL 1,210 mg/m³ (worker) (chronic systemic effect)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral DNEL 699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 1.01 (replaces version 1.00)

Revision: 30.11.2022

Trade name: SONAX Engine Starter

(Contd. of page 5)

Dermal	DNEL	699 mg/kg bw/day (consumer) (chronic exposition / systemi effects) 773 mg/kg bw/day (worker) (chronic exposition / systemic effects)
Inhalative	DNEL	608 mg/m ³ (consumer) (chronic exposition / systemic effects) 2,035 mg/m ³ (worker) (chronic exposition / systemic effects)

PNECs

CAS: 1634-04-4 tert-butyl methyl ether

PNEC	71 mg/l (sewage plant) 4.72 mg/l (sporadic release) 5.1 mg/l (water (fresh water)) 0.26 mg/l (water (sea water))
PNEC	1.43 mg/kg (gro) 23 mg/kg (sediment (fresh water)) 1.17 mg/kg (sediment (sea water))

CAS: 67-64-1 acetone

PNEC	100 mg/l (STP) 10.6 mg/l (water (fresh water)) 1.06 mg/l (water (sea water))
PNEC	30.4 mg/kg (sediment (fresh water)) 3.04 mg/kg (sediment (sea water)) 29.5 mg/kg (soil)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Ensure good ventilation/exhaustion at the workplace.

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥480min)

Eye/face protection

Safety glasses

[EN 166]

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state

Fluid

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 1.01 (replaces version 1.00)

Revision: 30.11.2022

Trade name: SONAX Engine Starter

(Contd. of page 6)

Colour:	Colourless
Odour:	Solvent-like
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	-40 °C (Active ingredient data)
Flammability	Extremely flammable aerosol.
Lower and upper explosion limit	
Lower:	0.6 Vol %
Upper:	15 Vol %
Flash point:	Not applicable, as aerosol.
Decomposition temperature:	Not determined.
pH	Not applicable.
Viscosity:	
Kinematic viscosity at 40 °C	<20.5 mm ² /s (Active ingredient data)
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.74-0.75 g/cm ³ (Active ingredient data)
Vapour density	Not determined.

9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Not determined.
Explosive properties:	In use, may form flammable/explosive vapour-air mixture.
Change in condition	
Evaporation rate	Not applicable.

Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	>85% (percent by mass) flammable components, combustion energy >30 kJ/g Extremely flammable aerosol. Pressurised container: May burst if heated.
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 1.01 (replaces version 1.00)

Revision: 30.11.2022

Trade name: SONAX Engine Starter

(Contd. of page 7)

10.2 Chemical stability Stable under normal conditions.**10.3 Possibility of hazardous reactions** Develops readily flammable gases/fumes.**10.4 Conditions to avoid**

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents**10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:**CAS: 1634-04-4 tert-butyl methyl ether**

Oral LD50 >2,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rat)

Inhalative LC50 / 4h 85 mg/l (rat)

CAS: 67-64-1 acetone

Oral LD50 5,800 mg/kg (rat) (OECD 401)

Dermal LD 50 >15,800 mg/kg (rabbit)

Inhalative LC50 / 4h 76 mg/m³ (rat)**CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light**

Oral LD50 >5,000 mg/kg (rat)

Dermal LD50 >2,000 mg/kg (rabbit)

Inhalative LC50/4d >2 mg/l (rat)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral LD50 >5,000 mg/kg (rat) (OECD 401)

Dermal LD50 >2,920 mg/kg (rabbit) (OECD 402)

Inhalative LC50 / 4h >20 mg/l (rat) (OECD 403)

CAS: 67-56-1 methanol

Oral LD0 143 mg/kg (human)

LD50 5,628 mg/kg (rat)

Dermal LD50 15,800 mg/kg (rabbit)

LDLo 393 mg/kg (monkey)

Inhalative LC50/4d 83.8 mg/l

Skin corrosion/irritation Causes skin irritation.**Serious eye damage/irritation** Causes serious eye irritation.**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** May cause drowsiness or dizziness.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard** Based on available data, the classification criteria are not met.

(Contd. on page 9)

GB

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 1.01 (replaces version 1.00)

Revision: 30.11.2022

Trade name: SONAX Engine Starter

(Contd. of page 8)

Additional toxicological information:**Repeated dose toxicity****CAS: 1634-04-4 tert-butyl methyl ether**

Oral NOAEL 300 mg/kg (rat)

Inhalative NOAEL 800 ppm (rat)

11.2 Information on other hazards**Endocrine disrupting properties**

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

SECTION 12: Ecological information**12.1 Toxicity**

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

Aquatic toxicity:**CAS: 75-28-5 isobutane**

LC50 / 96 h 27.98 mg/l (fish)

EC50 / 4 d 7.71 mg/l (algae)

CAS: 1634-04-4 tert-butyl methyl etherNOEC / 31 d 299 mg/l (*Pimephales promelas*)LC50 / 96h 672 mg/l (*Oncorhynchus mykiss*)LC50 / 48h >1,000 mg/l (*Leuciscus idus melanotus*)EC10 710 mg/l (*Pseudomonas putida*)EC50 / 48h 651 mg/l (*Daphnia magna*)EC50 / 72h >800 mg/l (*Scenedesmus subspicatus*)IC50 / 96h 491 mg/l (*Pseudokirchneriella subcapitata*)NOEC / 21 d 51 mg/l (*Daphnia magna*)**CAS: 67-64-1 acetone**LC50 / 96 h 5,540 mg/l (*Oncorhynchus mykiss*)

LC50 / 48h 8,800 mg/l (dp)

EC50 / 0,5h 61.15 mg/l (microorganisms)

LOEC / 28 d 1,106-2,212 mg/l (*Daphnia magna*)NOEC / 28d 2,212 mg/l (*Daphnia magna*)**CAS: 74-98-6 propane**

LC50 / 96 h 27.98 mg/l (fish)

EC50 / 96 h 7.71 mg/l (algae)

CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light

LC50 / 96h 2.5 mg/l (fish)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexaneNOEC / 3 d >0.1-≤1 mg/l (*Daphnia magna*)LL50 / 96h 11.4 mg/l (*Oncorhynchus mykiss*) (OECD 203)EL50 / 48h 3 mg/l (*Daphnia magna*) (OECD 202)EL50 / 72h 30-100 mg/l (*Pseudokirchneriella subcapitata*) (OECD 201)LOEC 0.32 mg/l (*Daphnia magna*) (21d)NOEC / 72 h 3 mg/l (*Pseudokirchneriella subcapitata*)**CAS: 106-97-8 butane**

LC50 / 96 h 27.98 mg/l (fish)

EC50 / 4 d 7.71 mg/l (algae)

(Contd. on page 10)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 1.01 (replaces version 1.00)

Revision: 30.11.2022

Trade name: SONAX Engine Starter

(Contd. of page 9)

CAS: 67-56-1 methanol

LC50 / 96h	15,400 mg/l (Lepomis macrochirus) (OECD-Prüfrichtlinie 203)
EC50 / 16h	6,600 mg/l (Pseudomonas putida)
EC50 / 48h	>1,000 mg/l (Daphnia magna) (OECD-Prüfrichtlinie 202)

12.2 Persistence and degradability

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Biodegradation	81 % (28d)
----------------	------------

12.3 Bioaccumulative potential

CAS: 1634-04-4 tert-butyl methyl ether

log POW	0.94
log Kow	1.06

CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light

log POW	3.3-3.9
---------	---------

12.4 Mobility in soil

diethyl ether:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane:

Highly volatile, will partition rapidly to air.

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects

Additional ecological information:

General notes: The product may not be released into the environment without control.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10*	packaging containing residues of or contaminated by hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP14	Ecotoxic

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR/RID/ADN 1950 AEROSOLS
IMDG AEROSOLS
IATA AEROSOLS, flammable

(Contd. on page 11)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 1.01 (replaces version 1.00)

Revision: 30.11.2022

Trade name: SONAX Engine Starter

(Contd. of page 10)

14.3 Transport hazard class(es)

ADR/RID/ADN



Class 2 5F Gases.
Label 2.1

IMDG, IATA



Class 2.1 Gases.
Label 2.1

14.4 Packing group

ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: Yes
absent due to package size =<5l

14.6 Special precautions for user see Sections 6-8
Warning: Gases.

Transport/Additional information:

ADR/RID/ADN

Limited quantities (LQ) 1L
Transport category 2
Tunnel restriction code D

UN "Model Regulation": UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Directives:

Directive 2010/75/EU (VOC) 91.67 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) P3a FLAMMABLE AEROSOLS

REGULATION (EU) 2019/1148

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

CAS: 67-64-1 | acetone

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 12)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 1.01 (replaces version 1.00)

Revision: 30.11.2022

Trade name: SONAX Engine Starter

(Contd. of page 11)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.
 H225 Highly flammable liquid and vapour.
 H280 Contains gas under pressure; may explode if heated.
 H301 Toxic if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H311 Toxic in contact with skin.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H336 May cause drowsiness or dizziness.
 H370 Causes damage to organs.
 H371 May cause damage to organs.
 H411 Toxic to aquatic life with long lasting effects.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

Aerosols, Section 2.3.1	On basis of test data
Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Date of previous version: 01.09.2022

Version number of previous version: 1.00

Abbreviations and acronyms:

vPvB: very persistent and very bioaccumulative
 PBT: persistent, bioaccumulative, toxic
 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 NOEL = No Observed Effect Level
 NOEC = No Observed Effect Concentration
 LC = letal Concentration
 EC50 = half maximal effective concentration
 log POW = Octanol / water partition coefficient
 GHS: Globally Harmonized System of Classification and Labelling of Chemicals
 ATE: acute toxicity estimate
 ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 DNEL: Derived No-Effect Level (UK REACH)
 PNEC: Predicted No-Effect Concentration (UK REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 IOELV = indicative occupational exposure limit values
 Flam. Gas 1A: Flammable gases – Category 1A
 Aerosol 1: Aerosols – Category 1
 : Aerosols – Category 3
 Press. Gas (Comp.): Gases under pressure – Compressed gas
 Flam. Liq. 2: Flammable liquids – Category 2
 Acute Tox. 3: Acute toxicity – Category 3
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
 STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 Asp. Tox. 1: Aspiration hazard – Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3