

Printing date 18.09.2024

Version: 5.01 (replaces version 5.00)

Revision: 25.07.2024

Printing date 18.09.2024	Version: 5.01 (replaces version 5.00)	Revision: 25.07.2024
SECTION 1: Identification	n of the substance/mixture and of th	e company/undertaking
1.1 Product identifier		
Trade name: <u>SONAX Cockpit S</u>	Spray New Car	
Application of the substance / Car care product Detergents Consumer uses: Private househ Professional uses	f the substance or mixture and uses advised the mixture olds / general public / consumers currently no information available on this.	l against
1.3 Details of the supplier of th Manufacturer/Supplier: SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0	ne safety data sheet	
<i>Further information obtainable</i> Product safety E-mail: erp@sonax.de Phone: + +49 (0) 8431 53 217 <u>United Kingdom:</u> Anglo American Oil Company Lt 58 Holton Road, Holton Heath T Telephone: (+44) 01929 551557 Email: info@aaoil.co.uk	d rading Park, Poole, Dorset, BH16 6LT	
1.4 Emergency telephone num <u>European Union:</u> +49 (0) 89 19 <u>United Kingdom:</u> 0344 892 01 Members of Public in England, S In Northern Ireland, contact your	240 (Poison Centre Munich) 11 (UK NPIS) Scotland and Wales can contact NHS 111/NHS	24 by dialling 111
	/* * * /*	
2.2 Label elements Labelling according to Regula	ance or mixture gulation (EC) No 1272/2008 mable aerosol. ntainer: May burst if heated.	
GHS02		
	y burst if heated. f children. at, hot surfaces, sparks, open flames and other open flame or other ignition source.	rignition sources. No smoking.

- P251 Do not pierce or burn, even after use.
- P260 Do not breathe spray.

(Contd. on page 2)



Printing date 18.09.2024

Version: 5.01 (replaces version 5.00)

Revision: 25.07.2024

Trade name: SONAX Cockpit Spray New Car

(Contd. of page 1)

P271 Use only outdoors or in a well-ventilated area.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations. *Additional information:*

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Formulation consisting of pressurised gas and solvents with additives

Dangerous components:		
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	_ 20-<25%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	_ 20-<25%
EC No 934-956-3 Reg.nr.: 01-2119827000-58-xxxx	Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7 � Asp. Tox. 1, H304	15-<20%
EC No 934-954-2 Reg.nr.: 01-2119826592-36-xxxx	Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7 & Asp. Tox. 1, H304	10-<15%
EINECS: 265-149-8 Reg.nr.: 01-2119453414-43-xxxx	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8	10-<15%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane	5-<10%
Regulation (EC) No 648/2004 or	n detergents / Labelling for contents	
aliphatic hydrocarbons		≥30%
perfumes (TETRAMETHYL ACE	TYLOCTAHYDRONAPHTHALENES)	
Additional information: For the	wording of the listed hazard phrases refer to section 16.	•

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air. Remove soiled clothing **After inhalation:** Supply fresh air.

(Contd. on page 3)

⁻ GB



Printing date 18.09.2024

Version: 5.01 (replaces version 5.00)

Revision: 25.07.2024

(Contd. of page 2)

Trade name: SONAX Cockpit Spray New Car

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact: Wash the areas of skin affected with water and a mild detergent. After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing agents: Foam Carbon dioxide Fire-extinguishing powder Water haze For safety reasons unsuitable extinguishing agents: Water with full jet 5.2 Special hazards arising from the substance or mixture In case of fire, the following can be released: Carbon monoxide (CO) Carbon dioxide (CO2) Nitrogen oxides (NOx) 5.3 Advice for firefighters Protective equipment: Do not inhale explosion gases or combustion gases. Wear fully protective suit. Do not enter the hazardous area without a self-contained breathing apparatus. See Section 8 for information on personal protection equipment. Additional information Cool endangered receptacles with water spray. Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation For non-emergency personnel
Keep away from ignition sources.
Particular danger of slipping on leaked/spilled product.
For emergency responders Wear protective equipment. Keep unprotected persons away.
6.2 Environmental precautions:
Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

(Contd. on page 4)



Printing date 18.09.2024

Safety data sheet according to UK REACH

Version: 5.01 (replaces version 5.00)

Revision: 25.07.2024

Trade name: SONAX Cockpit Spray New Car

Destination of an other than the	and a second la sublement as di nter () and () and ()	(Contd. of page 3)
	ures possible without sufficient ventilation. and explosion protection:	
Keep ignition s	sources away - Do not smoke.	
Pressurized container: pro pierce or burn, even after	otect from sunlight and do not expose to temperatures exc	eeding 50°C. Do not
	use. d flame or any incandescent material.	
	constituents are released during processing.	
Protect against electrosta	tic charges.	
	storage, including any incompatibilities	
Storage: Poquiromonts to be mot	by storerooms and receptacles:	
Provide solvent resistant,		
	ns on storing packagings with pressurised containers.	
Information about storag	ge in one common storage facility:	
Store away from foodstuff		
Observe local/state/federa Further information abo		
Further information abo	ut storade conditions:	
Store receptacle in a well	ventilated area.	urstina
Store receptacle in a well Store in a cool place. Hea	ventilated area. at will increase pressure and may lead to the receptacle bu	ırsting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te	ventilated area. at will increase pressure and may lead to the receptacle bu ect sunlight. emperature: 20 °C.	ırsting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te	ventilated area. at will increase pressure and may lead to the receptacle bu act sunlight.	ırsting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te	ventilated area. at will increase pressure and may lead to the receptacle bu ect sunlight. emperature: 20 °C.	ırsting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I	ventilated area. at will increase pressure and may lead to the receptacle bu ect sunlight. emperature: 20 °C.	ırsting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I SECTION 8: Exposu	ventilated area. at will increase pressure and may lead to the receptacle bu ect sunlight. emperature: 20 °C. No further relevant information available.	ırsting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I SECTION 8: Exposu 8.1 Control parameters	ventilated area. at will increase pressure and may lead to the receptacle bu ect sunlight. emperature: 20 °C. No further relevant information available.	ursting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) f SECTION 8: Exposu 8.1 Control parameters Ingredients with limit va	ventilated area. at will increase pressure and may lead to the receptacle bu ect sunlight. emperature: 20 °C. No further relevant information available. Ire controls/personal protection	ırsting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I SECTION 8: Exposu 8.1 Control parameters Ingredients with limit va CAS: 106-97-8 butane	ventilated area. at will increase pressure and may lead to the receptacle bu ect sunlight. emperature: 20 °C. No further relevant information available. Ire controls/personal protection Ilues that require monitoring at the workplace: Short-term value: 1810 mg/m ³ , 750 ppm	ursting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I SECTION 8: Exposu 8.1 Control parameters Ingredients with limit va CAS: 106-97-8 butane	ventilated area. at will increase pressure and may lead to the receptacle bu ect sunlight. emperature: 20 °C. No further relevant information available. Ire controls/personal protection Ilues that require monitoring at the workplace: Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm	ursting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I SECTION 8: Exposu 8.1 Control parameters Ingredients with limit va CAS: 106-97-8 butane	ventilated area. at will increase pressure and may lead to the receptacle bu- act sunlight. amperature: 20 °C. No further relevant information available. Ire controls/personal protection Ilues that require monitoring at the workplace: Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)	ursting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I SECTION 8: Exposu 8.1 Control parameters Ingredients with limit va CAS: 106-97-8 butane WEL (Great Britain) OEL (Ireland)	ventilated area. at will increase pressure and may lead to the receptacle bu ect sunlight. emperature: 20 °C. No further relevant information available. Ire controls/personal protection Ilues that require monitoring at the workplace: Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm	ursting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I SECTION 8: Exposu 8.1 Control parameters Ingredients with limit va CAS: 106-97-8 butane WEL (Great Britain) OEL (Ireland) CAS: 74-98-6 propane	ventilated area. at will increase pressure and may lead to the receptacle bu- act sunlight. amperature: 20 °C. No further relevant information available. Ire controls/personal protection Ilues that require monitoring at the workplace: Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)	<i>ursting.</i>
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I SECTION 8: Exposu 8.1 Control parameters Ingredients with limit va CAS: 106-97-8 butane WEL (Great Britain) OEL (Ireland) CAS: 74-98-6 propane OEL (Ireland)	ventilated area. at will increase pressure and may lead to the receptacle bu- pert sunlight. emperature: 20 °C. No further relevant information available. Ire controls/personal protection Iues that require monitoring at the workplace: Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1810 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) Short-term value: 1000 ppm Asphx	<i>ursting.</i>
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I SECTION 8: Exposu 8.1 Control parameters Ingredients with limit va CAS: 106-97-8 butane WEL (Great Britain) OEL (Ireland) CAS: 74-98-6 propane OEL (Ireland) Hydrocarbons, C13-C16	ventilated area. at will increase pressure and may lead to the receptacle bu- act sunlight. amperature: 20 °C. No further relevant information available. Ire controls/personal protection Ilues that require monitoring at the workplace: Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1850 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) Short-term value: 1000 ppm Asphx , n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	ursting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I SECTION 8: Exposu 8.1 Control parameters Ingredients with limit va CAS: 106-97-8 butane WEL (Great Britain) OEL (Ireland) CAS: 74-98-6 propane OEL (Ireland) Hydrocarbons, C13-C16, GERMAN RCP-METHOD	ventilated area. at will increase pressure and may lead to the receptacle buget sunlight. emperature: 20 °C. No further relevant information available. Ire controls/personal protection Ilues that require monitoring at the workplace: Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) Short-term value: 1000 ppm Asphx G. n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	ursting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I SECTION 8: Exposu 8.1 Control parameters Ingredients with limit va CAS: 106-97-8 butane WEL (Great Britain) OEL (Ireland) CAS: 74-98-6 propane OEL (Ireland) Hydrocarbons, C13-C16, GERMAN RCP-METHOD	ventilated area. at will increase pressure and may lead to the receptacle buget sunlight. emperature: 20 °C. No further relevant information available. Ire controls/personal protection Ilues that require monitoring at the workplace: Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) Short-term value: 1000 ppm Asphx G. n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	ursting.
Store receptacle in a well Store in a cool place. Hea Protect from heat and dire Recommended storage te 7.3 Specific end use(s) I SECTION 8: Exposu 8.1 Control parameters Ingredients with limit va CAS: 106-97-8 butane WEL (Great Britain) OEL (Ireland) CAS: 74-98-6 propane OEL (Ireland) Hydrocarbons, C13-C16 GERMAN RCP-METHOD Hydrocarbons, C12-C15	ventilated area. at will increase pressure and may lead to the receptacle buget sunlight. emperature: 20 °C. No further relevant information available. Ire controls/personal protection Ilues that require monitoring at the workplace: Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene) Short-term value: 1000 ppm Asphx G. n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	ursting.

CAS: 75-28-5 isobutane

OEL (Ireland) Short-term value: 1000 ppm

Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

(Contd. on page 5)

SONAX®

Printing date 18.09.2024

Safety data sheet according to UK REACH

Version: 5.01 (replaces version 5.00)

Revision: 25.07.2024

Trade name: SONAX Cockpit Spray New Car

	(Contd. of page 4)
Individual protection measures, such as personal protective equipment	
General protective and hygienic measures:	
The usual precautionary measures are to be adhered to when handling chemicals.	
Wash hands before breaks and at the end of work.	
Keep away from foodstuffs, beverages and feed.	
Respiratory protection:	
If the occupational exposure limit is exceeded:	
The following breathing protection is recommended:	
Respiratory filter for organic gases and vapours (Type A)	
Identification colour: Brown	
[DIN EN 14387]	
Hand protection Not required in normal cases.	
Eye/face protection Not required in normal cases	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical pr	operties
General Information	
Physical state	Fluid
Colour:	Colourless
Odour:	Wooden
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling	
range	Not applicable, as aerosol.
Flammability	Extremely flammable aerosol.
Lower and upper explosion limit	
Lower:	1.5 Vol % (CAS: 106-97-8 butane)
Upper:	10.9 Vol % (CAS: 74-98-6 propane)
Flash point:	Not applicable, as aerosol.
Decomposition temperature:	Not determined.
рН	Not applicable.
Viscosity:	··
Kinematic viscosity at 40 °C	<20.5 mm²/s
···· ·	(Active ingredient data)
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 20 °C:	0.8-0.82 g/cm ³
	(Active ingredient data)
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Aerosol
Important information on protection of health and	
environment, and on safety.	
Ignition temperature:	Not determined.
Explosive properties:	In use, may form flammable/explosive vapour-air
	mixture.
Change in condition	mixture.
Evaporation rate	Not applicable.
Information with regard to physical hazard classes	
Explosives	Void
Flammable gases	Void
Aerosols	
Extremely flammable aerosol.	
Pressurised container: May burst if heated.	
Oxidising gases	Void
Gases under pressure	Void
	(Contd. on page 6)
	GE



GB



Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 5.01 (replaces version 5.00)

Revision: 25.07.2024

Trade name: SONAX Cockpit Spray New Car

		(Contd. of page 5)
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.

10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met.

Hvdrocar	bons. C15-	C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)	
Inhalative	LC50 / 4h	>5.266 mg/m ³ (rat) (OECD 403)	
Hydrocar	bons, C13-	C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)	
Inhalative	LC50 / 4h	>5.266 mg/m³ (rat) (OECD 403)	
Hydrocar	bons, C12-	C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)	
Inhalative	LC50 / 4h	>5.6 mg/m³ (rat) (OECD 403)	
Skin corre	osion/irrita	tion Based on available data, the classification criteria are not met.	
Serious e	ye damage	/irritation Based on available data, the classification criteria are not met.	
Respirato	ry or skin	sensitisation Based on available data, the classification criteria are not m	et.
Germ cell	mutageni	city Based on available data, the classification criteria are not met.	
Carcinog	enicity Bas	ed on available data, the classification criteria are not met.	
Reproduc	tive toxici	y Based on available data, the classification criteria are not met.	
STOT-sin	gle exposi	re Based on available data, the classification criteria are not met.	
			(Contd. on page



Printing date 18.09.2024

Safety data sheet according to UK REACH

Version: 5.01 (replaces version 5.00)

Revision: 25.07.2024

Trade name: SONAX Cockpit Spray New Car

(Contd. of page 6)

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

SECTION 12: Ecological information

Aquatic toxic CAS: 106-97	-
	27.98 mg/l (fish)
	7.71 mg/l (algae)
CAS: 74-98-0	
	27.98 mg/l (fish)
	7.71 mg/l (algae)
	n <mark>s, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics</mark> >1,028 mg/l (Scophtalamus maximus) (OECD 203)
	>3,193 mg/l (Acartia tonsa)
	>1,000 mg/l (Daphnia magna)
	>1,000 mg/l (Oncorhynchus mykiss)
LC50 / 3 d	>10,000 mg/l (Skeletonema costatum)
•	ns, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics
	>3,193 mg/l (Acartia tonsa)
LC50 / 4 d	>1,028 mg/l (Scophtalamus maximus) (OECD 203)
	>1,000 mg/l (Daphnia magna)
	>1,000 mg/l (Oncorhynchus mykiss)
EC50 / 3 d	>10,000 mg/l (Skeletonema costatum)
•	ns, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
LC50 / 2 d	>1,000 mg/l (Daphnia magna) (OECD 202)
LC50 / 4 d	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)
	>1,000 mg/l (Daphnia magna)
	>1,000 mg/l (Oncorhynchus mykiss)
	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
CAS: 75-28-	
	27.98 mg/l (fish)
EC50 / 4 d	7.71 mg/l (algae)
	ence and degradability
•	ns, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics
Biodegradatio	
Hydrocarboı	ns, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics
Biodegradatio	
-	ns, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Biodegradatio	
12.3 Bioaccu	imulative potential No further relevant information available. In soil No further relevant information available.

- GB -



Printing date 18.09.2024

Safety data sheet according to UK REACH

Version: 5.01 (replaces version 5.00)

Revision: 25.07.2024

(Contd. of page 7)

Trade name: SONAX Cockpit Spray New Car

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT **vPvB**:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue Disposal / product + Disposal / contaminated packaging

Disposal / product + Disposal / contaminated packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name ADR/RID/ADN IMDG IATA	1950 AEROSOLS AEROSOLS AEROSOLS, flammable
14.3 Transport hazard class(es))
ADR/RID/ADN	
Class	2 5F Gases.
Label	2.1
IMDG, IATA	
Class	2.1 Gases.
Label	2.1
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	Νο
14.6 Special precautions for us	er Warning: Gases.
	(Contd. on page



Printing date 18.09.2024

Version: 5.01 (replaces version 5.00)

Revision: 25.07.2024

Trade name: SONAX Cockpit Spray New Car

	(Contd. of page 8
Transport/Additional informa	tion:
ADR/RID/ADN	
Limited quantities (LQ)	1L
Transport category	2
Tunnel restriction code	D
UN "Model Regulation":	UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) 50.60 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) P3a FLAMMABLE AEROSOLS REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

Aerosols, Section 2.3.1 On basis of test data

Date of previous version: 26.07.2022

Version number of previous version: 5.00

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent IOELV = indicative occupational exposure limit values

(Contd. on page 10)

Abbreviations and acronyms:



Printing date 18.09.2024

Version: 5.01 (replaces version 5.00)

Revision: 25.07.2024

Trade name: SONAX Cockpit Spray New Car

Flam. Gas 1A: Flammable gases – Category 1A Aerosol 1: Aerosols – Category 1 : Aerosols – Category 3 Press. Gas (Comp.): Gases under pressure – Compressed gas Asp. Tox. 1: Aspiration hazard – Category 1 * Data compared to the previous version altered. (Contd. of page 9)

GB