

Printing date 24.09.2024 Version: 3.00 (replaces version 2.00) Revision: 20.06.2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX PROFILINE HEADLIGHTPOLISH

Article number: 02761410

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Car care product

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

# SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

2.3 Other hazards

Results of PBT and vPvB assessment

PRT.

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

#### SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Emulsion of solvents, abrasives and additives

(Contd. on page 2)



Printing date 24.09.2024 Version: 3.00 (replaces version 2.00) Revision: 20.06.2022

Trade name: SONAX PROFILINE HEADLIGHTPOLISH

(Contd. of page 1) Dangerous components: CAS: 72623-86-0 5-<10% Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-EINECS: 276-737-9 based Reg.nr.: 01-2119474878-16-XXXX 🕸 Asp. Tox. 1, H304 CAS: 56-81-5 glycerol 3-<5% EINECS: 200-289-5 substance with a Community workplace exposure limit EC No 934-956-3 Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 3-<5% Reg.nr.: 01-2119827000-58-xxxx 0.03% aromatics Alternative CAS number: 64742-46-7 🗞 Asp. Tox. 1, H304 CAS: 107-98-2 1-Methoxy-2-propanol 1-<5% EINECS: 203-539-1 🚸 Flam. Lig. 3, H226; 伙 STOT SE 3, H336 Reg.nr.: 01-2119457435-35-xxxx EC No 934-954-2 Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 1-<3% Reg.nr.: 01-2119826592-36-xxxx 0.03% aromatics Alternative CAS number: 64742-46-7 🗞 Asp. Tox. 1, H304 EINECS: 265-149-8 Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% 1-<3% Reg.nr.: 01-2119453414-43-xxxx aromatics Alternative CAS number: 64742-47-8 🗞 Asp. Tox. 1, H304, EUH066

# SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Remove soiled clothing

After inhalation: Supply fresh air.

After skin contact: Wash the areas of skin affected with water and a mild detergent.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Additional information: For the wording of the listed hazard phrases refer to section 16.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

# SECTION 5: Firefighting measures

5.1 Extinguishing media

**Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

# SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation **For non-emergency personnel** Wear protective clothing.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Pick up mechanically.

(Contd. on page 3)



Printing date 24.09.2024 Version: 3.00 (replaces version 2.00) Revision: 20.06.2022

Trade name: SONAX PROFILINE HEADLIGHTPOLISH

(Contd. of page 2)

Absorb liquid components with liquid-binding material.

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

**7.1 Precautions for safe handling** No special precautions are necessary if used correctly. **Information about fire - and explosion protection:** No special measures required.

# 7.2 Conditions for safe storage, including any incompatibilities Storage:

Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor. Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:			
CAS: 56-81-5 glycerol			
WEL (Great Britain)	Long-term value: 10 mg/m³		
OEL (Ireland)	Long-term value: 10 mg/m³		
CAS: 107-98-2 1-Methoxy-2-pa	ropanol		
WEL (Great Britain)	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Sk		
IOELV (EU)	Short-term value: 568 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Skin		
OEL (Ireland)	Short-term value: 568 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm IOELV		
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics			
GERMAN RCP-METHOD (EU)	Long-term value: 300 mg/m³ 2 (II) / AGW (German TRGS 900)		
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
GERMAN RCP-METHOD (EU)	Long-term value: 300 mg/m³ 2 (II) / AGW (German TRGS 900)		

## Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

IOELV (EU): (EU) 2019/1831

	DNELs			
ſ	CAS: 726	23-86-0	Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	
ſ	Inhalative	DNEL	1.2 mg/m³ (consumer) (local / longterm (repeated))	
			5.4 mg/m³ (worker) (local / longterm (repeated))	
_				(Contd. on nogo 1)

(Contd. on page 4)



Printing date 24.09.2024 Version: 3.00 (replaces version 2.00) Revision: 20.06.2022

Trade name: SONAX PROFILINE HEADLIGHTPOLISH

CAS: 107-98-2 1-Methoxy-2-propanol

Oral DNEL 3.3 mg/kg (consumer) (long-term / systemic effects)

Dermal DNEL 18.1 mg/kg (consumer) (long-term / systemic effects)

50.6 mg/kg (worker) (long-term / systemic effects)

Inhalative DNEL 43.9 mg/m³ (consumer) (long-term / systemic effects)

553.5 mg/m³ (worker) (short-term / local effects)

DNEL 369 mg/m³ (worker) (long-term / systemic effects)

#### **PNECs**

# CAS: 107-98-2 1-Methoxy-2-propanol

PNEC 100 mg/l (STP)

100 mg/l (water (intermittent release))

10 mg/l (water (fresh water)) 1 mg/l (water (sea water))

PNEC 2.47 mg/kg (gro)

41.6 mg/kg (sediment (fresh water)) 4.17 mg/kg (sediment (sea water))

Additional information: The lists valid during the making were used as basis.

#### 8.2 Exposure controls

### Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

# Individual protection measures, such as personal protective equipment

## General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

#### Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Hand protection Not required in normal cases.

Eye/face protection Not required in normal cases

# SECTION 9: Physical and chemical properties

# 9.1 Information on basic physical and chemical properties

General Information

Physical stateFluidColour:WhiteOdour:Solvent-likeMelting point/freezing point:Undetermined.

Boiling point or initial boiling point and boiling

range Undetermined.
Flammability Product is not flammable.

Lower and upper explosion limit

Lower:Not determined.Upper:Not determined.Flash point:Not applicable.Decomposition temperature:Not determined.pHNot determined.

Viscosity:

Kinematic viscosity at 40 °C >20.5 mm<sup>2</sup>/s

Solubility

water:Partity miscible.Partition coefficient n-octanol/water (log value)Not determined.Vapour pressure:Not determined.

(Contd. on page 5)



Printing date 24.09.2024 Version: 3.00 (replaces version 2.00) Revision: 20.06.2022

Trade name: SONAX PROFILINE HEADLIGHTPOLISH

(Contd. of page 4) Density and/or relative density Density at 20 °C: 0.99-1.01 g/cm3 Vapour density Not determined. 9.2 Other information Appearance: Form: Pasty Important information on protection of health and environment, and on safety. Ignition temperature: Product is not selfigniting. Explosive properties: Product does not present an explosion hazard. Change in condition Evaporation rate Not determined Information with regard to physical hazard classes **Explosives** Void Flammable gases Void Aerosols Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void **Oxidising liquids** Void Void

Void

Void

Void

# SECTION 10: Stability and reactivity

Oxidising solids Organic peroxides

Corrosive to metals

Desensitised explosives

- 10.1 Reactivity No dangerous reactions known.
- 10.2 Chemical stability Stable under normal conditions.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid See Section 7 for information on safe handling.
- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:		
CAS: 72623-86-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based		
Oral	LD50	>5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4d	>5,000 mg/l (rat)
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5.266 mg/m³ (rat) (OECD 403)
		(Contd. on pag

on page o



Printing date 24.09.2024 Version: 3.00 (replaces version 2.00) Revision: 20.06.2022

Trade name: SONAX PROFILINE HEADLIGHTPOLISH

		(Contd. of pag
CAS: 107-	98-2 1-Met	thoxy-2-propanol
Oral	LD50	4,016 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
Inhalative	LC0 / 6h	>7,000 ppm (rat)
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>3,160 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5.266 mg/m³ (rat) (OECD 403)
Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50 / 4h	>5.6 mg/m³ (rat) (OECD 403)

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

#### Aspiration hazard

Viscosity: > 20,5mm²/s (40°C)

Based on available data, the classification criteria are not met.

#### 11.2 Information on other hazards

# Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

# **SECTION 12: Ecological information**

12.1 Toxicity There are no ecotoxicological data available on this mixture.

NOEC / 2 d	≥10,000 mg/l (Daphnia magna) (OECD 202)
LC50 / 96h	>100 mg/l (fish)
EC50 / 48h	>10,000 mg/l (Daphnia magna) (OECD 202)
ErC 50 / 72h	>100 mg/l (algae)
NOEC 96h	≥100 mg/l (fish) (OECD 203)
NOEC / 21 d	≥10 mg/l (Daphnia magna) (OECD 211)
NOEC / 72 h	≥100 mg/l (algae)
Hydrocarbon	ns, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics
LC50 / 4 d	>1,028 mg/l (Scophtalamus maximus) (OECD 203)
LC50 / 48h	>3,193 mg/l (Acartia tonsa)
NOEC / 21 d	>1,000 mg/l (Daphnia magna)
NOEC / 28d	>1,000 mg/l (Oncorhynchus mykiss)
LC50 / 3 d	>10,000 mg/l (Skeletonema costatum)
CAS: 107-98-	-2 1-Methoxy-2-propanol



Printing date 24.09.2024 Version: 3.00 (replaces version 2.00) Revision: 20.06.2022

Trade name: SONAX PROFILINE HEADLIGHTPOLISH

		(Contd. of page 6)		
LC50 / 48h	23,300 mg/l (Daphnia magna)	(Conta. or page o)		
EC50	>1,000 mg/l (Pseudokirchneriella subcapitata) (7d)			
EC50/3h	>1,000 mg/l (activated sludge) (OECD 209)			
Hydrocarbon	s, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics			
LC50 / 2 d	>3,193 mg/l (Acartia tonsa)			
LC50 / 4 d	>1,028 mg/l (Scophtalamus maximus) (OECD 203)			
NOEC / 21 d	>1,000 mg/l (Daphnia magna)			
NOEC / 28d	>1,000 mg/l (Oncorhynchus mykiss)			
EC50 / 3 d	>10,000 mg/l (Skeletonema costatum)			
Hydrocarbon	s, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
LC50 / 2 d	>1,000 mg/l (Daphnia magna) (OECD 202)			
LC50 / 4 d	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)			
NOEC / 21 d	>1,000 mg/l (Daphnia magna)			
NOEC / 28d	>1,000 mg/l (Oncorhynchus mykiss)			
EC50 / 3 d	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)			
12.2 Persiste	12.2 Persistence and degradability			
	6-0 Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based			
Biodegradation >60 % (28d)				
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics				
Biodegradatio	Biodegradation 74 %			
CAS: 107-98-2 1-Methoxy-2-propanol				
Biodegradation 90-100 % (OEECD 301E)				
Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics				
Biodegradation 74 %				
1 -	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
Biodegradatio	n 67.6 %			
12.3 Bioaccui	mulative potential			
	CAS: 107-98-2 1-Methoxy-2-propanol			
log Kow ≤0.43 (25°C)				

12.4 Mobility in soil No further relevant information available.

# 12.5 Results of PBT and vPvB assessment

#### PBT:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

#### vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

# 12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

# 12.7 Other adverse effects

# Additional ecological information:

General notes: The product may not be released into the environment without control.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Not classified as hazardous waste according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

### European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

20 01 13\* solvents

(Contd. on page 8)



Printing date 24.09.2024 Version: 3.00 (replaces version 2.00) Revision: 20.06.2022

Trade name: SONAX PROFILINE HEADLIGHTPOLISH

(Contd. of page 7)

15 01 02 plastic packaging

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

# SECTION 14: Transport information

14.1 UN number or ID number
ADR/RID/ADN. IMDG. IATA Void

ADR/RID/ADN, IMDG, IATA VOIC

14.2 UN proper shipping name
ADR/RID/ADN, IMDG, IATA Void

14.3 Transport hazard class(es)

ADR/RID/ADN, ADN, IMDG, IATA

Class Void

14.4 Packing group

ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Not applicable.

UN "Model Regulation": Void

# SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

The following substance(s) in this product is (are) identified by CAS number either in countries not subject to the UK REACH regulation or in regulations not yet updated with the new naming convention for hydrocarbon solvents.

Hydrocarbons, C14-C19, isoalkanes, cyclics, < 2% aromatics: CAS 64742-46-7

European Directives:

Directive 2010/75/EU (VOC) 6.00 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing

under Article 5(3))

None of the ingredients is listed.

### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

### National regulations:

# Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

EUH066 Repeated exposure may cause skin dryness or cracking.

Date of previous version: 12.04.2022

(Contd. on page 9)



Printing date 24.09.2024 Version: 3.00 (replaces version 2.00) Revision: 20.06.2022

Trade name: SONAX PROFILINE HEADLIGHTPOLISH

(Contd. of page 8)

### Version number of previous version: 2.00 Abbreviations and acronyms:

RID: Reglement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent IOELV = indicative occupational exposure limit values

Flam. Liq. 3: Flammable liquids - Category 3

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

\* Data compared to the previous version altered.



Printing date 24.09.2024 Version: 2.00 (replaces version 1.00) Revision: 05.07.2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

# 1.1 Product identifier

Trade name: SONAX PROFILINE Headlight Coating

Article number: 02765410

UFI: 8KN3-S0XJ-T00Y-Y1HM

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Car care product

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.

# 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

# Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

# SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

#### 2.2 Label elements

# Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

# Hazard pictograms





GHS02 GHS05

## Signal word Danger Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

(Contd. on page 2)



Revision: 05.07.2022 Printing date 24.09.2024 Version: 2.00 (replaces version 1.00)

### Trade name: SONAX PROFILINE Headlight Coating

(Contd. of page 1)

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/eye protection. P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P310 P332+P313 If skin irritation occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### Labelling of packages where the contents do not exceed 125 ml

Marking container <125 ml deviates. Reduced labeling according article 29 and annex I, no. 1.5 GB CLPregulation is used.

#### 2.3 Other hazards

Product hydrolyses under formation of methanol (CAS no. 67-56-1). Methanol is toxic by inhalation, in contact with skin and if swallowed. Methanol causes damage to organs. Methanol is highly flammable. Inhalation of aerosol spray may damage health.

#### Results of PBT and vPvB assessment

#### PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

#### vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

#### Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Description: Surface sealing made from additives and modified silicones in solvents

Dangerous components:		
CAS: 13475-82-6 EINECS: 297-629-8	2,2,4,6,6-pentamethylheptane Alternative CAS number: 93685-81-5 Flam. Liq. 3, H226;	25-<50%
CAS: 5593-70-4 EINECS: 227-006-8 Reg.nr.: 01-2119967423-33-xxxx	Tetrabutyltitanate ♠ Flam. Liq. 3, H226; ♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315; STOT SE 3, H335; STOT SE 3, H336	5-<10%
CAS: 162303-51-7	Polymer of tetra-n-butyl titanate and water Alternative CAS number: 9022-96-2 Flam. Liq. 3, H226;  Eye Dam. 1, H318;  Skin Irrit. 2, H315; STOT SE 3, H335; STOT SE 3, H336	5-<10%

Additional information: For the wording of the listed hazard phrases refer to section 16.

# SECTION 4: First aid measures

# 4.1 Description of first aid measures

#### General information:

Take affected persons out into the fresh air.

Remove soiled clothing

In any cases of doubt or if symptoms are present, seek medical advice.

### After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately .

(Contd. on page 3)



Printing date 24.09.2024 Version: 2.00 (replaces version 1.00) Revision: 05.07.2022

Trade name: SONAX PROFILINE Headlight Coating

(Contd. of page 2)

#### After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

#### After swallowing:

Do not induce vomiting; call for medical help immediately.

Rinse out mouth and then drink plenty of water.

#### 4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

**Drowsiness** 

Nausea

Cramp

Eye irritation / Eye damage

Skin irritation

#### 4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

# **SECTION 5: Firefighting measures**

# 5.1 Extinguishing media

# Suitable extinguishing agents:

Foam

Carbon dioxide

Fire-extinguishing powder

Water spray

#### For safety reasons unsuitable extinguishing agents: Water with full jet

# 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

Silicon oxides

Formaldehyde

Develops readily flammable gases/fumes.

### 5.3 Advice for firefighters

### Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

## Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

# SECTION 6: Accidental release measures

# **6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation For non-emergency personnel

Keep away from ignition sources.

Avoid contact with the eyes and skin.

The usual precautionary measures are to be adhered to when handling chemicals.

For emergency responders Wear protective equipment. Keep unprotected persons away.

# 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

# 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

(Contd. on page 4)



Revision: 05.07.2022 Printing date 24.09.2024 Version: 2.00 (replaces version 1.00)

Trade name: SONAX PROFILINE Headlight Coating

(Contd. of page 3)

#### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

# 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Do not breathe vapour.

Prevent formation of aerosols.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

# 7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Observe local/state/federal regulations.

#### Further information about storage conditions:

Store only in the original receptacle.

Store in cool, dry conditions in well sealed receptacles.

Recommended storage temperature: 20 °C.

Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

With exposure to moisture, product will release methanol.			
CAS: 67-56-1 methanol			
WEL (Great Britain)		in) Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm Sk	
IOELV (EU)		Long-term value: 260 mg/m³, 200 ppm Skin	
DNELs			
CAS: 5593-70-4 Tetrabutyltitanate			
Oral DNEL 3.1		3.75 mg/kg (consumer) (longterm systematic effects)	
Dermal	DNEL	37.5 mg/kg (consumer) (longterm systematic effects)	
Inhalative	DNEL	152 mg/m³ (consumer) (longterm systematic effects)	
	DNEL	127 mg/m³ (worker) (longterm systematic effects)	
CAS: 162303-51-7 Polymer of tetra-n-butyl titanate and water			
Inhalative DNEL 127 mg/m³ (worker) (longterm systematic effects)			
PNECs			
CAS: 5593-70-4 TetrabutyItitanate			
PNEC 65	mg/l (s	ewage plant)	
2.2	25 mg/l	(water) (zeitweise Freisetzung)	
0.08 mg/l (water (fresh water))		(water (fresh water))	

(Contd. on page 5)



Printing date 24.09.2024 Version: 2.00 (replaces version 1.00) Revision: 05.07.2022

Trade name: SONAX PROFILINE Headlight Coating

(Contd. of page 4)

O.008 mg/l (water (sea water))
PNEC 0.069 mg/kg (sediment (fresh water))
0.007 mg/kg (sediment (sea water))

0.017 mg/kg (soil)

CAS: 162303-51-7 Polymer of tetra-n-butyl titanate and water

PNEC 65 mg/l (sewage plant)

0.08 mg/l (water (fresh water))
0.008 mg/l (water (sea water))

PNEC 0.017 mg/kg (gro)

0.069 mg/kg (sediment (fresh water)) 0.007 mg/kg (sediment (sea water))

Additional information: The lists valid during the making were used as basis.

#### 8.2 Exposure controls

#### Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

# Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

# Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace.

Use suitable respiratory protective device in case of insufficient ventilation.

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

[DIN EN 14387]

Hand protection Protective gloves

# Material of gloves

Nitrile rubber, NBR Butyl rubber, BR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

# Penetration time of glove material

Value for the permeation: Level 6 (≥480min)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

# Eye/face protection

Safety glasses

[EN 166]

# SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

**General Information** 

Physical stateFluidColour:ColourlessOdour:Alcohol-likeMelting point/freezing point:Undetermined.

Boiling point or initial boiling point and boiling

range >35 °C (CAS: 897393-56-5 Silicone resin)

**Flammability** Flammable.

Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.

(Contd. on page 6)



Printing date 24.09.2024 Version: 2.00 (replaces version 1.00) Revision: 05.07.2022

Trade name: SONAX PROFILINE Headlight Coating

(Contd. of page 5)

Flash point: 40 °C (DIN EN ISO 13736)

Decomposition temperature:Not determined.pHNot determined.

Viscosity:

Kinematic viscosity at 40 °C 29 mm<sup>2</sup>/s

Solubility

water: Not miscible or difficult to mix.

**Partition coefficient n-octanol/water (log value) Vapour pressure:**Not determined.
Not determined.

Density and/or relative density

Density at 20 °C:0.9-0.92 g/cm³Vapour densityNot determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

**Ignition temperature:** Not determined.

Explosive properties: In use, may form flammable/explosive vapour-air

mixture.

Change in condition

**Evaporation rate** Not determined.

Information with regard to physical hazard classes

ExplosivesVoidFlammable gasesVoidAerosolsVoidOxidising gasesVoidGases under pressureVoid

Flammable liquids Flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Void
Pyrophoric liquids
Pyrophoric solids
Self-heating substances and mixtures
Void

Substances and mixtures, which emit flammable

gases in contact with waterVoidOxidising liquidsVoidOxidising solidsVoidOrganic peroxidesVoidCorrosive to metalsVoidDesensitised explosivesVoid

# SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Fumes can combine with air to form an explosive mixture.

10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products:

With exposure to moisture, product will release methanol.

Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150

°C through oxidation.



Printing date 24.09.2024 Version: 2.00 (replaces version 1.00) Revision: 05.07.2022

Trade name: SONAX PROFILINE Headlight Coating

(Contd. of page 6)

# **SECTION 11: Toxicological information**

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	LD/LC50 values relevant for classification:		
CAS: 134	CAS: 13475-82-6 2,2,4,6,6-pentamethylheptane		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)	
Inhalative	LC 50 / 8h	>5 mg/l (Ratte) (OECD 403)	
CAS: 559	CAS: 5593-70-4 TetrabutyItitanate		
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD 50	5,300 mg/kg (rabbit)	
Inhalative	LD50	20,100 mg/l (rat)	

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

Viscosity: > 20,5mm²/s (40°C)

Based on available data, the classification criteria are not met.

# 11.2 Information on other hazards

#### Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments

Aquatic tox	Aquatic toxicity:			
CAS: 13475	5-82-6 2,2,4,6,6-pentamethylheptane			
LC50 / 96h	>1,000 mg/l (Oncorhynchus mykiss) (OECD 203)			
EC50 / 48h	>1,000 mg/l (Daphnia magna) (OECD 202)			
IC50 / 72h	>1,000 mg/l (Pseudokirchneriella subcapitata) (OECD 201)			
CAS: 5593-70-4 TetrabutyItitanate				
LC50 / 96h	1,825 mg/l (fish) (acute)			
EC10	650 mg/l (bacteria)			
EC50 / 48h	1,300 mg/l (dp) (acute)			
EC50 / 96 h	225 mg/l (algae) (acute)			
12.2 Persistence and degradability				
CAS: 13475-82-6 2,2,4,6,6-pentamethylheptane				

(Contd. on page 8)



Printing date 24.09.2024 Version: 2.00 (replaces version 1.00) Revision: 05.07.2022

Trade name: SONAX PROFILINE Headlight Coating

(Contd. of page 7)

#### 12.3 Bioaccumulative potential

CAS: 13475-82-6 2,2,4,6,6-pentamethylheptane

log Kow 6.96

12.4 Mobility in soil No further relevant information available.

#### 12.5 Results of PBT and vPvB assessment

#### PRT

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

#### vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

#### 12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

#### 12.7 Other adverse effects

### Additional ecological information:

#### General notes:

The product may not be released into the environment without control.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

# SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Recommendation Waste must be disposed of while observing the local, official regulations.

## European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

20 01 13* solvents
--------------------

15 01 10\* packaging containing residues of or contaminated by hazardous substances

### Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

# SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA UN1993

14.2 UN proper shipping name

ADR/RID/ADN

1993 FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C4, 1,3-

BUTADIENE-FREE, TETRABUTYL TITANATE)

IMDG, IATA FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C4, 1,3-BUTADIENE-

FREE, TETRABUTYL TITANATE)

# 14.3 Transport hazard class(es)

# ADR/RID/ADN



Class 3 (F1) Flammable liquids. Label 3

(Contd. on page 9)



Printing date 24.09.2024 Version: 2.00 (replaces version 1.00) Revision: 05.07.2022

Trade name: SONAX PROFILINE Headlight Coating

(Contd. of page 8)

#### IMDG, IATA



Class 3 Flammable liquids.

Label 3

14.4 Packing group

ADR/RID/ADN, IMDG, IATA |||

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Warning: Flammable liquids.

Transport/Additional information:

ADR/RID/ADN

Limited quantities (LQ) 5L Transport category 3 Tunnel restriction code D/E

UN 1993 FLAMMABLE LIQUID, N.O.S. (HYDROCARBONS, C4, 1,3-

BUTADIENE-FREE, TETRABUTYL TITANATE), 3, III

# SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) 37.50 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) P5c FLAMMABLE LIQUIDS

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

# Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

### National regulations:

#### Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

### Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H413 May cause long lasting harmful effects to aquatic life.

(Contd. on page 10)



Printing date 24.09.2024 Version: 2.00 (replaces version 1.00) Revision: 05.07.2022

Trade name: SONAX PROFILINE Headlight Coating

(Contd. of page 9)

Classification according to Regulation (EC) No 1272/2008					
Flammable liquids	On basis of test data				
Skin corrosion/irritation Serious eye damage/irritation Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.				

Date of previous version: 22.04.2021 Version number of previous version: 1.00

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration LC = letal Concentration EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
STOT\_SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

\* Data compared to the previous version altered.