

**Safety data sheet
according to UK REACH**

Printing date 18.09.2024

Version: 6.00 (replaces version 5.00)

Revision: 27.01.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** SONAX Tyre Care**Article number:**

04353000

UFI: 7KT0-00FN-V00Q-Y47G**1.2 Relevant identified uses of the substance or mixture and uses advised against****Application of the substance / the mixture**

Car care product

Detergents

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against None**1.3 Details of the supplier of the safety data sheet****Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS02

Signal word Danger**Hazard statements**

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P271 Use only outdoors or in a well-ventilated area.

(Contd. on page 2)

GB

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 6.00 (replaces version 5.00)

Revision: 27.01.2022

Trade name: SONAX Tyre Care

(Contd. of page 1)

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Formulation consisting of pressurised gas and care components in aqueous solution

Dangerous components:

| | | |
|--|--|--------|
| EC No 926-141-6 Reg.nr.: 01-2119456620-43-xxxx | Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8 ⚠ Asp. Tox. 1, H304, EUH066 | 5-<10% |
| CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx | butane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 5-<10% |
| CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx | propane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 5-<10% |
| CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx | isobutane ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280 | 1-<3% |

Regulation (EC) No 648/2004 on detergents / Labelling for contents

| | |
|--|------------|
| aliphatic hydrocarbons | ≥15 - <30% |
| anionic surfactants, non-ionic surfactants | <5% |
| phenoxyethanol, sodium pyrithione | |

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out into the fresh air.

Remove soiled clothing

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 6.00 (replaces version 5.00)

Revision: 27.01.2022

Trade name: SONAX Tyre Care

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

Foam

Fire-extinguishing powder

Carbon dioxide

Water spray

For safety reasons unsuitable extinguishing agents: Water with full jet**5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO₂)

Silicon oxides

5.3 Advice for firefighters**Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation**For non-emergency personnel**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from ignition sources.

Wear protective clothing.

For emergency responders Wear protective equipment. Keep unprotected persons away.**6.2 Environmental precautions:**

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb liquid components with liquid-binding material.

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

(Contd. on page 4)

GB

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 6.00 (replaces version 5.00)

Revision: 27.01.2022

Trade name: SONAX Tyre Care

(Contd. of page 3)

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Prevent any seepage into the ground.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Protect from frost.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | |
|--------------|--|
| RCP-TWA (EU) | Long-term value: 1200 mg/m ³ , 165 ppm Vapour / Total Hydrocarbons |
|--------------|--|

CAS: 106-97-8 butane

| | |
|---------------------|---|
| WEL (Great Britain) | Short-term value: 1810 mg/m ³ , 750 ppm Long-term value: 1450 mg/m ³ , 600 ppm Carc (if more than 0.1% of buta-1.3-diene) |
|---------------------|---|

| | |
|---------------|----------------------------|
| OEL (Ireland) | Short-term value: 1000 ppm |
|---------------|----------------------------|

CAS: 74-98-6 propane

| | |
|---------------|-------|
| OEL (Ireland) | Asphx |
|---------------|-------|

CAS: 75-28-5 isobutane

| | |
|---------------|----------------------------|
| OEL (Ireland) | Short-term value: 1000 ppm |
|---------------|----------------------------|

Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2020 CoP for the Safety, Health and Welfare at Work

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection Not required in normal cases.

(Contd. on page 5)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 6.00 (replaces version 5.00)

Revision: 27.01.2022

Trade name: SONAX Tyre Care

Eye/face protection Not required in normal cases

(Contd. of page 4)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

| | |
|---|--|
| Physical state | Fluid |
| Colour: | White |
| Odour: | Nearly odourless |
| Melting point/freezing point: | Undetermined. |
| Boiling point or initial boiling point and boiling range | Not applicable, as aerosol. |
| Flammability | Extremely flammable aerosol. |
| Lower and upper explosion limit | |
| Lower: | 1,5 Vol.% (Propellant data) |
| Upper: | 10,9 Vol.% (Propellant data) |
| Flash point: | Not applicable, as aerosol. |
| Decomposition temperature: | Not determined. |
| pH at 20 °C | 8-9 (Active ingredient data) |
| Viscosity: | |
| Kinematic viscosity at 40 °C | <20.5 mm ² /s (Active ingredient data) |
| Solubility | |
| water: | Fully miscible. |
| Partition coefficient n-octanol/water (log value) | Not determined. |
| Vapour pressure: | Not determined. |
| Density and/or relative density | |
| Density at 20 °C: | 0.96-0.98 g/cm ³ (Active ingredient data) |
| Vapour density | Not determined. |

9.2 Other information

| | |
|--|--|
| Appearance: | |
| Form: | Aerosol |
| Important information on protection of health and environment, and on safety. | |
| Ignition temperature: | Product is not selfigniting. |
| Explosive properties: | In use, may form flammable/explosive vapour-air mixture. |
| Change in condition | |
| Evaporation rate | Not applicable. |

Information with regard to physical hazard classes

| | |
|--|---|
| Explosives | Void |
| Flammable gases | Void |
| Aerosols | Positive ignition distance test in line with 31.4 UN RTGD, handbook on test methods and criteria Extremely flammable aerosol. Pressurised container: May burst if heated. |
| Oxidising gases | Void |
| Gases under pressure | Void |
| Flammable liquids | Void |
| Flammable solids | Void |
| Self-reactive substances and mixtures | Void |
| Pyrophoric liquids | Void |
| Pyrophoric solids | Void |
| Self-heating substances and mixtures | Void |
| Substances and mixtures, which emit flammable gases in contact with water | Void |
| Oxidising liquids | Void |
| Oxidising solids | Void |

(Contd. on page 6)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 6.00 (replaces version 5.00)

Revision: 27.01.2022

Trade name: SONAX Tyre Care

(Contd. of page 5)

| | |
|--------------------------------|------|
| Organic peroxides | Void |
| Corrosive to metals | Void |
| Desensitised explosives | Void |

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.

10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | | |
|------------|---------|---|
| Oral | LD50 | >5,000 mg/kg (rat) (OECD 401) |
| Dermal | LD50 | >5,000 mg/kg (rabbit) (OECD 402) |
| Inhalative | LC50/8h | >5,000 mg/m ³ (rat) (OECD 403) |

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxicity:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | |
|----------|--|
| LLO 96 h | 1,000 mg/l (Oncorhynchus mykiss) |
| ELO 48 h | 1,000 mg/l (Daphnia magna) |
| ELO 72 h | 1,000 mg/l (Pseudokirchneriella subcapitata) |

(Contd. on page 7)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 6.00 (replaces version 5.00)

Revision: 27.01.2022

Trade name: SONAX Tyre Care

(Contd. of page 6)

CAS: 106-97-8 butane

| | |
|-------------|-------------------|
| LC50 / 96 h | 27.98 mg/l (fish) |
| EC50 / 4 d | 7.71 mg/l (algae) |

CAS: 74-98-6 propane

| | |
|-------------|-------------------|
| LC50 / 96 h | 27.98 mg/l (fish) |
| EC50 / 96 h | 7.71 mg/l (algae) |

CAS: 75-28-5 isobutane

| | |
|-------------|-------------------|
| LC50 / 96 h | 27.98 mg/l (fish) |
| EC50 / 4 d | 7.71 mg/l (algae) |

12.2 Persistence and degradability

The surface-active substances contained in the product meet the requirement of the EU Detergent Regulation (EC/648/2004) for ultimate biodegradability for surfactants in detergents.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

| | |
|----------------|------------|
| Biodegradation | 69 % (28d) |
|----------------|------------|

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes: The product may not be released into the environment without control.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste must be disposed of while observing the local, official regulations.

European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

| | |
|-----------|--|
| 15 01 10* | packaging containing residues of or contaminated by hazardous substances |
|-----------|--|

| | |
|-----|-----------|
| HP3 | Flammable |
|-----|-----------|

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

| | |
|-------------------------|--------|
| ADR/RID/ADN, IMDG, IATA | UN1950 |
|-------------------------|--------|

14.2 UN proper shipping name

| | |
|-------------|---------------------|
| ADR/RID/ADN | 1950 AEROSOLS |
| IMDG | AEROSOLS |
| IATA | AEROSOLS, flammable |

(Contd. on page 8)

Safety data sheet according to UK REACH

Printing date 18.09.2024

Version: 6.00 (replaces version 5.00)

Revision: 27.01.2022

Trade name: SONAX Tyre Care

(Contd. of page 7)

14.3 Transport hazard class(es)**ADR/RID/ADN**

Class 2 5F Gases.
Label 2.1

IMDG, IATA

Class 2.1 Gases.
Label 2.1

14.4 Packing group**ADR/RID/ADN, IMDG, IATA** Void**14.5 Environmental hazards:****Marine pollutant:** No**14.6 Special precautions for user** Warning: Gases.**Transport/Additional information:****ADR/RID/ADN**

Limited quantities (LQ) 1L
Transport category 2
Tunnel restriction code D

UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**European Directives:****Directive 2010/75/EU (VOC)** 21.73 %**REGULATION (EU) 2019/1148****Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:**Information about limitation of use:**

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning juveniles must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

(Contd. on page 9)

GB

**Safety data sheet
according to UK REACH**

Printing date 18.09.2024

Version: 6.00 (replaces version 5.00)

Revision: 27.01.2022

| |
|------------------------------------|
| Trade name: SONAX Tyre Care |
|------------------------------------|

(Contd. of page 8)

H304 May be fatal if swallowed and enters airways.
EUH066 Repeated exposure may cause skin dryness or cracking.

| |
|---|
| Classification according to Regulation (EC) No 1272/2008 |
|---|

| |
|---|
| Aerosols, Section 2.3.1 On basis of test data |
|---|

Date of previous version: 22.04.2021**Version number of previous version: 5.00****Abbreviations and acronyms:**

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = Lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

: Aerosols – Category 3

Press. Gas (Comp.): Gases under pressure – Compressed gas

Asp. Tox. 1: Aspiration hazard – Category 1

*** Data compared to the previous version altered.**

GB