

Printing date 18.09.2024 Version: 2.00 (replaces version 1.00) Revision: 02 05 2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Electronics & Contact Cleaner

Article number: 04603000

UFI: P9E3-S08T-S00W-R104

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Cleaning agent/ Cleaner

Detergents

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation. Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms







GHS02

GHS07

Signal word Danger

Hazard-determining components of labelling:

C6-7 Alkane/Cycloalkane

propan-2-ol

(Contd. on page 2)



Printing date 18.09.2024 Version: 2.00 (replaces version 1.00) Revision: 02.05.2022

Trade name: SONAX Electronics & Contact Cleaner

(Contd. of page 1)

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.
P280 Wear protective gloves/eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT.

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Preparation of propellent and solvents

CAS: 67-63-0 EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	propan-2-ol ♦ Flam. Liq. 2, H225; ♦ Eye Irrit. 2, H319; STOT SE 3, H336	25-<50%
EC No 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Alternative CAS number: 64742-49-0 Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	25-<50%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide ♦ Press. Gas (Ref. Liq.), H281	3-<5%

– GB



Printing date 18.09.2024 Version: 2.00 (replaces version 1.00) Revision: 02.05.2022

Trade name: SONAX Electronics & Contact Cleaner

CAS: 110-82-7 EINECS: 203-806-2	(Co cyclohexane	ntd. of page 2) 3-<5%
	1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); ♦ Skin Irrit. 2, H315; STOT SE 3, H336	
CAS: 110-54-3 EINECS: 203-777-6 Reg.nr.: 01-2119480412-44-xxxx	n-hexane	1-<3%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

aliphatic hydrocarbons ≥30%

Additional information:

For the wording of the listed hazard phrases refer to section 16.

Hydrocarbon mixture: Benzene content < 0.1%

Cyclohexane is a part of the hydrocarbon mixture. n-Hexane is a part of the hydrocarbon mixture.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out of danger area and lay down.

Take affected persons out into the fresh air.

Remove soiled clothing

After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache Dizziness Nausea Drowsiness Skin irritation Eye irritation

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Foam

Carbon dioxide

Fire-extinguishing powder

Water haze

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

(Contd. on page 4)



Printing date 18.09.2024 Version: 2.00 (replaces version 1.00) Revision: 02.05.2022

Trade name: SONAX Electronics & Contact Cleaner

(Contd. of page 3)

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

For non-emergency personnel

The usual precautionary measures are to be adhered to when handling chemicals.

Do not inhale gases / fumes / aerosols.

Wear protective clothing.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

In case of seepage into the ground inform responsible authorities.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

When using product on electrical parts disconnect them from power supply first. Before re-assembly, let dry for 2 minutes.

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Protect against electrostatic charges.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

(Contd. on page 5)



Printing date 18.09.2024 Version: 2.00 (replaces version 1.00) Revision: 02.05.2022

Trade name: SONAX Electronics & Contact Cleaner

(Contd. of page 4)

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.
Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with lin	nit values that require monitoring at the workplace:		
CAS: 67-63-0 propa	an-2-ol		
WEL (Great Britain)	Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm		
OEL (Ireland)	Short-term value: 400 ppm Long-term value: 200 ppm Sk		
CAS: 124-38-9 cark	oon dioxide		
WEL (Great Britain)	Short-term value: 27400 mg/m³, 15000 ppm Long-term value: 9150 mg/m³, 5000 ppm		
IOELV (EU)	Long-term value: 9000 mg/m³, 5000 ppm		
OEL (Ireland)	Long-term value: 9000 mg/m³, 5000 ppm IOELV		
CAS: 110-82-7 cycl	ohexane		
WEL (Great Britain)	Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm		
IOELV (EU)	Long-term value: 700 mg/m³, 200 ppm		
OEL (Ireland)	Long-term value: 700 mg/m³, 200 ppm IOELV		
CAS: 110-54-3 n-he	CAS: 110-54-3 n-hexane		
WEL (Great Britain)	Long-term value: 72 mg/m³, 20 ppm		
IOELV (EU)	Long-term value: 72 mg/m³, 20 ppm		
OEL (Ireland)	Long-term value: 72 mg/m³, 20 ppm		

Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

IOELV, Sk

IOELV (EU): (EU) 2019/1831

DNELs			
CAS: 67-63-0 propan-2-ol			
Oral	DNEL	26 mg/kg (consumer) (chornic effects (1d))	
Dermal	DNEL	319 mg/kg (consumer) (chronic effects (1d))	
		888 mg/kg (worker) (chronic effects (1d))	
Inhalative	DNEL	89 mg/m³ (consumer) (chronic effects)	
		500 mg/m³ (worker) (chronic effects)	
Hydrocari	bons, C	C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Oral	DNEL	699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)	
Dermal	DNEL	699 mg/kg bw/day (consumer) (chronic exposition / systemi effects)	
		773 mg/kg bw/day (worker) (chronic exposition / systemic effects)	
Inhalative	DNEL	608 mg/m³ (consumer) (chronic exposition / systemic effects)	
		2,035 mg/m³ (worker) (chronic exposition / systemic effects)	

PNECs

CAS: 67-63-0 propan-2-ol

PNEC 140.9 mg/l (sporadic release)

2,251 mg/l (STP)

(Contd. on page 6)



Revision: 02.05.2022 Printing date 18.09.2024 Version: 2.00 (replaces version 1.00)

Trade name: SONAX Electronics & Contact Cleaner

(Contd. of page 5)

140.9 mg/l (water (fresh water)) 140.9 mg/l (water (sea water))

PNEC 28 mg/kg (gro)

552 mg/kg (sediment)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Respiratory protection:

If the occupational exposure limit is exceeded: The following breathing protection is recommended: Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection Protective gloves

Material of gloves Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Penetration time of glove material Value for the permeation: Level 6 (≥480min)

Eye/face protection

Safety glasses [EN 166]

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid Colour: Colourless Odour: Solvent-like Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range 82 °C (CAS: 67-63-0 propan-2-ol) Flammability Extremely flammable aerosol.

Lower and upper explosion limit

Lower: 1 Vol % (Hydrocarbons, C6-C7, n-alkanes, isoalkanes,

cyclics, <5% n-hexane) (Active ingredient data)

13 Vol % (CAS: 67-63-0 propan-2-ol) Upper:

(Active ingredient data) Not applicable, as aerosol.

Flash point: Decomposition temperature:

Not determined. рН Not applicable. Viscosity:

Kinematic viscosity at 20 °C <20.5 mm²/s (DIN 53211/4) (Active ingredient data)

Solubility Not miscible or difficult to mix. water:

Partition coefficient n-octanol/water (log value) Not determined. Vapour pressure: Not determined.

(Contd. on page 7)



Printing date 18.09.2024 Version: 2.00 (replaces version 1.00) Revision: 02.05.2022

Trade name: SONAX Electronics & Contact Cleaner

(Contd. of page 6)

Density and/or relative density

Density at 20 °C: O.74-0.75 g/cm³ Vapour density Not determined.

9.2 Other information

Appearance:

Form: Aerosol

Important information on protection of health and

environment, and on safety.

Ignition temperature: Not determined.

Explosive properties: In use, may form flammable/explosive vapour-air

mixture.

Change in condition

Evaporation rate Not applicable.

Information with regard to physical hazard classes

Explosives Void Flammable gases Void

Aerosols >85% (percent by mass) flammable components,

combustion energy 30 kJ/g Extremely flammable aerosol.

Pressurised container: May burst if heated.

Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void

Substances and mixtures, which emit flammable

gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals Void
Desensitised explosives Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.

10.4 Conditions to avoid

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

An increase in pressure may lead to bursting.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials:

strong oxidizing agents

strong acids

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity Based on available data, the classification criteria are not met.

(Contd. on page 8)



Printing date 18.09.2024 Version: 2.00 (replaces version 1.00) Revision: 02.05.2022

Trade name: SONAX Electronics & Contact Cleaner

(Contd. of page 7) LD/LC50 values relevant for classification: CAS: 67-63-0 propan-2-ol Oral LD50 5,840 mg/kg (rat) Dermal LD50 13,900 mg/kg (rabbit) Inhalative | LC50 / 6 h | >25 mg/l (rat) (OECD 403) Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane >5,000 mg/kg (rat) (OECD 401) Oral LD50 LD50 Dermal >2,920 mg/kg (rabbit) (OECD 402) Inhalative | LC50 / 4h | >20 mg/l (rat) (OECD 403) CAS: 110-82-7 cyclohexane Oral LD50 >5,000 mg/kg (rabbit) Dermal LD50 >2,000 mg/kg (rabbit) Inhalative LC50 / 4h | >32,880 mg/m³ (rat) CAS: 110-54-3 n-hexane Oral LD50 3,200 mg/kg (rat) LD50 Dermal 3,350 mg/kg (rabbit) Inhalative LC50/4d 172 mg/l (rat) Skin corrosion/irritation Causes skin irritation. Serious eye damage/irritation Causes serious eye irritation. Respiratory or skin sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Reproductive toxicity Based on available data, the classification criteria are not met. STOT-single exposure May cause drowsiness or dizziness. STOT-repeated exposure Based on available data, the classification criteria are not met.

Additional toxicological information:

Values relevant for classification:

CAS: 67-63-0 propan-2-ol

Oral NOAEL 400 mg/kg/day (rat)

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

Aspiration hazard Based on available data, the classification criteria are not met.

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

Aquatic toxi	Aquatic toxicity:		
CAS: 67-63-	CAS: 67-63-0 propan-2-ol		
LC50 / 96h	9,640 mg/l (Pimephales promelas)		
LC50 / 24h	9,714 mg/l (daphnia)		
EC50	>100 mg/l (bacteria)		
EC50 / 72h	>100 mg/l (algae)		
LOEC	1,000 mg/l (algae)		

(Contd. on page 9)



Printing date 18.09.2024 Version: 2.00 (replaces version 1.00) Revision: 02.05.2022

Trade name: SONAX Electronics & Contact Cleaner

		(Contd. of page
Hydrocarboi	ns, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
NOEC / 3 d	>0.1-≤1 mg/l (Daphnia magna)	
LL50 / 96h	11.4 mg/l (Oncorhynchus mykiss) (OECD 203)	
EL50 / 48h	3 mg/l (Daphnia magna) (OECD 202)	
EL50 / 72h	30-100 mg/l (Pseudokirchneriella subcapitata) (OECD 201)	
LOEC	0.32 mg/l (Daphnia magna) (21d)	
NOEC / 72 h	3 mg/l (Pseudokirchneriella subcapitata)	
CAS: 110-82	-7 cyclohexane	
LC50 / 96h	4.53 mg/l (Pimephales promelas)	
EC50 / 48h	2.4 mg/l (Daphnia magna)	
EC50 / 72h	3.4 mg/l (Pseudokirchneriella subcapitata)	
CAS: 110-54	-3 n-hexane	
LL50 / 96h	12.51 mg/l (Oncorhynchus mykiss)	
EL50 / 48h	21.85 mg/l (Daphnia magna)	
12.2 Persiste	ence and degradability	
CAS: 67-63-0) propan-2-ol	
Biodegradation	on 53 %	
Hydrocarboi	ns, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
Biodegradation	on 81 % (28d)	
CAS: 110-54	-3 n-hexane	
Biodegradation	on 83 % (10d (ECHA))	
12.3 Bioaccu	ımulative potential	
CAS: 110-82	-7 cyclohexane	
log Kow 3.44	1 (pH: 7, 25°C)	
CAS: 110-54	-3 n-hexane	
log Kow 4 (p	H: 7, 20°C)	
40 4 14 1 111		

12.4 Mobility in soil

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane:

Highly volatile, will partition rapidly to air.

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes: The product may not be released into the environment without control.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10*	packaging containing residues of or contaminated by hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

(Contd. on page 10)



Printing date 18.09.2024 Version: 2.00 (replaces version 1.00) Revision: 02.05.2022

Trade name: SONAX Electronics & Contact Cleaner

HP14 Ecotoxic

(Contd. of page 9)

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA UN1950

14.2 UN proper shipping name

ADR/RID/ADN 1950 AEROSOLS IMDG AEROSOLS

AEROSOLS, flammable

14.3 Transport hazard class(es)

ADR/RID/ADN



IATA

Class 2 5F Gases.

Label 2.1

IMDG, IATA



Class 2.1 Gases.

Label 2.1

14.4 Packing group

ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant:

Yes

absent due to package size =<5l

14.6 Special precautions for user see Sections 6-8

Warning: Gases.

Transport/Additional information:

ADR/RID/ADN

Limited quantities (LQ) 1L Transport category 2 Tunnel restriction code D

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) 95.14 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU)

E2 Hazardous to the Aquatic Environment

P3b FLAMMABLE AEROSOLS

(Contd. on page 11)



Printing date 18.09.2024 Version: 2.00 (replaces version 1.00) Revision: 02.05.2022

Trade name: SONAX Electronics & Contact Cleaner

(Contd. of page 10)

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H281 Contains refrigerated gas; may cause cryogenic burns or injury.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 12	272/2008
Aerosols, Section 2.3.1	On basis of test data
Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Date of previous version: 22.04.2021 Version number of previous version: 1.00

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Aerosol 1: Aerosols – Category 1 : Aerosols – Category 3

Press. Gas (Ref. Liq.): Gases under pressure - Refrigerated liquefied gas

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

(Contd. on page 12)



Printing date 18.09.2024 Revision: 02.05.2022 Version: 2.00 (replaces version 1.00)

Trade name: SONAX Electronics & Contact Cleaner

(Contd. of page 11)

Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

^{*} Data compared to the previous version altered.