

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 1.01 (replaces version 1.00)

Revision: 22.04.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Trade name:** SONAX Zinc Aluminium Spray

**Article number:** 04793000

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

**Application of the substance / the mixture** Anticorrosion additive

#### 1.3 Details of the supplier of the safety data sheet

##### Manufacturer/Supplier:

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

##### Further information obtainable from:

Product safety

E-mail: [erp@sonax.de](mailto:erp@sonax.de)

Phone: + +49 (0) 8431 53 217

##### United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: [info@aaoil.co.uk](mailto:info@aaoil.co.uk)

#### 1.4 Emergency telephone number:

**European Union:** +49 (0) 89 19240 (Poison Centre Munich)

**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222 Extremely flammable aerosol.
	H229 Pressurised container: May burst if heated.
Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
STOT SE 3	H336 May cause drowsiness or dizziness.
Aquatic Chronic 2	H411 Toxic to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

##### Hazard pictograms



GHS02

GHS07

GHS09

**Signal word** Danger

##### Hazard-determining components of labelling:

ethyl acetate

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

acetone

##### Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

(Contd. on page 2)

GB

## Safety data sheet

### according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 1.01 (replaces version 1.00)

Revision: 22.04.2021

Trade name: SONAX Zinc Aluminium Spray

(Contd. of page 1)

H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.  
 P102 Keep out of reach of children.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P261 Avoid breathing spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/eye protection.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.  
 Buildup of explosive mixtures possible without sufficient ventilation.

**2.3 Other hazards****Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

Determination of endocrine-disrupting properties Not applicable.

## SECTION 3: Composition/information on ingredients

**3.2 Mixtures****Description:** Formulation consisting of pressurised gas and solvents with additives**Dangerous components:**

CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether ⚠ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	25 - <50%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	10 - <20%
CAS: 7440-66-6 EINECS: 231-175-3	zinc powder -zinc dust (stabilized) ⚠ Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1)	10 - <20%
EC No 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Alternative CAS number: 64742-49-0 ⚠ Flam. Liq. 2, H225; ⚠ Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	5 - <10%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-xxxx	acetone ⚠ Flam. Liq. 2, H225; ⚠ Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	5 - <10%
CAS: 1330-20-7 EINECS: 215-535-7	xylene ⚠ Flam. Liq. 3, H226; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	3 - <5%
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene ⚠ Flam. Liq. 2, H225; ⚠ STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Acute Tox. 4, H332	1 - <3%
CAS: 110-54-3 EINECS: 203-777-6 Reg.nr.: 01-2119480412-44-xxxx	n-hexane ⚠ Flam. Liq. 2, H225; ⚠ Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; ⚠ Aquatic Chronic 2, H411; ⚠ Skin Irrit. 2, H315; STOT SE 3, H336 Specific concentration limit: STOT RE 2; H373: C ≥ 5 %	0.1 - <1%

(Contd. on page 3)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 1.01 (replaces version 1.00)

Revision: 22.04.2021

**Trade name: SONAX Zinc Aluminium Spray**

(Contd. of page 2)

**Additional information:**

For the wording of the listed hazard phrases refer to section 16.  
n-Hexane is a part of the hydrocarbon mixture.

**SECTION 4: First aid measures****4.1 Description of first aid measures****General information:**

Take affected persons out of danger area and lay down.

Remove soiled clothing

**After inhalation:**

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

**After skin contact:**

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

**After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

**After swallowing:** Do not induce vomiting; call for medical help immediately.

**4.2 Most important symptoms and effects, both acute and delayed**

Headache

Dizziness

Nausea

Drowsiness

Eye irritation

Skin irritation

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing agents:**

Foam

Carbon dioxide

Fire-extinguishing powder

Water haze

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**5.2 Special hazards arising from the substance or mixture**

Can form explosive gas-air mixtures.

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO<sub>2</sub>)

**5.3 Advice for firefighters****Protective equipment:**

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

**Additional information**

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

**SECTION 6: Accidental release measures****6.1 Personal precautions, protective equipment and emergency procedures**

Keep away from ignition sources.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

GB

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 1.01 (replaces version 1.00)

Revision: 22.04.2021

**Trade name: SONAX Zinc Aluminium Spray**

(Contd. of page 3)

### 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

### 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

### 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

#### Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Protect against electrostatic charges.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage:

#### Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

#### Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

#### Further information about storage conditions:

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from heat and direct sunlight.

Recommended storage temperature: 20 °C.

### 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with limit values that require monitoring at the workplace:

##### CAS: 115-10-6 dimethyl ether

WEL (Great Britain) Short-term value: 958 mg/m<sup>3</sup>, 500 ppm

Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

IOELV (EU)

Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm

##### CAS: 141-78-6 ethyl acetate

WEL (Great Britain) Short-term value: 400 ppm

Long-term value: 200 ppm

##### CAS: 67-64-1 acetone

WEL (Great Britain) Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm

Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

(Contd. on page 5)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 1.01 (replaces version 1.00)

Revision: 22.04.2021

Trade name: SONAX Zinc Aluminium Spray

(Contd. of page 4)

IOELV (EU)	Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm	
<b>CAS: 100-41-4 ethylbenzene</b>		
WEL (Great Britain)	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk	
IOELV (EU)	Short-term value: 884 mg/m <sup>3</sup> , 200 ppm Long-term value: 442 mg/m <sup>3</sup> , 100 ppm Skin	
<b>CAS: 110-54-3 n-hexane</b>		
WEL (Great Britain)	Long-term value: 72 mg/m <sup>3</sup> , 20 ppm	
IOELV (EU)	Long-term value: 72 mg/m <sup>3</sup> , 20 ppm	
<b>Regulatory information WEL (Great Britain): EH40/2011</b>		
<b>DNELs</b>		
<b>CAS: 67-64-1 acetone</b>		
Oral	DNEL	62 mg/kg (consumer) (chronic systemic effect)
Dermal	DNEL	186 mg/kg (worker) (chronic systemic effect)
	DNEL	62 mg/kg (worker) (chronic systemic effect)
Inhalative	DNEL	200 mg/m <sup>3</sup> (consumer) (chronic systemic effect) 1,210 mg/m <sup>3</sup> (worker) (chronic systemic effect)
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>		
Oral	DNEL	699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)
Dermal	DNEL	699 mg/kg bw/day (consumer) (chronic exposition / systemic effects) 773 mg/kg bw/day (worker) (chronic exposition / systemic effects)
Inhalative	DNEL	608 mg/m <sup>3</sup> (consumer) (chronic exposition / systemic effects) 2,035 mg/m <sup>3</sup> (worker) (chronic exposition / systemic effects)
<b>PNECs</b>		
<b>CAS: 67-64-1 acetone</b>		
PNEC	100 mg/l (STP) 21 mg/l (water) 10.6 mg/l (water (fresh water)) 1.06 mg/l (water (sea water))	
PNEC	30.4 mg/kg (sediment (fresh water)) 3.04 mg/kg (sediment (sea water)) 29.5 mg/kg (soil)	
<b>Ingredients with biological limit values:</b>		
<b>CAS: 1330-20-7 xylene</b>		
BMGV (Great Britain)	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid	

**Regulatory information** BMGV (Great Britain): EH40/2011**Additional information:** The lists valid during the making were used as basis.**8.2 Exposure controls****Suitable technical control devices**

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

**Appropriate engineering controls** No further data; see section 7.

**Individual protection measures, such as personal protective equipment****General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Wash hands before breaks and at the end of work.

Keep away from foodstuffs, beverages and feed.

(Contd. on page 6)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 1.01 (replaces version 1.00)

Revision: 22.04.2021

Trade name: SONAX Zinc Aluminium Spray

(Contd. of page 5)

**Respiratory protection:**

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

**Hand protection**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

**Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material:  $\geq 0.45$  mm

[EN 374]

**Penetration time of glove material** Value for the permeation: Level 6 ( $\geq 480$ min)**Eye/face protection**

Safety glasses

[EN 166]

**SECTION 9: Physical and chemical properties****9.1 Information on basic physical and chemical properties****General Information****Physical state**

Fluid

**Colour:**

Grey

**Odour:**

Solvent-like

**Melting point/freezing point:**

Undetermined.

**Boiling point or initial boiling point and boiling range**70 - 115 °C  
(Active ingredient data )  
Not applicable.**Flammability****Lower and upper explosion limit****Lower:**

2.7 Vol %

**Upper:**

32 Vol %

**Flash point:**-40 °C  
(Active ingredient data )**Decomposition temperature:**

Not determined.

**pH**

Not applicable.

**Viscosity:****Kinematic viscosity**>20.5 mm<sup>2</sup>/s  
(Active ingredient data )  
Not determined.**Dynamic:****Solubility****water:**

Not miscible or difficult to mix.

**Partition coefficient n-octanol/water (log value)**

Not determined.

**Vapour pressure:**

Not determined.

**Density and/or relative density****Density at 20 °C:**1.1 g/cm<sup>3</sup> (DIN 51757)  
(Active ingredient data )**Relative density**

Not determined.

**Vapour density**

Not determined.

**9.2 Other information****Appearance:****Form:**

Aerosol

**Important information on protection of health and environment, and on safety.****Ignition temperature:**

Not determined.

**Explosive properties:**

In use, may form flammable/explosive vapour-air mixture.

**Change in condition****Evaporation rate**

Not applicable.

(Contd. on page 7)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 1.01 (replaces version 1.00)

Revision: 22.04.2021

Trade name: SONAX Zinc Aluminium Spray

(Contd. of page 6)

**Information with regard to physical hazard classes**

<b>Explosives</b>	Void
<b>Flammable gases</b>	Void
<b>Aerosols</b>	
Extremely flammable aerosol.	
Pressurised container: May burst if heated.	
<b>Oxidising gases</b>	Void
<b>Gases under pressure</b>	Void
<b>Flammable liquids</b>	Void
<b>Flammable solids</b>	Void
<b>Self-reactive substances and mixtures</b>	Void
<b>Pyrophoric liquids</b>	Void
<b>Pyrophoric solids</b>	Void
<b>Self-heating substances and mixtures</b>	Void
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	Void
<b>Oxidising liquids</b>	Void
<b>Oxidising solids</b>	Void
<b>Organic peroxides</b>	Void
<b>Corrosive to metals</b>	Void
<b>Desensitised explosives</b>	Void

**SECTION 10: Stability and reactivity****10.1 Reactivity** No dangerous reactions known.**10.2 Chemical stability** Stable under normal conditions.**10.3 Possibility of hazardous reactions** Develops readily flammable gases/fumes.**10.4 Conditions to avoid**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

An increase in pressure may lead to bursting.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

**10.5 Incompatible materials:** strong oxidizing agents**10.6 Hazardous decomposition products:** No dangerous decomposition products known.**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:****CAS: 115-10-6 dimethyl ether**

Inhalative	LC50/4d	308 mg/l (rat)
------------	---------	----------------

**CAS: 141-78-6 ethyl acetate**

Oral	LD50	4,100 mg/kg (mouse)
		5,620 mg/kg (rat)
		4,934 mg/kg (rabbit)
Dermal	LD50	>20,000 mg/kg (rabbit)
		Inhalative

**CAS: 7440-66-6 zinc powder -zinc dust (stabilized)**

Oral	LD50	>2,000 mg/kg (rat)
Inhalative	LC50/4d	>5,410 mg/l (rat)

**CAS: 67-64-1 acetone**

Oral	LD50	5,800 mg/kg (rat)
------	------	-------------------

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 1.01 (replaces version 1.00)

Revision: 22.04.2021

Trade name: SONAX Zinc Aluminium Spray

(Contd. of page 7)

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane**

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	>20 mg/l (rat) (OECD 403)

**CAS: 1330-20-7 xylene**

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	1,700 mg/kg (rabbit)
Inhalative	ATE	1.5 mg/l (aerosol)
	LC50/4d	21.7 mg/l (rat) (vapour)

**CAS: 100-41-4 ethylbenzene**

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	15,400 mg/kg (rabbit)
Inhalative	ATE	1.5 mg/l (aerosol)
	LC50/4d	17.2 mg/l (rat) (vapour)

**CAS: 110-54-3 n-hexane**

Oral	LD50	3,200 mg/kg (rat)
Dermal	LD50	3,350 mg/kg (rabbit)
Inhalative	LC50/4d	172 mg/l (rat)

**Skin corrosion/irritation**

Long-term exposure causes slight irritation of the skin.  
Repeated exposure may cause skin dryness or cracking.  
Causes skin irritation.

**Serious eye damage/irritation**

May cause slight, short-term eye complaints.  
Causes serious eye irritation.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure** May cause drowsiness or dizziness.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

**Additional toxicological information:****Repeated dose toxicity****CAS: 141-78-6 ethyl acetate**

NOAEL 90-92d | 900 mg/kg/d (rat)

**11.2 Information on other hazards****Endocrine disrupting properties**

None of the ingredients is listed.

**SECTION 12: Ecological information****12.1 Toxicity**

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

**Aquatic toxicity:****CAS: 141-78-6 ethyl acetate**

LC50 / 96h	230 mg/l (Pimephales promelas)
	640 mg/l (Daphnia magna)

(Contd. on page 9)



## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 1.01 (replaces version 1.00)

Revision: 22.04.2021

**Trade name: SONAX Zinc Aluminium Spray**

(Contd. of page 8)

EC50 / 48h	5,600 mg/l ( <i>Scenedesmus subspicatus</i> )
<b>CAS: 7440-66-6 zinc powder -zinc dust (stabilized)</b>	
LC50 / 96h	0.439 mg/l ( <i>Cottus bairdii</i> )
EC50 / 48h	2 mg/l ( <i>Daphnia magna</i> )
<b>CAS: 67-64-1 acetone</b>	
LC50 / 96h	5,540 mg/l ( <i>Oncorhynchus mykiss</i> )
	8,120 mg/l ( <i>Pimephales promelas</i> )
LOEC / 28 d	2,212 mg/l ( <i>Daphnia magna</i> )
NOEC / 28d	2,212 mg/l ( <i>Daphnia magna</i> )
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
LL50 / 96h	11.4 mg/l ( <i>Oncorhynchus mykiss</i> ) (OECD 203)
EL50 / 48h	3 mg/l ( <i>Daphnia magna</i> ) (OECD 202)
EL50 / 72h	30 mg/l ( <i>Pseudokirchneriella subcapitata</i> ) (OECD 201)
LOEC	0.32 mg/l ( <i>Daphnia magna</i> ) (21d)
NOELR 72 h	3 mg/l ( <i>Pseudokirchneriella subcapitata</i> )
NOEC / 21 d	0.17 mg/l ( <i>Daphnia magna</i> )
<b>CAS: 1330-20-7 xylene</b>	
LC50 / 96h	4.2 mg/l ( <i>Oncorhynchus mykiss</i> )
EC50 / 48h	1.8-2.9 mg/l ( <i>Daphnia magna</i> )
ErC50	>100 mg/l ( <i>Selenastrum capricornutum</i> )
<b>CAS: 100-41-4 ethylbenzene</b>	
ErC 50 / 96h	3.6 mg/l
<b>CAS: 110-54-3 n-hexane</b>	
LL50 / 96h	12.51 mg/l ( <i>Oncorhynchus mykiss</i> )
EL50 / 48h	21.85 mg/l ( <i>Daphnia magna</i> )
<b>12.2 Persistence and degradability</b>	
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b>	
Biodegradation	81 % (28d)
<b>CAS: 110-54-3 n-hexane</b>	
Biodegradation	83 % (10d (ECHA))
<b>12.3 Bioaccumulative potential</b>	
<b>CAS: 115-10-6 dimethyl ether</b>	
log POW	0.1 log POW
<b>CAS: 141-78-6 ethyl acetate</b>	
log POW	≤0.24 log POW
<b>CAS: 1330-20-7 xylene</b>	
log Kow	3.12-3.2 log Kow
<b>CAS: 100-41-4 ethylbenzene</b>	
log POW	3.15 log POW
<b>CAS: 110-54-3 n-hexane</b>	
log Kow	4 log Kow (pH: 7, 20°C)

**12.4 Mobility in soil** No further relevant information available.

**12.5 Results of PBT and vPvB assessment**
**PBT:** Not applicable.

**vPvB:** Not applicable.

**12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.

**12.7 Other adverse effects**
**Additional ecological information:**
**General notes:** The product may not be released into the environment without control.

GB

(Contd. on page 10)

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 1.01 (replaces version 1.00)

Revision: 22.04.2021

Trade name: SONAX Zinc Aluminium Spray

(Contd. of page 9)

### SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

**Recommendation** Waste must be disposed of while observing the local, official regulations.

#### European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10\* packaging containing residues of or contaminated by hazardous substances

### SECTION 14: Transport information

#### 14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA

UN1950

#### 14.2 UN proper shipping name ADR/RID/ADN IMDG IATA

1950 AEROSOLS  
AEROSOLS  
AEROSOLS, flammable

#### 14.3 Transport hazard class(es) ADR/RID/ADN



Class 2 5F Gases.  
Label 2.1

#### IMDG, IATA



Class 2.1 Gases.  
Label 2.1

#### 14.4 Packing group ADR/RID/ADN, IMDG, IATA

Void

#### 14.5 Environmental hazards: Marine pollutant:

Yes  
absent due to package size =<5l

#### 14.6 Special precautions for user

see Sections 6-8  
Warning: Gases.

#### 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

#### Transport/Additional information:

#### ADR/RID/ADN

Limited quantities (LQ) 1L  
Transport category 2  
Tunnel restriction code D

#### UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 1.01 (replaces version 1.00)

Revision: 22.04.2021

Trade name: SONAX Zinc Aluminium Spray

(Contd. of page 10)

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

The following substance(s) in this product is (are) identified by CAS number either in countries not subject to the UK REACH regulation or in regulations not yet updated with the new naming convention for hydrocarbon solvents.

#### European Directives:

**Catégorie SEVESO (DIRECTIVE 2012/18/EU)**

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

**REGULATION (EU) 2019/1148**

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

#### National regulations:

#### Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

**15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

#### Classification according to Regulation (EC) No 1272/2008

Aerosols, Section 2.3.1	On basis of test data
Skin corrosion/irritation Serious eye damage/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Version number of previous version: 1.00

#### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 12)

**Safety data sheet**  
**according to 1907/2006/EC, Article 31**

Printing date 15.12.2023

Version: 1.01 (replaces version 1.00)

Revision: 22.04.2021

**Trade name: SONAX Zinc Aluminium Spray**

(Contd. of page 11)

EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
DNEL: Derived No-Effect Level (UK REACH)  
PNEC: Predicted No-Effect Concentration (UK REACH)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
IOELV = indicative occupational exposure limit values  
Flam. Gas 1A: Flammable gases – Category 1A  
Aerosol 1: Aerosols – Category 1  
: Aerosols – Category 3  
Press. Gas (Comp.): Gases under pressure – Compressed gas  
Flam. Liq. 2: Flammable liquids – Category 2  
Flam. Liq. 3: Flammable liquids – Category 3  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2  
Repr. 2: Reproductive toxicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2  
Asp. Tox. 1: Aspiration hazard – Category 1  
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1  
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

GB