

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 6.00 (replaces version 5.00)

Revision: 20.09.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier****Trade name:** SONAX Smoke Reducer**Article number:**

05171000

UFI: FVU3-R0AJ-6002-8Y2A**1.2 Relevant identified uses of the substance or mixture and uses advised against****Application of the substance / the mixture** Oil-and Fuel Additives**1.3 Details of the supplier of the safety data sheet** None**Manufacturer/Supplier:**

SONAX GmbH

Münchener Straße 75

D-86633 Neuburg (Donau)

Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + 49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk**1.4 Emergency telephone number:****European Union:** +49 (0) 89 19240 (Poison Centre Munich)**United Kingdom:** 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS08

Signal word Danger**Hazard-determining components of labelling:**

C11-14 Alkane

Hazard statements

H304 May be fatal if swallowed and enters airways.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 6.00 (replaces version 5.00)

Revision: 20.09.2021

Trade name: SONAX Smoke Reducer

(Contd. of page 1)

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:**

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Additives in mineral oil

Dangerous components:

EC No 926-141-6 Reg.nr.: 01-2119456620-43-xxxx	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8 ⚠ Asp. Tox. 1, H304, EUH066	50-<75%
CAS: 125643-61-0 ELINCS: 406-040-9 Reg.nr.: 01-0000015551-76-xxxx	A mixture of isomers of: C7-9-alkyl-3-(3,5-di-trans-butyl-4-hydroxyphenyl)propionate Aquatic Chronic 4, H413	5-<20%
CAS: 36878-20-3 EINECS: 253-249-4 Reg.nr.: 01-2119488911-28-xxxx	Reaction products of Benzeneamine, N-phenyl- with nonene (branched) Aquatic Chronic 4, H413	5-<15%
	Mineral oil ⚠ Asp. Tox. 1, H304	3-<5%
CAS: 122-39-4 EINECS: 204-539-4 Reg.nr.: 01-2119488966-13-xxxx	diphenylamine ⚠ Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; ⚠ STOT RE 2, H373; ⚠ Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); ⚠ Eye Irrit. 2, H319	<0.25%

Additional information:

The mineral oil contained may be described by one or more of the following: EC No. 265-157-1, Registration No. 01-2119484627-25, Distillates (petroleum), hydrotreated heavy paraffinic; EC No. 265-169-7, Registration No. 01-2119471299-27, Distillates (petroleum), solvent-dewaxed heavy paraffinic; EC No. 265-158-7, Registration No. 01-2119487077-29, Distillates (petroleum), hydrotreated light paraffinic; EC No. 265-159-2, Registration No. 01-2119480132-48, Distillates (petroleum), solvent-dewaxed light paraffinic.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures**General information:**

Take affected persons out of danger area and lay down.

Remove soiled clothing

After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 6.00 (replaces version 5.00)

Revision: 20.09.2021

Trade name: SONAX Smoke Reducer

(Contd. of page 2)

4.2 Most important symptoms and effects, both acute and delayed

Headache
Nausea
Dizziness
Drowsiness
Reddening, drying and crack formation of the skin

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.
Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media****Suitable extinguishing agents:**

Foam
Fire-extinguishing powder
Water haze
Carbon dioxide

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Develops readily flammable gases/fumes.
In case of fire, the following can be released:

Carbon monoxide (CO)
Carbon dioxide (CO₂)
Nitrogen oxides (NO_x)

5.3 Advice for firefighters**Protective equipment:**

Do not inhale explosion gases or combustion gases.
Wear fully protective suit.
Do not enter the hazardous area without a self-contained breathing apparatus.
See Section 8 for information on personal protection equipment.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation**For non-emergency personnel**

Keep away from ignition sources.
Wear protective clothing.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage**7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.**Information about fire - and explosion protection:**

Highly volatile, flammable constituents are released during processing.
Keep ignition sources away - Do not smoke.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 6.00 (replaces version 5.00)

Revision: 20.09.2021

Trade name: SONAX Smoke Reducer

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities**Storage:****Requirements to be met by storerooms and receptacles:** Provide solvent resistant, sealed floor.**Information about storage in one common storage facility:**

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Keep container tightly sealed.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters**Ingredients with limit values that require monitoring at the workplace:****Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics**

RCP-TWA (EU)	Long-term value: 1200 mg/m ³ , 165 ppm Vapour / Total Hydrocarbons
--------------	--

CAS: 122-39-4 diphenylamine

WEL (Great Britain)	Short-term value: 20 mg/m ³ Long-term value: 10 mg/m ³
OEL (Ireland)	Short-term value: 20 mg/m ³ Long-term value: 10 mg/m ³

Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2020 CoP for the Safety, Health and Welfare at Work

Additional information: The lists valid during the making were used as basis.**8.2 Exposure controls****Suitable technical control devices**

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment**General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection Protective gloves**Material of gloves**

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material

Value for the permeation: Level 6 (≥480 min)

The determined penetration times according to EN 16523-1:2015 are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is recommended.

Eye/face protection

Goggles recommended during refilling

(Contd. on page 5)

-GB-

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 6.00 (replaces version 5.00)

Revision: 20.09.2021

Trade name: SONAX Smoke Reducer

[EN 166]

(Contd. of page 4)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state	Fluid
Colour:	Brown
Odour:	Mild
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range	180-270 °C (Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
Flammability	Combustible liquid.
Lower and upper explosion limit	
Lower:	0.6 Vol % (Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
Upper:	7 Vol % (Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics)
Flash point:	82 °C (DIN 51755)
Decomposition temperature:	Not determined.
pH	Not applicable.
Viscosity:	
Kinematic viscosity at 40 °C	<20.5 mm ² /s
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure:	Not determined.
Density and/or relative density	
Density at 15.6 °C:	0.85-086 g/cm ³
Vapour density	Not determined.

9.2 Other information

Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Evaporation rate	Not determined.

Information with regard to physical hazard classes

Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Void
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void

(Contd. on page 6)

-GB-

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 6.00 (replaces version 5.00)

Revision: 20.09.2021

Trade name: SONAX Smoke Reducer

(Contd. of page 5)

Desensitised explosives

Void

SECTION 10: Stability and reactivity**10.1 Reactivity** No dangerous reactions known.**10.2 Chemical stability** Stable under normal conditions.**10.3 Possibility of hazardous reactions** Fumes can combine with air to form an explosive mixture.**10.4 Conditions to avoid**

Protect from heat.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials:

strong oxidizing agents

strong acids

strong alkali

10.6 Hazardous decomposition products: No dangerous decomposition products known.**SECTION 11: Toxicological information****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity** Based on available data, the classification criteria are not met.**LD/LC50 values relevant for classification:**

Oral	ATE	>10,000 mg/kg (calculated)
Dermal	ATE	>5,000 mg/kg (calculated)
Inhalative	ATE	>20 mg/l (calculated)

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Oral	LD50	>5,000 mg/kg (rat) (OECD 401)
Dermal	LD50	>5,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50/8h	>5,000 mg/m ³ (rat) (OECD 403)

Skin corrosion/irritation

Long-term exposure causes slight irritation of the skin.

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

May cause slight, short-term eye complaints.

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.**Germ cell mutagenicity** Based on available data, the classification criteria are not met.**Carcinogenicity** Based on available data, the classification criteria are not met.**Reproductive toxicity** Based on available data, the classification criteria are not met.**STOT-single exposure** Based on available data, the classification criteria are not met.**STOT-repeated exposure** Based on available data, the classification criteria are not met.**Aspiration hazard**Viscosity: < 20,5mm²/s (40°C)

May be fatal if swallowed and enters airways.

11.2 Information on other hazards**Endocrine disrupting properties**

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

GB

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 6.00 (replaces version 5.00)

Revision: 20.09.2021

Trade name: SONAX Smoke Reducer

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

Aquatic toxicity:

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

LLO 96 h	1,000 mg/l (Oncorhynchus mykiss)
ELO 48 h	1,000 mg/l (Daphnia magna)
ELO 72 h	1,000 mg/l (Pseudokirchneriella subcapitata)

CAS: 36878-20-3 Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

LC50 / 4 d	>100 mg/l (Danio rerio)
EC50 / 2 d	>100 mg/l (Daphnia magna)
EC50 / 3 d	600 mg/l (Pseudokirchneriella subcapitata)
EC50 / 0,1 d	>1,000 mg/l (sludge)

Mineral oil

EC50 / 21 d	>10 mg/l (Daphnia magna)
LC50 / 4 d	>100 mg/l (Pimephales promelas)
NOEC / 21 d	>10 mg/l (Daphnia magna)
EC50 / 2 d	>10,000 mg/l (Daphnia magna)
EC50 / 3 d	>100 mg/l (scenedesmus quadricauda)

CAS: 122-39-4 diphenylamine

LC50 / 2 d	2.2 mg/l
EC50 / 2 d	0.31 mg/l (Daphnia magna)
EC50 / 3 d	1.51 mg/l (Pseudokirchneriella subcapitata)

12.2 Persistence and degradability

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

Biodegradation | 69 % (28d)

CAS: 36878-20-3 Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Biodegradation | 0 % (OECD TG 301B)

CAS: 122-39-4 diphenylamine

Biodegradation | 26 % (OECD TG 301 D)

12.3 Bioaccumulative potential

CAS: 36878-20-3 Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

log Kow | >7 (experimentelles Ergebnis)

CAS: 122-39-4 diphenylamine

log Kow | 3.4 (calculated)

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects

Additional ecological information:

General notes: The product may not be released into the environment without control.

GB

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 6.00 (replaces version 5.00)

Revision: 20.09.2021

Trade name: SONAX Smoke Reducer

(Contd. of page 7)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

20 01 13*	solvents
15 01 10*	packaging containing residues of or contaminated by hazardous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA	Void
14.2 UN proper shipping name ADR/RID/ADN, IMDG, IATA	Void
14.3 Transport hazard class(es) ADR/RID/ADN, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

European Directives:

Directive 2010/75/EU (VOC) 54.20 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to
REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))
None of the ingredients is listed.
Annex II - REPORTABLE EXPLOSIVES PRECURSORS
None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.12.2023

Version: 6.00 (replaces version 5.00)

Revision: 20.09.2021

Trade name: SONAX Smoke Reducer

(Contd. of page 8)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

- H301 Toxic if swallowed.
 H304 May be fatal if swallowed and enters airways.
 H311 Toxic in contact with skin.
 H319 Causes serious eye irritation.
 H331 Toxic if inhaled.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H400 Very toxic to aquatic life.
 H410 Very toxic to aquatic life with long lasting effects.
 H413 May cause long lasting harmful effects to aquatic life.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Classification according to Regulation (EC) No 1272/2008

Aspiration hazard Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.
--	--

Date of previous version: 14.09.2020

Version number of previous version: 5.00

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = lethal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Acute Tox. 3: Acute toxicity – Category 3

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard – Category 4

*** Data compared to the previous version altered.**