

Printing date 18.09.2024 Version: 7.01 (replaces version 7.00) Revision: 03.05.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Fuel Injection+Carburettor Cleaner

Article number: 05191000

UFI: 2FY4-Q0GH-M00H-UHWA

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Oil-and Fuel Additives

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against None

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

STOT SE 3 H336 May cause drowsiness or dizziness.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways. Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms







GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

C9-10 Alkane/Cycloalkane

Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)



Printing date 18.09.2024 Version: 7.01 (replaces version 7.00) Revision: 03.05.2023

Trade name: SONAX Fuel Injection+Carburettor Cleaner

(Contd. of page 1)

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Solvent mixture

Dangerous components:		
EC No 927-241-2 Reg.nr.: 01-2119471843-32-xxxx	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	50-<100%
•	Alternative CAS number: 64742-48-9 Flam. Liq. 3, H226;	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out of danger area and lay down.

Remove soiled clothing

After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact:

Remove soiled clothing

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Drowsiness

Nausea

(Contd. on page 3)



Printing date 18.09.2024 Version: 7.01 (replaces version 7.00) Revision: 03.05.2023

Trade name: SONAX Fuel Injection+Carburettor Cleaner

(Contd. of page 2)

Skin irritation

Reddening, drying and crack formation of the skin

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in case of vomiting, danger of entering the lungs.

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Carbon dioxide

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

Develops readily flammable gases/fumes.

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

Nitrogen oxides (NOx)

Aldehyde

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation For non-emergency personnel

Keep away from ignition sources.

Wear protective clothing.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Buildup of explosive mixtures possible without sufficient ventilation.

(Contd. on page 4)



Printing date 18.09.2024 Version: 7.01 (replaces version 7.00) Revision: 03.05.2023

Trade name: SONAX Fuel Injection+Carburettor Cleaner

(Contd. of page 3)

Information about fire - and explosion protection:



Keep ignition sources away - Do not smoke.

Highly volatile, flammable constituents are released during processing. Protect against electrostatic charges.

Use explosion-proof apparatus / fittings and spark-proof tools.

Buildup of explosive mixtures possible without sufficient ventilation.

7.2 Conditions for safe storage, including any incompatibilities Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Store in a cool location.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidising agents.

Observe local/state/federal regulations.

Further information about storage conditions:

Store receptacle in a well ventilated area.

Keep container tightly sealed.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

DNELs	DNELs							
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics								
Oral	DNEL	125 mg/kg bw/day (consumer) (ChronicExposure, SystemicEffects)						
Dermal	DNEL	125 mg/kg bw/day (consumer) (ChronicExposure, SystemiEffects)						
		208 mg/kg bw/day (worker) (ChronicExposure, SystemicEffects)						
Inhalative	DNEL	185 mg/m³ (consumer) (ChronicExposure, SystemicEffects)						
		871 mg/m³ (worker) (ChronicExposure, SystemicEffects)						

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection Protective gloves

(Contd. on page 5)



Printing date 18.09.2024 Version: 7.01 (replaces version 7.00) Revision: 03.05.2023

Trade name: SONAX Fuel Injection+Carburettor Cleaner

(Contd. of page 4)

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)

Eye/face protection

Goggles recommended during refilling

[EN 166]

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical stateFluidColour:ColourlessOdour:Solvent-likeMelting point/freezing point:Undetermined.

Boiling point or initial boiling point and boiling

range 139 °C

Flammability Flammable liquid and vapour.

Lower and upper explosion limit

Lower: 0.6 Vol % (Hydrocarbons, C9-C10, n-alkanes,

isoalkanes, cyclics, <2% aromatics)

Upper: 7 Vol % (Hydrocarbons, C9-C10, n-alkanes,

isoalkanes, cyclics, <2% aromatics)

Flash point: 24 °C (DIN 51755)

Decomposition temperature: Not determined.

pH Not determined.

Viscosity:

Kinematic viscosity at 40 °C <20.5 mm²/s

Solubility

water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value) Not determined.

Vapour pressure at 20 °C: 5 hPa (Hydrocarbons, C9-C10, n-alkanes, isoalkanes,

cyclics, <2% aromatics)

Density and/or relative density

Density at 20 °C: 0.75-0.76 g/cm³ (DIN 51757)

Vapour density Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Ignition temperature:Not determined.Explosive properties:Not determined.

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

Flammable liquids Flammable liquid and vapour.

Flammable solids
Self-reactive substances and mixtures
Void
Pyrophoric liquids
Void
Pyrophoric solids
Void
Self-heating substances and mixtures
Void

(Contd. on page 6)



Printing date 18.09.2024 Version: 7.01 (replaces version 7.00) Revision: 03.05.2023

Trade name: SONAX Fuel Injection+Carburettor Cleaner

(Contd. of page 5)

Substances and mixtures, which emit flammable gases in contact with water

Oxidising liquids

Oxidising solids

Organic peroxides

Corrosive to metals

Desensitised explosives

Void

Void

Void

Void

Void

Void

Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions known.
- 10.2 Chemical stability Stable under normal conditions.
- 10.3 Possibility of hazardous reactions Fumes can combine with air to form an explosive mixture.
- 10.4 Conditions to avoid

Keep ignition sources away - Do not smoke.

Protect from heat.

See Section 7 for information on safe handling.

- 10.5 Incompatible materials: oxidizing agents
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	LD/LC50 values relevant for classification:						
Hydrocar	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics						
Oral	al LD50 >5,000 mg/kg (rat) (OECD 401)						
Dermal	Dermal LD50 >5,000 mg/kg (rabbit) (OECD 402)						
Inhalative	LC50 / 4h	>4,951 mg/m³ (rat) (OECD 403)					

Skin corrosion/irritation

Long-term exposure causes slight irritation of the skin.

Repeated exposure may cause skin dryness or cracking.

Serious eye damage/irritation

May cause slight, short-term eye complaints.

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

Viscosity: $< 20,5mm^2/s$ (40°C)

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

GB



Printing date 18.09.2024 Version: 7.01 (replaces version 7.00) Revision: 03.05.2023

Trade name: SONAX Fuel Injection+Carburettor Cleaner

(Contd. of page 6)

SECTION 12: Ecological information

12.1 Toxicity

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

Aquatic toxic	Aquatic toxicity:								
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics									
LL50 / 96h	LL50 / 96h >10-<30 mg/l (Oncorhynchus mykiss)								
EL50 / 48h >22-<46 mg/l (Daphnia magna)									
EL50 / 72h	EL50 / 72h >1,000 mg/l (Pseudokirchneriella subcapitata)								
NOELR 72 h	NOELR 72 h <1 mg/l (Pseudokirchneriella subcapitata)								

12.2 Persistence and degradability

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradation 89 % (28d)

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Highly volatile, will partition rapidly to air.

12.5 Results of PBT and vPvB assessment

PRT.

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects

Additional ecological information:

General notes: The product may not be released into the environment without control.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

20 01 13*	solvents							
15 01 10*	packaging containing residues of or contaminated by hazardous substances							
HP3 Flammable								
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity							
HP14	Ecotoxic							

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

		 ~ •							•		4.0	
	136	 r	1 9	<i>1</i> • • • • • • • • • • • • • • • • • • •	Inc	m	rt	' In	to	rma	tio	n
_					 -) • A •	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		441		-	

14.1 UN number or ID number ADR/RID/ADN, IMDG, IATAUN3295

14.2 UN proper shipping name

ADR/RID/ADN 3295 HYDROCARBONS, LIQUID, N.O.S. IMDG, IATA HYDROCARBONS, LIQUID, N.O.S.

(Contd. on page 8)



Printing date 18.09.2024 Version: 7.01 (replaces version 7.00) Revision: 03.05.2023

Trade name: SONAX Fuel Injection+Carburettor Cleaner

(Contd. of page 7)

14.3 Transport hazard class(es)

ADR/RID/ADN



Class 3 (F1) Flammable liquids.

Label 3

IMDG, IATA



Class 3 Flammable liquids.

Label 3

14.4 Packing group

ADR/RID/ADN, IMDG, IATA |||

14.5 Environmental hazards: Not applicable.

14.6 Special precautions for user Warning: Flammable liquids.

Transport/Additional information:

ADR/RID/ADN

Limited quantities (LQ) 5L Transport category 3 Tunnel restriction code D/E

UN "Model Regulation": UN 3295 HYDROCARBONS, LIQUID, N.O.S., 3, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) 98.47 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) P5c FLAMMABLE LIQUIDS

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

(Contd. on page 9)



Printing date 18.09.2024 Version: 7.01 (replaces version 7.00) Revision: 03.05.2023

Trade name: SONAX Fuel Injection+Carburettor Cleaner

(Contd. of page 8)

Classification according to Regulation (EC) No 1272/2008								
Flammable liquids	On basis of test data							
Specific target organ toxicity (single exposure) Aspiration hazard Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.							

Date of previous version: 10.05.2022 Version number of previous version: 7.00

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration LC = letal Concentration EC50 = half maximal effective concentration log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent IOELV = indicative occupational exposure limit values

Flam. Liq. 3: Flammable liquids – Category 3 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.