

Printing date 18.09.2024 Version: 1.01 (replaces version 1.00) Revision: 02.08.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX PreStar - EVOLUTION-

Article number:

06787050, 06788000, 06789000 **UFI:** AC15-U0P8-C00E-D1QR

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Car care product Detergents Professional uses

Uses advised against Consumer uses: Private households / general public / consumers

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05

Signal word Danger

Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

(Contd. on page 2)



Printing date 18.09.2024 Version: 1.01 (replaces version 1.00) Revision: 02.08.2024

(Contd. of page 1)

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international

egulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Alkaline tenside solution

Dangerous components:		
CAS: 102-71-6 EINECS: 203-049-8 Reg.nr.: 01-2119486482-31-xxxx	Triethanolamine substance with a Community workplace exposure limit	5-<10%
CAS: 112-34-5 EINECS: 203-961-6 Reg.nr.: 01-2119475104-44-xxxx	2-(2-butoxyethoxy)ethanol	5-<10%
CAS: 1310-73-2 EINECS: 215-185-5 Reg.nr.: 01-2119457892-27-xxxx	sodium hydroxide Met. Corr.1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318 Specific concentration limits: Skin Corr. 1A; H314: C ≥ 5 % Skin Corr. 1B; H314: 2 % ≤ C < 5 % Skin Irrit. 2; H315: 0.5 % ≤ C < 2 % Eye Irrit. 2; H319: 0.5 % ≤ C < 2 %	3-<5%
CAS: 69011-36-5 EC No 931-138-8	isotridecanol,ethoxylated (>5-20EO)	3-<5%
CAS: 15763-76-5 EINECS: 239-854-6 Reg.nr.: 01-2119489411-37-xxxx	sodium-p-cumene sulphonate Alternative CAS numbers: 28348-53-0, 32073-22-6	3-<5%
CAS: 68515-73-1 NLP: 500-220-1 Reg.nr.: 01-2119488530-36-xxxx	Alkyl polyglycoside C8-10 Eye Dam. 1, H318 Specific concentration limits: Eye Dam. 1; H318: C ≥ 10 % Eye Irrit. 2; H319: C ≥ 10 %	1-<3%

Regulation (EC) No 648/2004 on detergents / Labelling for contents		
non-ionic surfactants		≥5 - <15%
perfumes (Tetramethyl Acetylo	ctahydronaphtalenes, MENTHOL)	

Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Immediately remove any clothing soiled by the product. Take affected persons out of danger area and lay down.

After inhalation:

Supply fresh air.

Seek immediate medical advice.

(Contd. on page 3)



Printing date 18.09.2024 Version: 1.01 (replaces version 1.00) Revision: 02.08.2024

(Contd. of page 2)

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek immediate medical advice.

After eye contact:

Rinse opened eye for several minutes under running water.

Seek immediate medical advice.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Eye irritation / Eye damage

Caustic effect on skin and mucous membranes.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

The normal measures for firefighting are to be taken.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation For non-emergency personnel

Wear protective clothing.

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

When diluting always pour product into water and not vice versa.

Information about fire - and explosion protection: The product is not flammable.

(Contd. on page 4)



Printing date 18.09.2024 Version: 1.01 (replaces version 1.00) Revision: 02.08.2024

(Contd. of page 3)

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Provide alkali-resistant floor.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from metals.

Observe local/state/federal regulations.

Further information about storage conditions:

Keep container tightly sealed.

Store receptacle in a well ventilated area.

Protect from frost.

Recommended storage temperature: 20 °C. Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with lin	Ingredients with limit values that require monitoring at the workplace:	
CAS: 102-71-6 Trie	CAS: 102-71-6 Triethanolamine	
OEL (Ireland)	Long-term value: 5 mg/m³	
CAS: 112-34-5 2-(2-	-butoxyethoxy)ethanol	
WEL (Great Britain)	Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm	
IOELV (EU)	Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm	
OEL (Ireland)	Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm IOELV	
CAS: 1310-73-2 soc	CAS: 1310-73-2 sodium hydroxide	
WEL (Great Britain)	Short-term value: 2 mg/m³	
OEL (Ireland)	Short-term value: 2 mg/m³	

Regulatory information

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

WEL (Great Britain): EH40/2020 IOELV (EU): (EU) 2019/1831

DNELs			
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol			
Oral	DNEL	5 mg/kg bw/day (consumer) (chronic systemic effect)	
Dermal	DNEL	83 mg/bw/day (worker) (chronic systemic effect)	
	DNEL	50 mg/kg bw/day (consumer) (chronic systemic effect)	
Inhalative	DNEL	67.5 mg/m³ (worker) (chronic systemic effect)	
	DNEL	67.5 mg/m³ (worker) (chronic locale effects)	
	DNEL	40.5 mg/m³ (consumer) (chronic systemic effect)	
	DNEL	40.5 mg/m³ (consumer) (chronic locale effects)	
CAS: 131	0-73-2	sodium hydroxide	
Inhalative	DNEL	1 mg/m³ (worker) (longterm local effects)	
	DNEL	1 mg/m³ (consumer) (longterm local effects)	
CAS: 157	63-76-5	sodium-p-cumene sulphonate	
Oral	DNEL	3.8 mg/kg bw/day (consumer) (longterm systematic effects)	
Dermal	DNEL	3.8 mg/kg bw/day (consumer) (longterm systematic effects)	
		7.6 mg/kg bw/day (worker) (longterm systematic effects)	
Inhalative	DNEL	13.2 mg/m³ (consumer) (longterm systematic effects)	
		53.6 mg/m³ (worker) (longterm systematic effects)	
			(Contd. on pa



Printing date 18.09.2024 Version: 1.01 (replaces version 1.00) Revision: 02.08.2024

			(Contd. of pag
CAS: 685	15-73-1	Alkyl polyglycoside C8-10	
Oral	DNEL	35.7 mg/kg (consumer) (longterm exposure - systemic effects)	
Dermal	DNEL	357,000 mg/kg (consumer) (longterm exposure - systemic effects)	
	DNEL	595,000 mg/kg (worker) (longterm exposure - systemic effects)	
Inhalative	DNEL	124 mg/m³ (consumer) (longterm exposure - systemic effects)	
		420 mg/m³ (worker) (longterm exposure - systemic effects)	
PNECs			
CAS: 112	34-5 2-	(2-butoxyethoxy)ethanol	
PNEC 20	0 mg/l (STP)	
11	mg/l (w	vater)	
1.1	mg/l (v	vater (fresh water))	
0.1	1 mg/l	(water (sea water))	
PNEC 4.4	mg/kg	(sediment (fresh water))	
0.4	4 mg/k	g (sediment (sea water))	
0.3	2 mg/k	g (soil)	
56	mg/kg	(water)	
CAS: 685	15-73-1	Alkyl polyglycoside C8-10	
PNEC 0.2	?7 mg/l	(sporadic release)	
56	0 mg/l (STP)	
0.1	76 mg/	l (water (fresh water))	
0.0	176 mg	g/l (water (sea water))	
PNEC 11	1.11 mg	g/kg (oral (secondary poisoning))	
0.6	354 mg/	(kg (gro)	
1.5	16 mg/	kg (sediment (fresh water))	
	-	/kg (sediment (sea water))	

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Filter P2

[DIN EN 14387]

Hand protection Protective gloves

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥480min)

Eye/face protection



Tightly sealed goggles

[EN 166]

(Contd. on page 6)



Printing date 18.09.2024 Version: 1.01 (replaces version 1.00) Revision: 02.08.2024

(Contd. of page 5)

Body protection: Alkaline resistant protective clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid Colour: Colourless Odour: Fruit-like Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

>100 °C

Product is not flammable. **Flammability**

Lower and upper explosion limit

Lower: Not applicable Upper: Not applicable Flash point: Not applicable. Decomposition temperature: Not determined. pH at 20 °C 12.5 - 13.5

Viscosity:

<20.5 mm²/s Kinematic viscosity at 40 °C

Solubility

water: Fully miscible. Not determined. Partition coefficient n-octanol/water (log value) Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: 1.11-1.13 g/cm³ Vapour density Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and

environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard classes

Explosives Void Flammable gases Void Aerosols Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void Void

Oxidising solids Organic peroxides Void

Corrosive to metals May be corrosive to metals.

Desensitised explosives Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

(Contd. on page 7)



Printing date 18.09.2024 Version: 1.01 (replaces version 1.00) Revision: 02.08.2024

(Contd. of page 6)

10.3 Possibility of hazardous reactions Exothermic reaction with strong acids

10.4 Conditions to avoid See Section 7 for information on safe handling.

10.5 Incompatible materials:

Store away from metals.

acids

10.6 Hazardous decomposition products: Corrosive gases/vapours

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC5	LD/LC50 values relevant for classification:		
CAS: 11	CAS: 112-34-5 2-(2-butoxyethoxy)ethanol		
Oral	Oral LD50 2,410 mg/kg (mouse) (ECHA)		
Dermal	LD50	2,764 mg/kg (rabbit) (ECHA)	
CAS: 69	CAS: 69011-36-5 isotridecanol,ethoxylated (>5-20EO)		
Oral	LD50	>300-2,000 mg/kg (rat) (OECD 423)	
	ATE	>300-2,000 mg/kg (rat)	
CAS: 18	CAS: 15763-76-5 sodium-p-cumene sulphonate		
Oral	LD50	>7,000 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rat)	

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Additional toxicological information:

Repeated dose toxicity		
CAS: 112	2-34-5 2-(2-butox	yethoxy)ethanol
Oral	NOAEL	250 mg/kg (rat) (ECHA)
Inhalative	NOAEC	0.094 mg/m³ (Ratte) (OECD 413)
CAS: 15763-76-5 sodium-p-cumene sulphonate		p-cumene sulphonate
Oral	NOAEL	>936 mg/kg (rat)
	NOAEL 90-92d	>440 mg/kg/d (OECD 411 Subcronic Dermal Toxicity: 90-day Stucy)

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture

12.1 Toxicity There are no ecotoxicological data available on this mixture.	
Aquatic toxicity:	
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol	
LC50 / 96h 1,300 mg/l (Lepomis macrochirus) (OECD 203)	
EC50 / 48h	>100 mg/l (Daphnia magna) (ECHA)

(Contd. on page 8)



Printing date 18.09.2024 Version: 1.01 (replaces version 1.00) Revision: 02.08.2024

	(Contd. of page 7)
ErC50	1,101 mg/l (Pseudokirchneriella subcapitata) (ECHA)
CAS: 1310-7	73-2 sodium hydroxide
LC50 / 96 h	196 mg/l (fish)
EC50 / 48h	40.4 mg/l (Invertebrates)
CAS: 15763	-76-5 sodium-p-cumene sulphonate
LC50 / 96h	>1,000 mg/l (fish) (EPA OPPTS EPA OTS 797)
EC50/3h	>1,000 mg/l (bacteria) (OECD 209)
EC50 / 48h	>1,000 mg/l (Daphnia magna) (EPA OPPTS EPA OTS 797)
	>100 mg/l (daphnia) (OECD 202)
EC50 / 96 h	>230 mg/l (algae) (EPA OPPTS EPA OTS 797)
NOEC 96h	31 mg/l (algae) (EPA OPPTS)

12.2 Persistence and degradability

The surface-active substances contained in the product meet the requirement of the EU Detregent Regulation (EC/648/2004) for ultimate biodegradability for surfactants in detergents.

CAS: 15763-76-5 sodium-p-cumene sulphonate

Biodegradation 60-100 % (OECD 301 B Ready Biodegradability -. CO2 Evolution)

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PRT

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

12.7 Other adverse effects

Additional ecological information:

General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. The product does not contain organically bounded halogens (AOX-free).

The product does not contain organic complexing agents.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Waste must be disposed of while observing the local, official regulations.

European waste catalogue	
20 01 29*	detergents containing hazardous substances
HP4	Irritant - skin irritation and eye damage

Uncleaned packaging:

15 01 10*: packaging containing residues of or contaminated by dangerous substances

Recommendation:

Packaging may be reused or recycled after cleaning.

15 01 02: plastic packaging

Recommended cleansing agents: Water

SECTION 14: Transport information

14.1 UN number or ID number

ADR/RID/ADN, IMDG, IATA UN1760

(Contd. on page 9)



Printing date 18.09.2024 Version: 1.01 (replaces version 1.00) Revision: 02.08.2024

(Contd. of page 8)

14.2 UN proper shipping name

ADR/RID/ADN

1760 CORROSIVE LIQUID, N.O.S. (N,N-BIS(CARBOXYMETHYL)-

ALANINE, TRISODIUM SALT, SODIUM HYDROXIDE)

IMDG, IATA CORROSIVE LIQUID, N.O.S. (N,N-BIS(CARBOXYMÉTHYL)-ALANINE,

TRISODIUM SALT, SODIUM HYDROXIDE)

14.3 Transport hazard class(es)

ADR/RID/ADN



Class 8 (C9) Corrosive substances.

Label 8

IMDG, IATA



Class 8 Corrosive substances.

Label 8

14.4 Packing group

ADR/RID/ADN, IMDG, IATA III

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Warning: Corrosive substances.

Transport/Additional information:

ADR/RID/ADN

Limited quantities (LQ) 5L Transport category 3 Tunnel restriction code E

UN "Model Regulation": UN 1760 CORROSIVE LIQUID, N.O.S. (N,N-BIS(CARBOXYMETHYL)-

ALANINE, TRISODIUM SALT, SODIUM HYDROXIDE), 8, III

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) not subject to

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB ·



Printing date 18.09.2024 Version: 1.01 (replaces version 1.00) Revision: 02.08.2024

(Contd. of page 9)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

Relevant phrases

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

Classification according to Regulation (EC) No 1272/2008	
Corrosive to metals	Bridging principles
	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Date of previous version: 30.06.2022 Version number of previous version: 1.00

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail)

DGR: Przepisy dotyczące towarów niebezpiecznych - Dangerous Goods Regulations by IATA ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Met. Corr.1: Corrosive to metals – Category 1 Acute Tox. 4: Acute toxicity – Category 4 Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

* Data compared to the previous version altered.