

Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 24.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX AGRO Active Cleaner Alkaline

Article number:

07261410, 07265000, 07267050 **UFI:** V504-10UD-G00U-C16J

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Alkaline cleaner/ detergent

Detergents Professional uses

Uses advised against Do not use for private purposes (household).

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008

Met. Corr.1 H290 May be corrosive to metals.

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS05

Signal word Danger

Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

(Contd. on page 2)



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 24.06.2022

(Contd. of page 1)

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Aqueous tenside solution.

CAS: 68891-38-3	alcohols, C12-14, ethoxylated, sulfates, sodium salts	3-<5%
NLP: 500-234-8	🔷 Eye Dam. 1, H318; 🕔 Skin Irrit. 2, H315; Aquatic Chronic 3,	1
Reg.nr.: 01-2119488639-16-xxxx		
	Specific concentration limits: Eye Dam. 1; H318: C ≥ 10 % Eye Irrit. 2; H319: 5 % ≤ C < 10 %	
CAS: 15763-76-5	sodium-p-cumene sulphonate	3-<5%
INECS: 239-854-6	Alternative CAS numbers: 28348-53-0, 32073-22-6	
Reg.nr.: 01-2119489411-37-xxxx	♠ Eye Irrit. 2, H319	
AS: 1310-58-3	potassium hydroxide	3-<5%
INECS: 215-181-3	♠ Met. Corr.1, H290; Skin Corr. 1A, H314; Eye Dam. 1, H318;	1
eg.nr.: 01-2119487136-33-xxxx	♠ Acute Tox. 4, H302	
	Špecific concentration limits: Skin Corr. 1A; H314: C ≥ 5 %	
	Skin Corr. 1B; H314: 2 % ≤ C < 5 %	
	Skin Irrit. 2; H315: $0.5 \% \le C < 2 \%$	
	Eye Irrit. 2; H319: 0.5 % ≤ C < 2 %	
AS: 112-34-5	2-(2-butoxyethoxy)ethanol] 1-<3%
EINECS: 203-961-6	♠ Eye Irrit. 2, H319	
Reg.nr.: 01-2119475104-44-xxxx		
CAS: 577-11-7	Sodium diisooctyl sulphosuccinate	1-<3%
EINECS: 209-406-4	♦ Eye Dam. 1, H318; ♦ Skin Irrit. 2, H315	1
Reg.nr.: 01-2119491296-29-xxxx		1

4.1 Description of first aid measures

SECTION 4: First aid measures

phosphates, anionic surfactants

General information:

Immediately remove any clothing soiled by the product.

Take affected persons out of danger area and lay down.

After inhalation: Supply fresh air; consult doctor in case of complaints.

Additional information: For the wording of the listed hazard phrases refer to section 16.

After skin contact:

Immediately wash with water and soap and rinse thoroughly.

Seek immediate medical advice.

(Contd. on page 3)

<5%



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 24.06.2022

(Contd. of page 2)

After eye contact:

Rinse opened eye for several minutes under running water.

Seek immediate medical advice.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Eye irritation / Eye damage

Caustic effect on skin and mucous membranes.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

5.3 Advice for firefighters

Protective equipment:

The normal measures for firefighting are to be taken.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation For non-emergency personnel

Wear protective clothing.

Avoid contact with the eyes and skin.

The usual precautionary measures are to be adhered to when handling chemicals.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/surface or ground water.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well ventilated areas.

Open and handle receptacle with care.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Provide alkali-resistant floor.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from metals.

Observe local/state/federal regulations.

Further information about storage conditions:

Keep container tightly sealed.

(Contd. on page 4)



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 24.06.2022

(Contd. of page 3)

Protect from frost.

Recommended storage temperature: 20 °C. Protect from heat and direct sunlight.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

	Ingredients with limit values that require monitoring at the workplace:			
ĺ	CAS: 1310-58-3 po	CAS: 1310-58-3 potassium hydroxide		
Ì	WEL (Great Britain)	Short-term value: 2 mg/m³		
	OEL (Ireland)	Short-term value: 2 mg/m³		
Ì	CAS: 112-34-5 2-(2-	CAS: 112-34-5 2-(2-butoxyethoxy)ethanol		
	WEL (Great Britain)	Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm		
	IOELV (EU)	Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm		
	OEL (Ireland)	Short-term value: 101.2 mg/m³, 15 ppm Long-term value: 67.5 mg/m³, 10 ppm IOELV		

Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

IOELV (EU): (EU) 2019/1831

CAS: 688	91-38-3	alcohols, C12-14, ethoxylated, sulfates, sodium salts
Oral	DNEL	15 mg/kg (VL)
Dermal	DNEL	1,650 mg/kg (VL)
		2,750 mg/kg (worker long-term)
Inhalative	DNEL	52 mg/m³ (VL)
	DNEL	175 mg/m³ (worker long-term)
CAS: 157	63-76-5	sodium-p-cumene sulphonate
Oral	DNEL	3.8 mg/kg bw/day (consumer) (longterm systematic effects)
Dermal	DNEL	3.8 mg/kg bw/day (consumer) (longterm systematic effects)
		7.6 mg/kg bw/day (worker) (longterm systematic effects)
Inhalative	DNEL	13.2 mg/m³ (consumer) (longterm systematic effects)
		53.6 mg/m³ (worker) (longterm systematic effects)
CAS: 131	0-58-3	potassium hydroxide
Inhalative	DNEL	1 mg/m³ (consumer) (long-term/local effects)
	DNEL	1 mg/m³ (worker) (long-term/local effects)
CAS: 112-	34-5 2-	-(2-butoxyethoxy)ethanol
Oral	DNEL	5 mg/kg bw/day (consumer) (chronic systemic effect)
Dermal	DNEL	83 mg/bw/day (worker) (chronic systemic effect)
	DNEL	50 mg/kg bw/day (consumer) (chronic systemic effect)
Inhalative	DNEL	67.5 mg/m³ (worker) (chronic systemic effect)
	DNEL	67.5 mg/m³ (worker) (chronic locale effects)
	DNEL	40.5 mg/m³ (consumer) (chronic systemic effect)
		40.5 mg/m³ (consumer) (chronic locale effects)
CAS: 577-		odium diisooctyl sulphosuccinate
Oral		17.86 mg/kg (vls)
Dermal		267.86 mg/kg bw/day (wls)
		160.71 mg/kg (vls)
Inhalative		1,889.1 mg/m³ (wls)
	DNEL	559.01 mg/m³ (vls)

—— G



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 24.06.2022

(Contd. of page 4) **PNECs** CAS: 68891-38-3 alcohols, C12-14, ethoxylated, sulfates, sodium salts PNEC 10,000 mg/l (sewage plant) 0.24 mg/l (water (fresh water)) 0.024 mg/l (water (sea water)) PNEC 7.5 mg/kg (gro) 0.9168 mg/kg (sediment (fresh water)) 0.09168 mg/kg (sediment (sea water)) CAS: 112-34-5 2-(2-butoxyethoxy)ethanol PNEC 200 mg/l (STP) 11 mg/l (water) 1.1 mg/l (water (fresh water)) 0.11 mg/l (water (sea water)) PNEC 4.4 mg/kg (sediment (fresh water)) 0.44 mg/kg (sediment (sea water)) 0.32 mg/kg (soil) 56 mg/kg (water) CAS: 577-11-7 Sodium diisooctyl sulphosuccinate PNEC 12.2 mg/l (sewage plant) 0.18 mg/l (water (fresh water)) 0.018 mg/l (water (sea water)) PNEC 17.789 mg/kg (sediment (fresh water)) 1.779 mg/kg (sediment (sea water)) 1.04 mg/kg (soil)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Filter P2

Filter P3

[DIN EN 14387]

Hand protection

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥480min)

Eye/face protection



Tightly sealed goggles

[EN 166]

(Contd. on page 6)



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 24.06.2022

Body protection: Alkaline resistant protective clothing

(Contd. of page 5)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid Colour: Colourless Odour: soap scent Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

Undetermined.

Flammability Product is not flammable.

Lower and upper explosion limit

Lower: Not applicable Upper: Not applicable Flash point: Not applicable. Decomposition temperature: Not determined. pH at 20 °C 12.5-13.5

Viscosity:

<20.5 mm²/s Kinematic viscosity at 40 °C

Solubility

water: Fully miscible. Not determined. Partition coefficient n-octanol/water (log value) Vapour pressure: Not determined.

Density and/or relative density

Density at 20 °C: 1.12-1.14 g/cm³ Vapour density Not determined.

9.2 Other information

Appearance:

Form: Fluid

Important information on protection of health and environment, and on safety.

Ignition temperature: Product is not selfigniting.

Explosive properties: Product does not present an explosion hazard.

Change in condition

Evaporation rate Not determined.

Information with regard to physical hazard classes

Explosives Void Flammable gases Void Aerosols Void Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void

Oxidising solids Void Organic peroxides Void

Corrosive to metals May be corrosive to metals.

Desensitised explosives Void

SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

(Contd. on page 7)



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 24.06.2022

(Contd. of page 6)

10.3 Possibility of hazardous reactions Exothermic reaction with strong acids

10.4 Conditions to avoid See Section 7 for information on safe handling.

10.5 Incompatible materials: acids

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC5	LD/LC50 values relevant for classification:		
CAS: 68	CAS: 68891-38-3 alcohols, C12-14, ethoxylated, sulfates, sodium salts		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD 50	>5,000 mg/kg (rat)	
CAS: 15	5763-76	6-5 sodium-p-cumene sulphonate	
Oral	LD50	>7,000 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rat)	
CAS: 13	CAS: 1310-58-3 potassium hydroxide		
Oral	LD50	333 mg/kg (rat)	
CAS: 11	CAS: 112-34-5 2-(2-butoxyethoxy)ethanol		
Oral	LD50	2,410 mg/kg (mouse) (ECHA)	
Dermal	LD50	2,764 mg/kg (rabbit) (ECHA)	
CAS: 57	CAS: 577-11-7 Sodium diisooctyl sulphosuccinate		
Oral	LD50	>2,100 mg/kg (rat)	
Dermal	LD50	>10,000 mg/kg (rat)	

Skin corrosion/irritation Causes severe skin burns and eye damage.

Serious eye damage/irritation Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

Additional toxicological information:

Repeated	Repeated dose toxicity		
CAS: 157	CAS: 15763-76-5 sodium-p-cumene sulphonate		
Oral	NOAEL	>936 mg/kg (rat)	
	NOAEL 90-92d	>440 mg/kg/d (OECD 411 Subcronic Dermal Toxicity: 90-day Stucy)	
CAS: 112	CAS: 112-34-5 2-(2-butoxyethoxy)ethanol		
Oral	NOAEL	250 mg/kg (rat) (ECHA)	
Inhalative	NOAEC	0.094 mg/m³ (Ratte) (OECD 413)	

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 24.06.2022

		(Contd. of page
Aquatic toxicity:		
CAS: 68891-	38-3 alcohols, C12-14, ethoxylated, sulfates, sodium salts	
LC 50	>10-100 mg/l (Leuciscus idus)	
EC0	>100 mg/l (Pseudomonas putida)	
EC50	>100 mg/l (Scenedesmus subspicatus)	
	>10-100 mg/l (Daphnia magna)	
NOEC	>1-10 mg/l (Leuciscus idus)	
	>0.1-1 mg/l (Daphnia magna)	
CAS: 15763-	76-5 sodium-p-cumene sulphonate	
LC50 / 96h	>1,000 mg/l (fish) (EPA OPPTS EPA OTS 797)	
EC50/3h	>1,000 mg/l (bacteria) (OECD 209)	
EC50 / 48h	>1,000 mg/l (Daphnia magna) (EPA OPPTS EPA OTS 797)	
	>100 mg/l (daphnia) (OECD 202)	
EC50 / 96 h	>230 mg/l (algae) (EPA OPPTS EPA OTS 797)	
NOEC 96h	31 mg/l (algae) (EPA OPPTS)	
CAS: 1310-58-3 potassium hydroxide		
LC50 / 96h	80 mg/l (Gambusia affinis)	
LC50 / 24h	165 mg/l (Poecilla reticulata)	
EC 50/15 min 22 mg/l (Photobacterium phosphoreum)		
CAS: 112-34	-5 2-(2-butoxyethoxy)ethanol	
LC50 / 96h	1,300 mg/l (Lepomis macrochirus) (OECD 203)	
EC50 / 48h	>100 mg/l (Daphnia magna) (ECHA)	
ErC50	1,101 mg/l (Pseudokirchneriella subcapitata) (ECHA)	
CAS: 577-11	-7 Sodium diisooctyl sulphosuccinate	
LC50 / 96h	49 mg/l (Danio rerio)	
EC50 / 48h	15.2 mg/l (Daphnia magna)	
EC50 / 72h	82.5 mg/l (algae)	
12.2 Parciet	ence and degradability	

12.2 Persistence and degradability

The surface-active substances contained in the product meet the requirement of the EU Detregent Regulation (EC/648/2004) for ultimate biodegradability for surfactants in detergents.

CAS: 15763-76-5 sodium-p-cumene sulphonate	
Biodegradation	60-100 % (OECD 301 B Ready Biodegradability CO2 Evolution)

12.3 Bioaccumulative potential No further relevant information available.

12.4 Mobility in soil No further relevant information available.

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

The product does not contain substances with endocrine disrupting properties.

12.7 Other adverse effects

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

The product does not contain organically bounded halogens (AOX-free).

The product does not contain organic complexing agents.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 24.06.2022

(Contd. of page 8)

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Waste must be disposed of while observing the local, official regulations.

Γ	European waste catalogue		
Γ	20 01 29*	detergents containing hazardous substances	
Ī	HP4	Irritant - skin irritation and eye damage	

Uncleaned packaging:

15 01 10*: packaging containing residues of or contaminated by dangerous substances

Recommendation: Packaging may be reused or recycled after cleaning.

Recommended cleansing agents: Water

SECTION 14: Transport information

14.1 UN number or ID number ADR/RID/ADN, IMDG, IATAUN1719

14.2 UN proper shipping name

ADR/RID/ADN

1719 CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE,

N,N-BIS(CARBOXYMETHYL)-ALANINE, TRISODIUM SALT)

CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE, N,N-

BIS(CARBOXYMETHYL)-ALANINĖ, TRISODIUM SALT)

14.3 Transport hazard class(es)

ADR/RID/ADN

IMDG, IATA



Label

Class 8 (C5) Corrosive substances.

8

IMDG, IATA



Class 8 Corrosive substances.

Label 8

14.4 Packing group

ADR/RID/ADN, IMDG, IATA III

14.5 Environmental hazards:

Marine pollutant: No

14.6 Special precautions for user Warning: Corrosive substances.

Transport/Additional information:

ADR/RID/ADN

Limited quantities (LQ) 5L Transport category 3 Tunnel restriction code E

UN 1719 CAUSTIC ALKALI LIQUID, N.O.S. (POTASSIUM HYDROXIDE,

N,N-BIS(CARBOXYMETHYL)-ALANINE, TRISODIUM SALT), 8, III

-GB



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 24.06.2022

(Contd. of page 9)

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) not subject to

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H290 May be corrosive to metals.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008		
Corrosive to metals	Bridging principles	
	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

Date of previous version: 25.05.2022 Version number of previous version: 4.00

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the

International Transport of Dangerous Goods by Rail) NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration LC = letal Concentration

EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International

Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (ÚK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Met. Corr.1: Corrosive to metals - Category 1

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

* Data compared to the previous version altered.