

Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 21 07 2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: SONAX Cockpit Spray Vanilla-fresh (Greece)

Article number: 342300-560

1.2 Relevant identified uses of the substance or mixture and uses advised against

Application of the substance / the mixture

Car care product Detergents

Consumer uses: Private households / general public / consumers

Professional uses

Uses advised against There is currently no information available on this.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

Further information obtainable from:

Product safety

E-mail: erp@sonax.de

Phone: + +49 (0) 8431 53 217

United Kingdom:

Anglo American Oil Company Ltd

58 Holton Road, Holton Heath Trading Park, Poole, Dorset, BH16 6LT

Telephone: (+44) 01929 551557

Email: info@aaoil.co.uk

1.4 Emergency telephone number:

European Union: +49 (0) 89 19240 (Poison Centre Munich)

United Kingdom: 0344 892 0111 (UK NPIS)

Members of Public in England, Scotland and Wales can contact NHS 111/NHS 24 by dialling 111

In Northern Ireland, contact your local GP

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms







GHS02

GHS07

Signal word Danger

Hazard-determining components of labelling:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Hazard statements

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

(Contd. on page 2)



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 21.07.2022

Trade name: SONAX Cockpit Spray Vanilla-fresh (Greece)

(Contd. of page 1)

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

2.3 Other hazards

Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB.

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as VPVR

Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Formulation consisting of pressurised gas and solvents with additives

Dangerous components:		
EC No 921-024-6 Reg.nr.: 01-2119475514-35-xxxx	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Alternative CAS number: 64742-49-0 Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	50-<75%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane ♦ Flam. Gas 1A, H220; Press. Gas (Comp.), H280	10-<15%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 110-82-7 EINECS: 203-806-2 Reg.nr.: 01-2119463273-41-xxxx	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400 (M=1); Aquatic Chronic 1, H410 (M=1); Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	3-<5%
CAS: 110-54-3 EINECS: 203-777-6 Reg.nr.: 01-2119480412-44-xxxx	n-hexane	1-<3%

Regulation (EC) No 648/2004 on detergents / Labelling for contents	
aliphatic hydrocarbons	≥30%
perfumes	

(Contd. on page 3)



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 21.07.2022

Trade name: SONAX Cockpit Spray Vanilla-fresh (Greece)

(Contd. of page 2)

Additional information:

Hydrocarbon mixture:

Benzene content < 0.1%

Any entry in the EC-column that begins with the number "9" is a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. See Section 15 for additional CAS number information for the substance.

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Take affected persons out of danger area and lay down.

Remove soiled clothing

After inhalation:

Supply fresh air.

In the event of irritation of the respiratory tract, dizziness, nausea or unconsciousness, call medical assistance immediately.

After skin contact:

Wash the areas of skin affected with water and a mild detergent.

If symptoms persist consult doctor.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Nausea

Drowsiness

Skin irritation

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents:

Foam

Fire-extinguishing powder

Carbon dioxide

Water haze

For safety reasons unsuitable extinguishing agents: Water with full jet

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO)

Carbon dioxide (CO2)

5.3 Advice for firefighters

Protective equipment:

Do not inhale explosion gases or combustion gases.

Wear fully protective suit.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation

(Contd. on page 4)



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 21.07.2022

Trade name: SONAX Cockpit Spray Vanilla-fresh (Greece)

(Contd. of page 3)

For non-emergency personnel

Keep away from ignition sources.

Do not inhale gases / fumes / aerosols.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. **Information about fire - and explosion protection:**



Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

Highly volatile, flammable constituents are released during processing.

Fumes can combine with air to form an explosive mixture.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Provide solvent resistant, sealed floor.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Observe local/state/federal regulations.

Further information about storage conditions:

Protect from heat and direct sunlight.

Store receptacle in a well ventilated area.

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with lin	Ingredients with limit values that require monitoring at the workplace:		
	CAS: 106-97-8 butane		
WEL (Great Britain)	Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)		
OEL (Ireland)	Short-term value: 1000 ppm		
CAS: 74-98-6 propane			
OEL (Ireland)	Asphx		

(Contd. on page 5)



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 21.07.2022

Trade name: SONAX Cockpit Spray Vanilla-fresh (Greece)

	(Contd. of page 4)		
CAS: 110-82-7 cycl	CAS: 110-82-7 cyclohexane		
WEL (Great Britain)	Short-term value: 1050 mg/m³, 300 ppm Long-term value: 350 mg/m³, 100 ppm		
IOELV (EU)	Long-term value: 700 mg/m³, 200 ppm		
OEL (Ireland)	Long-term value: 700 mg/m³, 200 ppm IOELV		
CAS: 75-28-5 isobu	tane		
OEL (Ireland)	Short-term value: 1000 ppm		
CAS: 110-54-3 n-he	CAS: 110-54-3 n-hexane		
WEL (Great Britain)	Long-term value: 72 mg/m³, 20 ppm		
IOELV (EU)	Long-term value: 72 mg/m³, 20 ppm		
OEL (Ireland)	Long-term value: 72 mg/m³, 20 ppm IOELV, Sk		

Regulatory information

WEL (Great Britain): EH40/2020

OEL (Ireland): 2021 CoP for the Safety, Health and Welfare at Work

IOELV (EU): (EU) 2019/1831

DNELs		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	DNEL	699 mg/kg bw/day (consumer) (chronic exposition / systemic effects)
Dermal	DNEL	699 mg/kg bw/day (consumer) (chronic exposition / systemi effects)
		773 mg/kg bw/day (worker) (chronic exposition / systemic effects)
Inhalative	DNEL	608 mg/m³ (consumer) (chronic exposition / systemic effects)
		2,035 mg/m³ (worker) (chronic exposition / systemic effects)

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection:

If the occupational exposure limit is exceeded:

The following breathing protection is recommended:

Respiratory filter for organic gases and vapours (Type A)

Identification colour: Brown

[DIN EN 14387]

Hand protection Protective gloves

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

[EN 374]

Penetration time of glove material Value for the permeation: Level 6 (≥480min)

Eye/face protection

Safety glasses

[EN 166]

GB



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 21.07.2022

Trade name: SONAX Cockpit Spray Vanilla-fresh (Greece)

(Contd. of page 5)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Physical state Fluid Colour: Yellowish Vanilla Odour: Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

>34 °C range

(Active ingredient data) **Flammability** Extremely flammable aerosol.

Lower and upper explosion limit

Lower: 1 Vol % (Hydrocarbons, C6-C7, n-alkanes, isoalkanes,

cyclics, <5% n-hexane)

8.5 Vol % (CAS: 106-97-8 butane) Upper:

Flash point: Not applicable, as aerosol.

Decomposition temperature: Not determined. Not applicable. pН

Viscosity:

Kinematic viscosity at 40 °C <20.5 mm²/s

(Active ingredient data)

Solubility

water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value) Not determined. Not determined. Vapour pressure:

Density and/or relative density

Density at 20 °C: 0.73-0.74 g/cm3 (Active ingredient data)

Vapour density Not determined.

9.2 Other information

Appearance:

Form: Aerosol

Important information on protection of health and

environment, and on safety.

Ignition temperature: Not determined.

Explosive properties: In use, may form flammable/explosive vapour-air

mixture.

Change in condition

Evaporation rate Not applicable.

Information with regard to physical hazard classes

Explosives Void Flammable gases Void

Aerosols

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Oxidising gases Void Gases under pressure Void Flammable liquids Void Flammable solids Void Self-reactive substances and mixtures Void Pyrophoric liquids Void Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable Void

gases in contact with water Oxidising liquids Void Oxidising solids Void Organic peroxides Void Corrosive to metals Void

(Contd. on page 7)



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 21.07.2022

Trade name: SONAX Cockpit Spray Vanilla-fresh (Greece)

(Contd. of page 6)

Desensitised explosives

Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions known.
- 10.2 Chemical stability Stable under normal conditions.
- 10.3 Possibility of hazardous reactions Develops readily flammable gases/fumes.
- 10.4 Conditions to avoid

An increase in pressure may lead to bursting.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Keep ignition sources away - Do not smoke.

See Section 7 for information on safe handling.

10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50	LD/LC50 values relevant for classification:		
Hydrocari	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)	
Dermal	LD50	>2,920 mg/kg (rabbit) (OECD 402)	
Inhalative	LC50 / 4h	>20 mg/l (rat) (OECD 403)	
CAS: 110-	CAS: 110-82-7 cyclohexane		
Oral	LD50	>5,000 mg/kg (rabbit)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
Inhalative	LC50 / 4h	>32,880 mg/m³ (rat)	
CAS: 110-54-3 n-hexane			
Oral	LD50	3,200 mg/kg (rat)	
Dermal	LD50	3,350 mg/kg (rabbit)	
Inhalative	LC50/4d	172 mg/l (rat)	

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with health effects.

None of the ingredients is listed.

GB



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 21.07.2022

Trade name: SONAX Cockpit Spray Vanilla-fresh (Greece)

(Contd. of page 7)

SECTION 12: Ecological information

12.1 Toxicity

Product is considered to be harmful to aquatic organisms. May have long-term harmful effects in aquatic environments.

Aquatic toxicity:		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane		
NOEC/3d	>0.1-≤1 mg/l (Daphnia magna)	
LL50 / 96h	11.4 mg/l (Oncorhynchus mykiss) (OECD 203)	
EL50 / 48h	3 mg/l (Daphnia magna) (OECD 202)	
EL50 / 72h	30-100 mg/l (Pseudokirchneriella subcapitata) (OECD 201)	
LOEC	0.32 mg/l (Daphnia magna) (21d)	
NOEC / 72 h	3 mg/l (Pseudokirchneriella subcapitata)	
CAS: 106-97	-8 butane	
LC50 / 96 h	27.98 mg/l (fish)	
EC50 / 4 d	7.71 mg/l (algae)	
CAS: 74-98-6		
LC50 / 96 h	27.98 mg/l (fish)	
EC50 / 96 h	7.71 mg/l (algae)	
CAS: 110-82	-7 cyclohexane	
LC50 / 96h	4.53 mg/l (Pimephales promelas)	
EC50 / 48h	2.4 mg/l (Daphnia magna)	
EC50 / 72h	3.4 mg/l (Pseudokirchneriella subcapitata)	
CAS: 75-28-		
LC50 / 96 h	27.98 mg/l (fish)	
EC50 / 4 d	7.71 mg/l (algae)	
CAS: 110-54		
LL50 / 96h	12.51 mg/l (Oncorhynchus mykiss)	
EL50 / 48h	21.85 mg/l (Daphnia magna)	
12.2 Persiste	ence and degradability	
•	ns, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
	on 81 % (28d)	
CAS: 110-54-3 n-hexane		
Biodegradation 83 % (10d (ECHA))		
12.3 Bioaccu	imulative potential	
	-7 cyclohexane	
log Kow 3.44 (pH: 7, 25°C)		
CAS: 110-54-3 n-hexane		
log Kow 4 (p	H: 7, 20°C)	

12.4 Mobility in soil

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane:

Highly volatile, will partition rapidly to air.

12.5 Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix conatins less than 0.1% of any substances classified as vPvB

12.6 Endocrine disrupting properties

According to the current state of scientific knowledge, there is no data for the product regarding endocrine disrupting properties with effects on the environment.

(Contd. on page 9)



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 21.07.2022

Trade name: SONAX Cockpit Spray Vanilla-fresh (Greece)

(Contd. of page 8)

12.7 Other adverse effects

Additional ecological information:

General notes: The product may not be released into the environment without control.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste must be disposed of while observing the local, official regulations.

European waste catalogue

Disposal / product + Disposal / contaminated packaging

15 01 10* packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA	UN1950
14.2 UN proper shipping name	
ADR/RID/ADN	1950 AEROSOLS
IMDG	AEROSOLS (Petroleum Distillates), MARINE POLLUTAN
IATA 14.3 Transport hazard class(es)	AEROSOLS, flammable



 Class
 2 5F Gases.

 Label
 2.1

IMDG, IATA



Class 2.1 Gases. Label 2.1

14.4 Packing group

ADR/RID/ADN, IMDG, IATA Void

14.5 Environmental hazards:

Marine pollutant: Yes

absent due to package size =<5l

14.6 Special precautions for user

Hazard identification number (Kemler code):

Stowage Code

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of

living quarters.

Warning: Gases.

Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1

except for division 1.4.

(Contd. on page 10)



ADR/RID/ADN

Transport category

Safety data sheet according to UK REACH

Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 21.07.2022

Trade name: SONAX Cockpit Spray Vanilla-fresh (Greece)

(Contd. of page 9) For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2. Transport/Additional information: Limited quantities (LQ) 1L 2 Tunnel restriction code D UN "Model Regulation": UN1950, AEROSOLS, 2.1

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

Directive 2010/75/EU (VOC) 94.12 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU)

P3a FLAMMABLE AEROSOLS

E2 Hazardous to the Aquatic Environment

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning pregnant and lactating women must be observed.

Employment restrictions concerning juveniles must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H361f Suspected of damaging fertility.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008		
Aerosols, Section 2.3.1	On basis of test data	
Skin corrosion/irritation Specific target organ toxicity (single exposure) Hazardous to the aquatic environment - long-term (chronic) aquatic hazard	The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.	

Date of previous version: 22.04.2021 Version number of previous version: 4.00

(Contd. on page 11)



Printing date 18.09.2024 Version: 5.00 (replaces version 4.00) Revision: 21.07.2022

Trade name: SONAX Cockpit Spray Vanilla-fresh (Greece)

(Contd. of page 10)

Abbreviations and acronyms:

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concer

LC = letal Concentration EC50 = half maximal effective concentration

log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (UK REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Actions - Category 3

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard — Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard — Category 2

* Data compared to the previous version altered.